

oprobit — Ordered probit regression

[Description](#)
[Options](#)
[References](#)

[Quick start](#)
[Remarks and examples](#)
[Also see](#)

[Menu](#)
[Stored results](#)

[Syntax](#)
[Methods and formulas](#)

Description

`oprobit` fits ordered probit models of ordinal variable *depvar* on the independent variables *indepvars*. The actual values taken on by the dependent variable are irrelevant, except that larger values are assumed to correspond to “higher” outcomes.

Quick start

Ordinal probit model of *y* on *x1* and categorical variables *a* and *b*

```
oprobit y x1 i.a i.b
```

Model of *y* on *x1* and a one-period lagged value of *x1* using `tsset` data

```
oprobit y x1 L.x1
```

Same as above, but calculate results for each level of *catvar* and save statistics to *myfile.dta*

```
statsby, by(catvar) saving(myfile): oprobit y x1 L.x1
```

Menu

Statistics > Ordinal outcomes > Ordered probit regression

Syntax

```
oprobit deivar [indepvars] [if] [in] [weight] [, options]
```

<i>options</i>	Description
Model	
<code>offset(<i>varname</i>)</code>	include <i>varname</i> in model with coefficient constrained to 1
<code>constraints(<i>constraints</i>)</code>	apply specified linear constraints
SE/Robust	
<code>vce(<i>vcetype</i>)</code>	<i>vcetype</i> may be <code>oim</code> , <code>opg</code> , <code>robust</code> , <code>cluster <i>clustvar</i></code> , <code>bootstrap</code> , or <code>jackknife</code>
Reporting	
<code>level(#)</code>	set confidence level; default is <code>level(95)</code>
<code>nocnsreport</code>	do not display constraints
<code>display_options</code>	control columns and column formats, row spacing, line width, display of omitted variables and base and empty cells, and factor-variable labeling
Maximization	
<code>maximize_options</code>	control the maximization process; seldom used
<code>collinear</code>	keep collinear variables
<code>coeflegend</code>	display legend instead of statistics
<i>indepvars</i> may contain factor variables; see [U] 11.4.3 Factor variables .	
<i>deivar</i> and <i>indepvars</i> may contain time-series operators; see [U] 11.4.4 Time-series varlists .	
<code>bayes</code> , <code>bootstrap</code> , <code>by</code> , <code>collect</code> , <code>fmm</code> , <code>fp</code> , <code>jackknife</code> , <code>mfp</code> , <code>mi estimate</code> , <code>nestreg</code> , <code>rolling</code> , <code>statsby</code> , <code>stepwise</code> , and <code>svy</code> are allowed; see [U] 11.1.10 Prefix commands . For more details, see [BAYES] bayes: oprobit and [FMM] fmm: oprobit .	
<code>vce(bootstrap)</code> and <code>vce(jackknife)</code> are not allowed with the <code>mi estimate</code> prefix; see [MI] mi estimate .	
Weights are not allowed with the <code>bootstrap</code> prefix; see [R] bootstrap .	
<code>vce()</code> and weights are not allowed with the <code>svy</code> prefix; see [SVY] svy .	
<code>fweights</code> , <code>iwweights</code> , and <code>pweights</code> are allowed; see [U] 11.1.6 weight .	
<code>collinear</code> and <code>coeflegend</code> do not appear in the dialog box.	
See [U] 20 Estimation and postestimation commands for more capabilities of estimation commands.	

Options

Model

`offset(varname)`, `constraints(constraints)`; see [R] **Estimation options**.

SE/Robust

`vce(vcetype)` specifies the type of standard error reported, which includes types that are derived from asymptotic theory (`oim`, `opg`), that are robust to some kinds of misspecification (`robust`), that allow for intragroup correlation (`cluster clustvar`), and that use bootstrap or jackknife methods (`bootstrap`, `jackknife`); see [R] **vce_option**.

Reporting

level(#); see [R] [Estimation options](#).

nocnsreport; see [R] [Estimation options](#).

display_options: [noci](#), [nopvalues](#), [noomitted](#), [vsquish](#), [noemptycells](#), [baselevels](#), [allbaselevels](#), [nofvlabel](#), [fvwrap\(#\)](#), [fvwrapon\(style\)](#), [cformat\(%fmt\)](#), [pformat\(%fmt\)](#), [sformat\(%fmt\)](#), and [nolstretch](#); see [R] [Estimation options](#).

Maximization

maximize_options: [difficult](#), [technique\(algorithm_spec\)](#), [iterate\(#\)](#), [\[no\]log](#), [trace](#), [gradient](#), [showstep](#), [hessian](#), [showtolerance](#), [tolerance\(#\)](#), [ltolerance\(#\)](#), [nrtolerance\(#\)](#), [nonrto](#)lerance, and [from\(init_specs\)](#); see [R] [Maximize](#). These options are seldom used.

The following options are available with `oprobit` but is not shown in the dialog box:

[collinear](#), [coeflegend](#); see [R] [Estimation options](#).

Remarks and examples

stata.com

An ordered probit model is used to estimate relationships between an ordinal dependent variable and a set of independent variables. An *ordinal* variable is a variable that is categorical and ordered, for instance, “poor”, “good”, and “excellent”, which might indicate a person’s current health status or the repair record of a car. If there are only two outcomes, see [R] [logistic](#), [R] [logit](#), and [R] [probit](#). This entry is concerned only with more than two outcomes. If the outcomes cannot be ordered (for example, residency in the north, east, south, or west), see [R] [mlogit](#). This entry is concerned only with models in which the outcomes can be ordered. See [R] [logistic](#) for a list of related estimation commands.

In ordered probit, an underlying score is estimated as a linear function of the independent variables and a set of cutpoints. The probability of observing outcome i corresponds to the probability that the estimated linear function, plus random error, is within the range of the cutpoints estimated for the outcome:

$$\Pr(\text{outcome}_j = i) = \Pr(\kappa_{i-1} < \beta_1 x_{1j} + \beta_2 x_{2j} + \cdots + \beta_k x_{kj} + u_j \leq \kappa_i)$$

u_j is assumed to be normally distributed. In either case, we estimate the coefficients $\beta_1, \beta_2, \dots, \beta_k$ together with the cutpoints $\kappa_1, \kappa_2, \dots, \kappa_{I-1}$, where I is the number of possible outcomes. κ_0 is taken as $-\infty$, and κ_I is taken as $+\infty$. All of this is a direct generalization of the ordinary two-outcome probit model.

► Example 1

In [example 2](#) of [R] [ologit](#), we use a variation of the automobile dataset (see [U] [1.2.2 Example datasets](#)) to analyze the 1977 repair records of 66 foreign and domestic cars. We use ordered logit to explore the relationship of `rep77` in terms of `foreign` (origin of manufacture), `length` (a proxy for size), and `mpg`. Here we fit the same model using ordered probit rather than ordered logit:

```

. use https://www.stata-press.com/data/r18/fullauto
(Automobile models)

. oprobit rep77 foreign length mpg

Iteration 0:  Log likelihood = -89.895098
Iteration 1:  Log likelihood = -78.106316
Iteration 2:  Log likelihood = -78.020086
Iteration 3:  Log likelihood = -78.020025
Iteration 4:  Log likelihood = -78.020025

Ordered probit regression

Log likelihood = -78.020025

Number of obs =    66
LR chi2(3)     =   23.75
Prob > chi2    = 0.0000
Pseudo R2     = 0.1321

```

rep77	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
foreign	1.704861	.4246796	4.01	0.000	.8725037	2.537217
length	.0468675	.012648	3.71	0.000	.022078	.0716571
mpg	.1304559	.0378628	3.45	0.001	.0562463	.2046656
/cut1	10.1589	3.076754			4.128577	16.18923
/cut2	11.21003	3.107527			5.119389	17.30067
/cut3	12.54561	3.155233			6.361467	18.72975
/cut4	13.98059	3.218793			7.671874	20.28931

We find that foreign cars have better repair records, as do larger cars and cars with better mileage ratings.

◀

Stored results

oprobit stores the following in `e()`:

Scalars

<code>e(N)</code>	number of observations
<code>e(N_cdd)</code>	number of completely determined observations
<code>e(k_cat)</code>	number of categories
<code>e(k)</code>	number of parameters
<code>e(k_aux)</code>	number of auxiliary parameters
<code>e(k_eq)</code>	number of equations in <code>e(b)</code>
<code>e(k_eq_model)</code>	number of equations in overall model test
<code>e(k_dv)</code>	number of dependent variables
<code>e(df_m)</code>	model degrees of freedom
<code>e(r2_p)</code>	pseudo- R^2
<code>e(ll)</code>	log likelihood
<code>e(ll_0)</code>	log likelihood, constant-only model
<code>e(N_clust)</code>	number of clusters
<code>e(chi2)</code>	χ^2
<code>e(p)</code>	p -value for model test
<code>e(rank)</code>	rank of <code>e(V)</code>
<code>e(ic)</code>	number of iterations
<code>e(rc)</code>	return code
<code>e(converged)</code>	1 if converged, 0 otherwise

Macros

<code>e(cmd)</code>	oprobit
<code>e(cmdline)</code>	command as typed
<code>e(depvar)</code>	name of dependent variable
<code>e(wtype)</code>	weight type

<code>e(wexp)</code>	weight expression
<code>e(title)</code>	title in estimation output
<code>e(clustvar)</code>	name of cluster variable
<code>e(offset)</code>	linear offset variable
<code>e(chi2type)</code>	Wald or LR; type of model χ^2 test
<code>e(vce)</code>	<i>vcetype</i> specified in <code>vce()</code>
<code>e(vcetype)</code>	title used to label Std. err.
<code>e(opt)</code>	type of optimization
<code>e(which)</code>	max or min; whether optimizer is to perform maximization or minimization
<code>e(ml_method)</code>	type of ml method
<code>e(user)</code>	name of likelihood-evaluator program
<code>e(technique)</code>	maximization technique
<code>e(properties)</code>	b V
<code>e(predict)</code>	program used to implement <code>predict</code>
<code>e(marginsdefault)</code>	default <code>predict()</code> specification for <code>margins</code>
<code>e(asbalanced)</code>	factor variables <code>fvset</code> as <code>asbalanced</code>
<code>e(asobserved)</code>	factor variables <code>fvset</code> as <code>asobserved</code>

Matrices

<code>e(b)</code>	coefficient vector
<code>e(Cns)</code>	constraints matrix
<code>e(ilog)</code>	iteration log (up to 20 iterations)
<code>e(gradient)</code>	gradient vector
<code>e(cat)</code>	category values
<code>e(V)</code>	variance–covariance matrix of the estimators
<code>e(V_modelbased)</code>	model-based variance

Functions

<code>e(sample)</code>	marks estimation sample
------------------------	-------------------------

In addition to the above, the following is stored in `r()`:

Matrices

<code>r(table)</code>	matrix containing the coefficients with their standard errors, test statistics, <i>p</i> -values, and confidence intervals
-----------------------	--

Note that results stored in `r()` are updated when the command is replayed and will be replaced when any *r*-class command is run after the estimation command.

Methods and formulas

See *Methods and formulas* of [R] `ologit`.

References

- Aitchison, J., and S. D. Silvey. 1957. The generalization of probit analysis to the case of multiple responses. *Biometrika* 44: 131–140. <https://doi.org/10.2307/2333245>.
- Bauldry, S., J. Xu, and A. S. Fullerton. 2018. `gencrm`: A new command for generalized continuation-ratio models. *Stata Journal* 18: 924–936.
- Cameron, A. C., and P. K. Trivedi. 2005. *Microeconometrics: Methods and Applications*. New York: Cambridge University Press.
- Canette, I. 2013. Fitting ordered probit models with endogenous covariates with Stata’s `gsem` command. *The Stata Blog: Not Elsewhere Classified*. <http://blog.stata.com/2013/11/07/fitting-ordered-probit-models-with-endogenous-covariates-with-statas-gsem-command/>.
- Chiburis, R., and M. Lokshin. 2007. Maximum likelihood and two-step estimation of an ordered-probit selection model. *Stata Journal* 7: 167–182.
- De Luca, G., and V. Perotti. 2011. Estimation of ordered response models with sample selection. *Stata Journal* 11: 213–239.

- Drukker, D. M. 2016. An ordered-probit inverse probability weighted (IPW) estimator. *The Stata Blog: Not Elsewhere Classified*. <http://blog.stata.com/2016/09/13/an-ordered-probit-inverse-probability-weighted-ipw-estimator/>.
- Huismans, J., J. W. Nijenhuis, and A. Sirchenko. 2022. A mixture of ordered probit models with endogenous switching between two latent classes. *Stata Journal* 22: 557–596.
- Long, J. S. 1997. *Regression Models for Categorical and Limited Dependent Variables*. Thousand Oaks, CA: Sage.
- Long, J. S., and J. Freese. 2014. *Regression Models for Categorical Dependent Variables Using Stata*. 3rd ed. College Station, TX: Stata Press.
- Miranda, A., and S. Rabe-Hesketh. 2006. Maximum likelihood estimation of endogenous switching and sample selection models for binary, ordinal, and count variables. *Stata Journal* 6: 285–308.
- Smith, E. K., M. G. Lacy, and A. Mayer. 2019. Performance simulations for categorical mediation: Analyzing khb estimates of mediation in ordinal regression models. *Stata Journal* 19: 913–930.
- Stewart, M. B. 2004. Semi-nonparametric estimation of extended ordered probit models. *Stata Journal* 4: 27–39.
- Williams, R. 2010. Fitting heterogeneous choice models with `oglm`. *Stata Journal* 10: 540–567.
- Xu, J., and J. S. Long. 2005. Confidence intervals for predicted outcomes in regression models for categorical outcomes. *Stata Journal* 5: 537–559.

Also see

- [R] **oprobit postestimation** — Postestimation tools for `oprobit`
- [R] **heckoprobit** — Ordered probit model with sample selection
- [R] **hetoprobit** — Heteroskedastic ordered probit regression
- [R] **logistic** — Logistic regression, reporting odds ratios
- [R] **mlogit** — Multinomial (polytomous) logistic regression
- [R] **mprobit** — Multinomial probit regression
- [R] **ologit** — Ordered logistic regression
- [R] **probit** — Probit regression
- [R] **zioprobit** — Zero-inflated ordered probit regression
- [BAYES] **bayes: oprobit** — Bayesian ordered probit regression
- [CM] **cmoprobit** — Rank-ordered probit choice model
- [ERM] **eoprobit** — Extended ordered probit regression
- [FMM] **fmm: oprobit** — Finite mixtures of ordered probit regression models
- [ME] **meoprobit** — Multilevel mixed-effects ordered probit regression
- [MI] **Estimation** — Estimation commands for use with `mi` estimate
- [SVY] **svy estimation** — Estimation commands for survey data
- [XT] **xtoprobit** — Random-effects ordered probit models
- [U] **20 Estimation and postestimation commands**

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).