

Example 6 — Linear regression[Description](#)[Remarks and examples](#)[Also see](#)

Description

Linear regression is demonstrated using `auto.dta`:

```
. sysuse auto  
(1978 automobile data)
```

See *Structural models 1: Linear regression* in [SEM] **Intro 5** for background.

Remarks and examples

stata.com

Remarks are presented under the following headings:


- Fitting linear regression models*
- Displaying standardized results*
- Fitting the model with the Builder*

Fitting linear regression models

The first two examples in [R] **regress** are

```
. regress mpg weight c.weight#c.weight foreign  
. regress, beta
```

This model corresponds to



To fit this model with `sem`, we type

```
. generate weight2 = weight^2
. sem (mpg <- weight weight2 foreign)
Endogenous variables
  Observed: mpg
Exogenous variables
  Observed: weight weight2 foreign
Fitting target model:
Iteration 0:  Log likelihood = -1909.8206
Iteration 1:  Log likelihood = -1909.8206
Structural equation model                                Number of obs = 74
Estimation method: ml
Log likelihood = -1909.8206
```

	OIM				
	Coefficient	std. err.	z	P> z	[95% conf. interval]
Structural					
mpg					
weight	-.0165729	.0038604	-4.29	0.000	-.0241392 -0.0090067
weight2	1.59e-06	6.08e-07	2.62	0.009	4.00e-07 2.78e-06
foreign	-2.2035	1.03022	-2.14	0.032	-4.222695 -1.1843056
_cons	56.53884	6.027559	9.38	0.000	44.72504 68.35264
var(e.mpg)	10.19332	1.675772			7.385485 14.06865

Warning: The LR test of model vs. saturated is not reported because the fitted model is not full rank. There appears to be 1 more fitted parameter than the data can support.

Notes:

1. We wished to include variable `weight2` in our model. Because `sem` does not allow Stata's factor-variable notation, we first had to `generate` new variable `weight2`.
2. Reported coefficients match those reported by `regress`.
3. Reported standard errors (SEs) differ slightly from those reported by `regress`. For instance, the SE for `foreign` is reported here as 1.03, whereas `regress` reported 1.06. SEM is an asymptotic estimator, and `sem` divides variances and covariances by $N = 74$, the number of observations. `regress` provides unbiased finite-sample estimates and divides by $N - k - 1 = 74 - 3 - 1 = 70$. Note that $1.03\sqrt{74/70} = 1.06$.
4. `sem` reports z statistics whereas `regress` reports t statistics.
5. Reported confidence intervals differ slightly between `sem` and `regress` because of the $(N - k - 1)/N$ issue.
6. `sem` reports the point estimate of `e.mpg` as 10.19332. `regress` reports the root MSE as 3.2827. And $\sqrt{10.19332 \times 74/70} = 3.2827$.
7. The warning at the bottom of the output indicates that the fitted model is not of full rank. Although this model is theoretically identified, the scale of variable `weight` causes the model to be less than full rank. If we rescale `weight`, say, by dividing by 100, we will not receive this warning.

Displaying standardized results

To obtain standardized coefficients from `regress`, you specify the `beta` option. To obtain standardized coefficients from `sem`, you specify the `standardized` option.

```
. sem, standardized
Structural equation model                               Number of obs = 74
Estimation method: ml
Log likelihood = -1909.8206
```

Standardized	OIM				[95% conf. interval]	
	Coefficient	std. err.	z	P> z		
Structural						
mpg						
weight	-2.226321	.4950378	-4.50	0.000	-3.196577	-1.256064
weight2	1.32654	.498261	2.66	0.008	.3499662	2.303113
foreign	-.17527	.0810378	-2.16	0.031	-.3341011	-.0164389
_cons	9.839209	.9686872	10.16	0.000	7.940617	11.7378
var(e.mpg)						
	.308704	.0482719			.2272168	.4194152

Warning: The LR test of model vs. saturated is not reported because the fitted model is not full rank. There appears to be 1 more fitted parameter than the data can support.

`regress` simply reports standardized coefficients in an extra column. All other results are reported in unstandardized form. `sem` updates the entire output with the standardized values.

Fitting the model with the Builder

Use the diagram above for reference.

1. Open the dataset and create the additional variable `weight2`.


In the Command window, type

```
. use https://www.stata-press.com/data/r18/auto
. generate weight2 = weight^2
```

2. Open a new Builder diagram.

Select menu item **Statistics > SEM (structural equation modeling) > Model building and estimation**.

3. Create the regression component for the `mpg` outcome.


Select the Add regression component tool, , and then click in the center of the diagram.

In the resulting dialog box,

- a. select `mpg` in the *Dependent variable* control;
- b. select `weight`, `weight2`, and `foreign` by using the *Independent variables* control;
- c. select `Left` in the *Independent variables' direction* control;
- d. click on **OK**.

If you wish, move this component by clicking on any variable and dragging it.

4. Estimate.

Click on the **Estimate** button, , in the Standard Toolbar, and then click on **OK** in the resulting *SEM estimation options* dialog box.

5. Show standardized estimates.

From the SEM Builder menu, select **View > Standardized estimates**.

You can open a completed diagram in the Builder by typing

```
. webgetsem sem_regress
```

Also see

[SEM] [Example 12](#) — Seemingly unrelated regression

[SEM] [Example 38g](#) — Random-intercept and random-slope models (multilevel)

[SEM] [Example 43g](#) — Tobit regression

[SEM] [Example 44g](#) — Interval regression

[SEM] [sem](#) — Structural equation model estimation command

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).