

expand — Duplicate observations[Description](#)
[Option](#)[Quick start](#)
[Remarks and examples](#)[Menu](#)
[References](#)[Syntax](#)
[Also see](#)

Description

`expand` replaces each observation in the dataset with n copies of the observation, where n is equal to the required expression rounded to the nearest integer. If the expression is less than 1 or equal to *missing*, it is interpreted as if it were 1, and the observation is retained but not duplicated.

Quick start

Duplicate each observation 3 times, resulting in the original and 2 copies

```
expand 3
```

Duplicate each observation the number of times stored in `v`

```
expand v
```

Same as above, but flag duplicated observations using generated `newv`

```
expand v, generate(newv)
```

Same as above, but only duplicate observations where `catvar` equals 4

```
expand v if catvar==4, generate(newv)
```

Menu

Data > Create or change data > Other variable-transformation commands > Duplicate observations

Syntax

```
expand [=] exp [if] [in][, generate(newvar) ]
```

Option

`generate(newvar)` creates new variable *newvar* containing 0 if the observation originally appeared in the dataset and 1 if the observation is a duplicate. For instance, after an `expand`, you could revert to the original observations by typing `keep if newvar==0`.

Remarks and examples

[stata.com](https://www.stata.com)

► Example 1

`expand` is, admittedly, a strange command. It can, however, be useful in tricky programs or for reformatting data for survival analysis (see examples in [R] [Eptab](#)). Here is a silly use of `expand`:

```
. use https://www.stata-press.com/data/r18/expandxmpl
. list
```

	n	x
1.	-1	1
2.	0	2
3.	1	3
4.	2	4
5.	3	5

```
. expand n
(1 negative count ignored; observation not deleted)
(1 zero count ignored; observation not deleted)
(3 observations created)
. list
```

	n	x
1.	-1	1
2.	0	2
3.	1	3
4.	2	4
5.	3	5
6.	2	4
7.	3	5
8.	3	5

The new observations are added to the end of the dataset. `expand` informed us that it created 3 observations. The first 3 observations were not replicated because `n` was less than or equal to 1. `n` is 2 in the fourth observation, so `expand` created one replication of this observation, bringing the total number of observations of this type to 2. `expand` created two replications of observation 5 because `n` is 3.

Because there were 5 observations in the original dataset and because `expand` adds new observations onto the end of the dataset, we could now undo the expansion by typing `drop in 6/1`.

References

- Cox, N. J. 2013. *Stata tip 114: Expand paired dates to pairs of dates*. *Stata Journal* 13: 217–219.
- . 2014. *Stata tip 119: Expanding datasets for graphical ends*. *Stata Journal* 14: 230–235.
- Huber, C. 2014. How to simulate multilevel/longitudinal data. *The Stata Blog: Not Elsewhere Classified*. <http://blog.stata.com/2014/07/18/how-to-simulate-multilevellongitudinal-data/>.

Also see

- [D] **contract** — Make dataset of frequencies and percentages
- [D] **expandcl** — Duplicate clustered observations
- [D] **fillin** — Rectangularize dataset

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).