connectstyle - Choices for how points are connected

Description Syntax Remarks and examples Also see

Description

connectstyle specifies if and how points in a scatter are to be connected, for example, via straight lines or stairsteps.

connectstyle is specified inside the connect() option which is allowed, for instance, with scatter:

. scatter ..., connect(connectstylelist) ...

Here a *connectstylelist* is allowed. A *connectstylelist* is a sequence of *connectstyles* separated by spaces. Shorthands are allowed to make specifying the list easier; see [G-4] *stylelists*.

Syntax

connectstyle	Synonym	Description
none	i	do not connect
direct	1	connect with straight lines
ascending	L	direct, but only if $x_{j+1} \ge x_j$
stairstep	J	flat, then vertical
stepstair		vertical, then flat

Other connectstyles may be available; type

. graph query connectstyle

to obtain the full list installed on your computer.

Remarks and examples

stata.com

Points are connected in the order of the data, so be sure that data are in the desired order (which is usually ascending value of x) before specifying the connect(connectstyle) option. Commands that provide connect() also provide a sort option, which will sort by the x variable for you.

connect(1) is the most common choice.

connect(J) is an appropriate way to connect the points of empirical cumulative distribution functions (CDFs).

Also see

[G-3] connect_options — Options for connecting points with lines

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on citing Stata documentation.