

if — if (exp) ... else ...

[Description](#)[Syntax](#)[Remarks and examples](#)[Also see](#)

Description

`if` evaluates the expression, and if it is true (evaluates to a nonzero number), `if` executes the statement or statement block that immediately follows it; otherwise, `if` skips the statement or block.

`if ... else` evaluates the expression, and if it is true (evaluates to a nonzero number), `if` executes the statement or statement block that immediately follows it and skips the statement or statement block following the `else`; otherwise, it skips the statement or statement block immediately following it and executes the statement or statement block following the `else`.

Syntax

```
if (exp) stmt1
```

```
if (exp) stmt1
else stmt2
```

```
if (exp) {
    stmts1
}
else {
    stmts2
}
```

```
if (exp1) ...
else if (exp2) ...
else if (exp3) ...
...
else ...
```

where `exp`, `exp1`, `exp2`, `exp3`, ... must evaluate to real scalars.

Remarks and examples

[stata.com](#)

`if` followed by multiple `elses` is interpreted as being nested, that is,

```
if (exp1) ...
else if (exp2) ...
else if (exp3) ...
...
else ...
```

is equivalent to

```
if (exp1) ...
else {
  if (exp2) ...
  else {
    if (exp3) ...
    else {
      ...
    }
  }
}
```

Also see

[M-2] [Intro](#) — Language definition

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).