

op_arith — Arithmetic operators

Description Diagnostics	Syntax Also see	Remarks and examples	Conformability
----------------------------	--------------------	----------------------	----------------

Description

The above operators perform basic arithmetic.

Syntax

$a + b$	addition
$a - b$	subtraction
$a * b$	multiplication
a / b	division
$a \wedge b$	power
$-a$	negation

where a and b may be numeric scalars, vectors, or matrices.

Remarks and examples

stata.com

Also see [M-2] [op_colon](#) for the `:+`, `:-`, `:*`, and `:/` operators. Colon operators have relaxed conformability restrictions.

The `*` and `:*` multiplication operators can also perform string duplication—`3*"a" = "aaa"`—see [M-5] [strdup\(\)](#).

Conformability

$a + b, a - b:$

$a:$	$r \times c$
$b:$	$r \times c$
$result:$	$r \times c$

$a * b:$

$a:$	$k \times n$	$k \times n$	1×1
$b:$	$n \times m$	1×1	$n \times m$
$result:$	$k \times m$	$k \times n$	$n \times m$

$a / b:$

$a:$	$r \times c$
$b:$	1×1
$result:$	$r \times c$

$a \wedge b:$

$a:$	1×1
$b:$	1×1
$result:$	1×1

$-a$:
 a: $r \times c$
 result: $r \times c$

Diagnostics

All operators return missing when arguments are missing.

$a*b$ with a : $k \times 0$ and b : $0 \times m$ returns a $k \times m$ matrix of zeros.

a/b returns missing when $b=0$ or when a/b would result in overflow.

a^b returns a real when both a and b are real; thus, $(-4)^.5$ evaluates to missing, whereas $(-4+0i)^.5$ evaluates to $2i$.

a^b returns missing on overflow.

Also see

[M-2] [exp](#) — Expressions

[M-2] [Intro](#) — Language definition

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

