

Dmatrix() — Duplication matrix

[Description](#) [Syntax](#) [Remarks and examples](#) [Conformability](#)
[Diagnostics](#) [Reference](#) [Also see](#)

Description

`Dmatrix(n)` returns the $n^2 \times n(n+1)/2$ duplication matrix D for which $D \cdot \text{vech}(X) = \text{vec}(X)$, where X is an arbitrary $n \times n$ symmetric matrix.

Syntax

real matrix `Dmatrix(real scalar n)`

Remarks and examples

stata.com

Duplication matrices are frequently used in computing derivatives of functions of symmetric matrices. Section 9.5 of [Lütkepohl \(1996\)](#) lists many useful properties of duplication matrices.

Conformability

`Dmatrix(n)`:
n: 1×1
result: $n^2 \times n(n+1)/2$

Diagnostics

`Dmatrix(n)` aborts with error if n is less than 0 or is missing. n is interpreted as `trunc(n)`.

Reference

Lütkepohl, H. 1996. *Handbook of Matrices*. New York: Wiley.

Also see

[M-5] [Kmatrix\(\)](#) — Commutation matrix

[M-5] [Lmatrix\(\)](#) — Elimination matrix

[M-5] [vec\(\)](#) — Stack matrix columns

[M-4] [Standard](#) — Functions to create standard matrices

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

