

st_numscalar() — Obtain values from and put values into Stata scalars

Description	Syntax	Remarks and examples	Conformability
Diagnostics	Also see		

Description

`st_numscalar(name)` returns the value of the specified Stata numeric scalar, or it returns `J(0,0,.)` if the scalar does not exist.

`st_numscalar(name, value)` sets or resets the value of the specified numeric scalar, assuming `value != J(0,0,.)`. `st_numscalar(name, value)` deletes the specified scalar if `value == J(0,0,.)`. `st_numscalar("x", J(0,0,..))` erases the scalar `x`, or it does nothing if scalar `x` did not exist.

`st_strscalar(name)` returns the value of the specified Stata string scalar, or it returns `J(0,0,"")` if the scalar does not exist.

`st_strscalar(name, value)` sets or resets the value of the specified scalar, assuming `value != J(0,0,"")`. `st_strscalar(name, value)` deletes the specified scalar if `value == J(0,0,"")`. `st_strscalar("x", J(0,0,""))` erases the scalar `x`, or it does nothing if scalar `x` did not exist.

Concerning deletion of a scalar, it does not matter whether you code `st_numscalar(name, J(0,0,..))` or `st_strscalar(name, J(0,0,""))`; both yield the same result.

`st_numscalar(name, value, hcat)` and `st_numscalar_hcat(name)` are used to set and query the `hcat` corresponding to an `e()` or `r()` value. They are also rarely used. See [R] **Stored results** and [P] **return** for more information.

Syntax

```

real    st_numscalar(string scalar name)
void   st_numscalar(string scalar name, real value)
void   st_numscalar(string scalar name, real value, string scalar hcat)
string  st_numscalar_hcat(string scalar name)

string  st_strscalar(string scalar name)
void   st_strscalar(string scalar name, string value)

```

where

1. Functions allow `name` to be

- a. global scalar such as "myname",
- b. `r()` scalar such as "r(mean)",
- c. `e()` scalar such as "e(N)", or
- d. `c()` scalar such as "c(namerlenchar)".

Note that string scalars never appear in `r()` and `e()`; thus (b) and (c) do not apply to `st_strscalar()`.

2. `st_numscalar(name)` and `st_strscalar(name)` return the value of the specified Stata scalar. They return a 1×1 result if the specified Stata scalar exists and return a 0×0 result otherwise.
3. `st_numscalar(name, value)` and `st_strscalar(name, value)` set or reset the contents of the specified Stata scalar.
4. `st_numscalar(name, value)` and `st_strscalar(name, value)` delete the specified Stata scalar if `value==J(0,0,.)` (if `value` is 0×0).
5. `st_numscalar(name, value, hcat)` sets or resets the specified Stata scalar and sets or resets the hidden or historical status when `name` is an `e()` or `r()` value. Allowed `hcat` values are "visible", "hidden", "historical", and a string scalar release number such as such as "10", "10.1", or any string release number matching "#[#][.#[#]]". See [\[P\] return](#) for a description of hidden and historical stored results.

When `st_numscalar(name, value)` is used to set an `e()` or `r()` value, its `hcat` is set to "visible".

There is no three-argument form of `st_strscalar()` because there are no `r()` or `e()` string scalar values.

Remarks and examples

[stata.com](#)

See [\[M-5\] st_global\(\)](#) and [\[M-5\] st_rclear\(\)](#).

Conformability

`st_numscalar(name), st_strscalar(name):`

<code>name:</code>	1×1
<code>result:</code>	1×1 or 0×0

`st_numscalar(name, value), st_strscalar(name, value):`

<code>name:</code>	1×1
<code>value:</code>	1×1 or 0×0
<code>result:</code>	<code>void</code>

`st_numscalar(name, value, hcat):`

<code>name:</code>	1×1
<code>value:</code>	1×1
<code>hcat:</code>	1×1
<code>result:</code>	<code>void</code>

`st_numscalar(name):`

<code>name:</code>	1×1
<code>result:</code>	1×1

Diagnostics

All functions abort with error if *name* is malformed.

`st_numscalar(name)` and `st_strscalar(name)` return `J(0,0,.)` or `J(0,0,"")` if Stata scalar *name* does not exist. They abort with error, however, if the name is malformed.

`st_numscalar(name, value, hcat)` aborts with error if *hcat* is not an allowed value.

`st_numscalar_hcat(name)` returns "visible" when *name* is not an `e()` or `r()` value and returns "" when *name* is an `e()` or `r()` value that does not exist.

Also see

[M-5] [st_rclear\(\)](#) — Clear `r()`, `e()`, or `s()`

[M-4] [Stata](#) — Stata interface functions

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

