

program — Define and manipulate programs

[Description](#)
[Syntax](#)
[Options](#)
[Remarks and examples](#)
[Also see](#)

Description

`program define` defines and manipulates programs. `define` is required if *program_name* is any of the words: `define`, `dir`, `drop`, `list`, or `plugin`.

`program dir` lists the names of all the programs stored in memory.

`program list` lists the contents of the named program or programs. `program list _all` lists the contents of all programs stored in memory.

`program drop` eliminates the named program or programs from memory. `program drop _all` eliminates all programs stored in memory. `program drop _allado` eliminates all programs stored in memory that were loaded from ado-files. See [\[U\] 17 Ado-files](#) for an explanation of ado-files.

See [\[U\] 18 Programming Stata](#) for a description of programs. The remarks below address only the use of the `program dir`, `program drop`, and `program list` commands.

See [\[P\] trace](#) for information on debugging programs.

See the *Combined subject table of contents for programming*, which immediately follows the *Contents*, for a subject summary of the programming commands.

Syntax

Define program

```
program [define] program_name [, [nclass|rclass|eclass|sclass]
    byable(recall[, noheader]|onecall) properties(namelist) sortpreserve
    plugin]
```

List names of programs stored in memory

```
program dir
```

Eliminate program from memory

```
program drop {program_name [program_name [...]] | _all | _allado }
```

List contents of program

```
program list [program_name [program_name [...]] | _all]
```

Options

`nclass` states that the program being defined does not return results in `r()`, `e()`, or `s()`, and is the default.

`rclass` states that the program being defined returns results in `r()`. This is done using the `return` command; see [P] [return](#). If the program is not explicitly declared to be `rclass`, then it may not change or replace results in `r()`.

`eclass` states that the program being defined returns results in `e()` or modifies already existing results in `e()`. This is done using the `ereturn` command; see [P] [return](#) and [P] [ereturn](#). If the program is not explicitly declared to be `eclass`, it may not directly replace or change results in `e()`.

`sclass` states that the program being defined returns results in `s()`. This is done using the `sreturn` command; see [P] [return](#). If the program is not explicitly declared to be `sclass`, then it may not directly change or replace results in `s()`, but it still may clear `s()` by using `sreturn clear`.

`byable(recall[, noheader] | onecall)` specifies that the program allow Stata's `by varlist:` prefix. There are two styles for writing `byable` programs: `byable(recall)` and `byable(onecall)`. The writing of `byable` programs is discussed in [P] [byable](#).

`properties(namelist)` states that `program_name` has the specified properties. `namelist` may contain up to 80 characters, including separating spaces. See [P] [program properties](#).

`sortpreserve` states that the program changes the sort order of the data and that Stata is to restore the original order when the program concludes; see [P] [sortpreserve](#).

`plugin` specifies that a plugin (a specially compiled C program) be dynamically loaded and that the plugin define the new command; see [P] [plugin](#).

Remarks and examples

[stata.com](http://www.stata.com)

The program `dir` command lists the names of all the programs stored in memory. `program list` lists contents of the program or programs.

► Example 1

When you start Stata, there are no programs stored in memory. If you type `program dir`, Stata displays an empty list:

```
. program dir
.
```

Later during the session, you might see

```
. program dir
(output omitted)
ado      756  _pred_se
ado      644  logit_p.GenScores
ado      306  logit_p.GetRhs
ado     5296  logit_p
ado      339  predict
(output omitted)
ado      559  logit.Replay
ado     4272  logit.Estimate
ado      827  logit
ado      287  webuse.Query
ado      588  webuse.Set
ado      269  webuse.GetDefault
ado      686  webuse
-----
118187
```

The `ado` in front indicates that the program was automatically loaded and thus can be automatically dropped should memory become scarce; see [\[U\] 17 Ado-files](#). The number is the size, in bytes, of the program. Notice the `logit_p.GetRhs` and `logit_p.GenScores` entries. These programs are defined in the `logit_p.ado` file and were loaded when `logit_p` was loaded.

Let's now create two of our own programs with program:

```
. program rng
1. args n a b
2. if "'b'==" {
3.   display "You must type three arguments: n a b"
4.   exit
5. }
6. drop _all
7. set obs 'n'
8. generate x = (_n-1)/(_N-1)*('b'-'a')+ 'a'
9. end

. program smooth
1. args v1 v2
2. confirm variable 'v1'
3. confirm new variable 'v2'
4. generate 'v2' = cond(_n==1|_n==_N,'v1',('v1'[_n-1]+'v1'+ 'v1'[_n+1])/3)
5. end
```

After you type `program`, lines are collected until you type a line with the word `end`. For our purposes, it does not matter what these programs do. If we were now to type `program dir`, we would see

```
. program dir
      286 smooth
      319 rng
(output omitted)
ado    756 _pred_se
ado    644 logit_p.GenScores
ado    306 logit_p.GetRhs
ado    5296 logit_p
ado    339 predict
(output omitted)
ado    559 logit.Replay
ado    4272 logit.Estimate
ado    827 logit
ado    287 webuse.Query
ado    588 webuse.Set
ado    269 webuse.GetDefault
ado    686 webuse
-----
      118792
```

We can list a program by using the `program list` command:

```
. program list smooth
smooth:
1. args v1 v2
2. confirm variable 'v1'
3. confirm new variable 'v2'
4. generate 'v2' = cond(_n==1|_n==_N,'v1',('v1'[_n-1]+'v1'+v1'[_n+1])/3)
```

If we do not specify the program that we want listed, `program list` lists all the programs stored in memory.

The `program drop` command eliminates programs from memory. Typing `program drop program_name` eliminates *program_name* from memory. Typing `program drop _all` eliminates all programs from memory.

```
. program drop smooth
. program dir
      319  rng
(output omitted)
ado      756  _pred_se
ado      644  logit_p.GenScores
ado      306  logit_p.GetRhs
ado      5296 logit_p
ado      339  predict
(output omitted)
ado      559  logit.Replay
ado      4272 logit.Estimate
ado      827  logit
ado      287  webuse.Query
ado      588  webuse.Set
ado      269  webuse.GetDefault
ado      686  webuse
-----
      118506
. program drop _all
. program dir
.
```

4

Also see

- [P] [byable](#) — Make programs byable
- [P] [discard](#) — Drop automatically loaded programs
- [P] [sortpreserve](#) — Sort within programs
- [P] [trace](#) — Debug Stata programs
- [D] [clear](#) — Clear memory
- [R] [query](#) — Display system parameters
- [U] [18 Programming Stata](#)

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).