

`set clevel` — Set default credible level

[Description](#)[Syntax](#)[Option](#)[Remarks and examples](#)[Also see](#)

Description

`set clevel` specifies the default credible level for credible intervals for all Bayesian commands (see [\[BAYES\] Bayesian commands](#)) that report credible intervals. The initial value is 95, meaning 95% credible intervals.

Syntax

```
set clevel # [ , permanently ]
```

is any number between 10.00 and 99.99 and may be specified with at most two digits after the decimal point.

Option

`permanently` specifies that in addition to making the change right now, the `clevel` setting be remembered and become the default setting when you invoke Stata.

Remarks and examples

[stata.com](#)

To change the level of credible intervals reported by a particular command, you need not reset the default credible level. All commands that report credible intervals have a `clevel(#)` option. When you do not specify the option, the credible intervals are calculated for the default level set by `set clevel` or for 95% if you have not reset `set clevel`.

▷ Example 1

We use the bayesmh command to obtain the credible interval for the mean of mpg:

```
. use https://www.stata-press.com/data/r18/auto
(1978 automobile data)
. set seed 14
. bayesmh mpg, likelihood(normal(30)) prior({mpg:_cons}, flat)
Burn-in ...
Simulation ...
Model summary
```

```
Likelihood:
  mpg ~ normal({mpg:_cons},30)
Prior:
  {mpg:_cons} ~ 1 (flat)
```

```
Bayesian normal regression                MCMC iterations = 12,500
Random-walk Metropolis-Hastings sampling  Burn-in         = 2,500
                                           MCMC sample size = 10,000
                                           Number of obs   = 74
                                           Acceptance rate = .4195
                                           Efficiency      = .2378

Log marginal-likelihood = -234.09275
```

mpg	Mean	Std. dev.	MCSE	Median	Equal-tailed [95% cred. interval]	
_cons	21.30364	.6429995	.013186	21.30381	20.03481	22.5555

To obtain 90% credible intervals, we would type

```
. bayesmh, clevel(90)
Model summary
```

```
Likelihood:
  mpg ~ normal({mpg:_cons},30)
Prior:
  {mpg:_cons} ~ 1 (flat)
```

```
Bayesian normal regression                MCMC iterations = 12,500
Random-walk Metropolis-Hastings sampling  Burn-in         = 2,500
                                           MCMC sample size = 10,000
                                           Number of obs   = 74
                                           Acceptance rate = .4195
                                           Efficiency      = .2378

Log marginal-likelihood = -234.09275
```

mpg	Mean	Std. dev.	MCSE	Median	Equal-tailed [90% cred. interval]	
_cons	21.30364	.6429995	.013186	21.30381	20.24172	22.35158

or we could type

```
. set clevel 90
. bayesmh
```

Model summary

Likelihood:

```
mpg ~ normal({mpg:_cons},30)
```

Prior:

```
{mpg:_cons} ~ 1 (flat)
```

Bayesian normal regression	MCMC iterations =	12,500
Random-walk Metropolis-Hastings sampling	Burn-in =	2,500
	MCMC sample size =	10,000
	Number of obs =	74
	Acceptance rate =	.4195
	Efficiency =	.2378
Log marginal-likelihood = -234.09275		

	Mean	Std. dev.	MCSE	Median	Equal-tailed [90% cred. interval]	
mpg						
_cons	21.30364	.6429995	.013186	21.30381	20.24172	22.35158

If we opt for the second alternative, the next time that we fit a model, 90% credible intervals will be reported. If we wanted 95% credible intervals, we could specify `clevel(95)` on the estimation command, or we could reset the default by typing `set clevel 95`.

The current setting of `clevel()` is stored as the c-class value `c(clevel)`; see [P] [creturn](#).

◀

Also see

[BAYES] [bayes](#) — Bayesian regression models using the bayes prefix⁺

[BAYES] [bayesmh](#) — Bayesian models using Metropolis–Hastings algorithm⁺

[BAYES] [Bayesian estimation](#) — Bayesian estimation commands

[R] [query](#) — Display system parameters

[P] [creturn](#) — Return c-class values

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).