

**lowertriangle()** — Extract lower or upper triangle

Description Diagnostics	Syntax Also see	Remarks and examples	Conformability
----------------------------	--------------------	----------------------	----------------

## Description

`lowertriangle()` returns the lower triangle of  $A$ .

`uppertriangle()` returns the upper triangle of  $A$ .

`_lowertriangle()` replaces  $A$  with its lower triangle.

`_uppertriangle()` replaces  $A$  with its upper triangle.

## Syntax

*numeric matrix*    `lowertriangle(numeric matrix  $A$  [ , numeric scalar  $d$  ])`

*numeric matrix*    `uppertriangle(numeric matrix  $A$  [ , numeric scalar  $d$  ])`

*void*                `_lowertriangle(numeric matrix  $A$  [ , numeric scalar  $d$  ])`

*void*                `_uppertriangle(numeric matrix  $A$  [ , numeric scalar  $d$  ])`

where argument  $d$  is optional.

## Remarks and examples

Remarks are presented under the following headings:

*Optional argument  $d$*   
*Nonsquare matrices*

### Optional argument $d$

Optional argument  $d$  specifies the treatment of the diagonal. Specifying  $d > .$ , or not specifying  $d$  at all, means no special treatment; if

$$A = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

then

$$\text{lowertriangle}(A, .) = \begin{bmatrix} 1 & 0 & 0 \\ 4 & 5 & 0 \\ 7 & 8 & 9 \end{bmatrix}$$

If a nonmissing value is specified for  $d$ , however, that value is substituted for each element of the diagonal, for example,

$$\text{lowertriangle}(A, 1) = \begin{bmatrix} 1 & 0 & 0 \\ 4 & 1 & 0 \\ 7 & 8 & 1 \end{bmatrix}$$

### Nonsquare matrices

`lowertriangle()` and `uppertriangle()` may be used with nonsquare matrices. If

$$A = \begin{bmatrix} 1 & 2 & 3 & 4 \\ 5 & 6 & 7 & 8 \\ 9 & 10 & 11 & 12 \end{bmatrix}$$

then

$$\text{lowertriangle}(A) = \begin{bmatrix} 1 & 0 & 0 \\ 5 & 6 & 0 \\ 9 & 10 & 11 \end{bmatrix}$$

and

$$\text{uppertriangle}(A) = \begin{bmatrix} 1 & 2 & 3 & 4 \\ 0 & 6 & 7 & 8 \\ 0 & 0 & 11 & 12 \end{bmatrix}$$

`_lowertriangle()` and `_uppertriangle()`, however, may not be used with nonsquare matrices.

### Conformability

`lowertriangle(A, d)`:

$A$ :  $r \times c$   
 $d$ :  $1 \times 1$  (optional)  
*result*:  $r \times \min(r, c)$

`uppertriangle(A, d)`:

$A$ :  $r \times c$   
 $d$ :  $1 \times 1$  (optional)  
*result*:  $\min(r, c) \times c$

`_lowertriangle(A, d)`, `_uppertriangle(A, d)`:

*input*:

$A$ :  $n \times n$   
 $d$ :  $1 \times 1$  (optional)

*output*:

$A$ :  $n \times n$

## Diagnostics

None.

## Also see

[M-4] [Manipulation](#) — Matrix manipulation

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

