

range() — Vector over specified range

Description
Diagnostics

Syntax
Also see

Remarks and examples

Conformability

Description

`range(a, b, delta)` returns a column vector going from a to b in steps of $\text{abs}(\text{delta})$ ($b \geq a$) or $-\text{abs}(\text{delta})$ ($b < a$).

`rangen(a, b, n)` returns a $\text{round}(n) \times 1$ column vector going from a to b in $\text{round}(n)-1$ steps. a may be less than, equal to, or greater than b .

Syntax

numeric colvector `range(a, b, numeric scalar delta)`

numeric colvector `rangen(a, b, real scalar n)`

where a and b are numeric scalars.

Remarks and examples

stata.com

`range(0, 1, .25)` returns $(0 \setminus .25 \setminus .5 \setminus .75 \setminus 1)$. The sign of the third argument does not matter; `range(0, 1, -.25)` returns the same thing. `range(1, 0, .25)` and `range(1, 0, -.25)` return $(1 \setminus .75 \setminus .5 \setminus .25 \setminus 0)$.

`rangen(0, .5, 6)` returns $(0 \setminus .1 \setminus .2 \setminus .3 \setminus .4 \setminus .5)$. `rangen(.5, 0, 6)` returns $(.5 \setminus .4 \setminus .3 \setminus .2 \setminus .1 \setminus 0)$.

`range()` and `rangen()` may be used with complex arguments. `range(1, 1i, .4)` returns $(1 \setminus .75+.25i \setminus .5+.5i \setminus .25+.75i \setminus 1i)$. `rangen(1, 1i, 5)` returns the same thing. For `range()`, only the distance of delta from zero matters, so `range(1, 1i, .4i)` would produce the same result, as would `range(1, 1i, .25+.312i)`.

Conformability

`range(a, b, delta)`:

<i>a</i> :	1×1
<i>b</i> :	1×1
<i>delta</i> :	1×1
<i>result</i> :	1×1 , if $a = b$
	$\max(1+\text{abs}(b-a)/\text{abs}(\text{delta}), 2) \times 1$, otherwise

```
rangem(a, b, n):  
  a:      1 × 1  
  b:      1 × 1  
  n:      n × 1  
  result: round(n) × 1
```

Diagnostics

`range(a, b, delta)` aborts with error if a , b , or $delta$ contains missing, if $\text{abs}(b-a)/\text{abs}(delta)$ results in overflow, or if $1+\text{abs}(b-a)/\text{abs}(delta)$ results in a vector that is too big given the amount of memory available.

`range(a, b, delta)` returns a 1×1 result when $a = b$. In all other cases, the result is 2×1 or longer.

`rangem(a, b, n)` aborts with error if `round(n)` is less than 0 or missing.

Also see

[M-4] **Standard** — Functions to create standard matrices

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).