

## mi reshape — Reshape mi data

Description      Menu      Syntax      Options  
 Remarks and examples      Also see

## Description

mi reshape is Stata's reshape for mi data; see [D] [reshape](#).

## Menu

Statistics > Multiple imputation

## Syntax

## Overview

(The words long and wide in what follows have nothing to do with mi styles mlong, flong, flongsep, and wide; they have to do with reshape's concepts.)

<i>long</i>				<i>wide</i>		
<i>i</i>	<i>j</i>	<i>stub</i>	← reshape →	<i>i</i>	<i>stub1</i>	<i>stub2</i>
1	1	4.1		1	4.1	4.5
1	2	4.5		2	3.3	3.0
2	1	3.3				
2	2	3.0				

To go from long to wide:

```
mi reshape wide stub, i(i) j(j)
```

/ *j* existing variable

To go from wide to long:

```
mi reshape long stub, i(i) j(j)
```

\ *j* new variable

## Basic syntax

Convert mi data from long form to wide form

```
mi reshape wide stubnames, i(varlist) j(varname) [options]
```

Convert mi data from wide form to long form

```
mi reshape long stubnames, i(varlist) j(varname) [options]
```

<i>options</i>	Description
<i>i</i> ( <i>varlist</i> )	<i>i</i> variable(s)
<i>j</i> ( <i>varname</i> [ <i>values</i> ])	long→wide: <i>j</i> , existing variable wide→long: <i>j</i> , new variable optionally specify values to subset <i>j</i>
<u>s</u> tr <i>ing</i>	<i>j</i> is string variable (default is numeric)

---

where *values* is #[-#] [...] if *j* is numeric (the default)  
"string" ["string" ...] if *j* is string

and where *stubnames* are variable names (long→wide), or stubs of variable names (wide→long). Unlike `reshape` (see [\[D\] reshape](#)), *stubnames* may not contain @ to denote where *j* appears in the name; all *stubnames* must follow the style *stub#*.

## Options

See [\[D\] reshape](#) for descriptions of the other options.

## Remarks and examples

[stata.com](#)

The `reshape` command you specify is carried out on the  $m = 0$  data, and then the result is duplicated in  $m = 1, m = 2, \dots, m = M$ .

In `mi reshape`, all variables corresponding to the same *stubnames* must be registered of the same `mi` type: `imputed`, `passive`, or `regular`.

## Also see

[\[MI\] Intro](#) — Introduction to `mi`

[\[MI\] mi replace0](#) — Replace original data

[\[D\] reshape](#) — Convert data from wide to long form and vice versa

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the [FAQ on citing Stata documentation](#).