

cttost — Convert count-time data to survival-time data

[Description](#)
[Options](#)[Quick start](#)
[Remarks and examples](#)[Menu](#)
[Also see](#)[Syntax](#)

Description

`cttost` converts count-time data to their survival-time format so that they can be analyzed with Stata. Do not confuse count-time data with counting-process data, which can also be analyzed with the `st` commands; see [\[ST\] ctset](#) for a definition and examples of count data.

Quick start

Convert count-time data to survival-time data using `ctset` data

```
cttost
```

Same as above, but name the new weight variable `mywvar` instead of using the default name

```
cttost, wvar(mywvar)
```

Menu

[Statistics](#) > [Survival analysis](#) > [Setup and utilities](#) > [Convert count-time data to survival-time data](#)

Syntax

```
cttost [ , options ]
```

<i>options</i>	Description
<code>t0(<i>t0var</i>)</code>	name of entry-time variable
<code>wvar(<i>wvar</i>)</code>	name of frequency-weighted variable
<code>clear</code>	overwrite current data in memory
<code>nopreserve</code>	do not save the original data; programmer's command

You must `ctset` your data before using `cttost`; see [ST] [ctset](#).

`nopreserve` does not appear in the dialog box.

Options

`t0(t0var)` specifies the name of the new variable to create that records entry time. (For most ct data, no entry-time variable is necessary because everyone enters at time 0.)

Even if an entry-time variable is necessary, you need not specify this option. `cttost` will, by default, choose `t0`, `time0`, or `etime` according to which name does not already exist in the data.

`wvar(wvar)` specifies the name of the new variable to be created that records the frequency weights for the new pseudo-observations. Count-time data are actually converted to frequency-weighted st data, and a variable is needed to record the weights. This sounds more complicated than it is. Understand that `cttost` needs a new variable name, which will become a permanent part of the st data.

If you do not specify `wvar()`, `cttost` will, by default, choose `w`, `pop`, `weight`, or `wgt` according to which name does not already exist in the data.

`clear` specifies that it is okay to proceed with the conversion, even though the current dataset has not been saved on disk.

The following option is available with `cttost` but is not shown in the dialog box:

`nopreserve` speeds the conversion by not saving the original data that can be restored should things go wrong or should you press *Break*. `nopreserve` is intended for use by programmers who use `cttost` as a subroutine. Programmers can specify this option if they have already preserved the original data. `nopreserve` does not affect the conversion.

Remarks and examples

[stata.com](https://www.stata.com)

Converting ct to st data is easy. We have some count-time data,

```
. use https://www.stata-press.com/data/r18/cttost
. ct
Count-time data settings
      Time: time
  Failures: ndead
  Number lost: ncens
  Number entered: All enter at time 0
  Group variables: agecat treat
```

```
. list in 1/5
```

	agecat	treat	time	ndead	ncens
1.	2	1	464	4	0
2.	3	0	268	3	1
3.	2	0	638	2	0
4.	1	0	803	1	4
5.	1	0	431	2	0

and to convert it, we type cttost:

```
. cttost
Count-time data settings
      Time: time
      Failures: ndead
      Number lost: ncens
      Number entered: All enter at time 0
      Group variables: agecat treat
Converting count-time data to survival-time data ...
Survival-time data settings
      Failure event: ndead!=0 & ndead<.
Observed time interval: (0, time]
      Exit on or before: failure
      Weight: [fweight=w]

-----
      33 total observations
      0  exclusions

-----
      33 physical observations remaining, equal to
      82 weighted observations, representing
      39 failures in single-record/single-failure data
48,726 total analysis time at risk and under observation
                               At risk from t =           0
                               Earliest observed entry t =       0
                               Last observed exit t =       1,227
```

Now that it is converted, we can use any of the st commands:

```
. sts test treat, logrank
      Failure _d: ndead
      Analysis time _t: time
      Weight: [fweight=w]
Equality of survivor functions
Log-rank test
```

treat	Observed events	Expected events
0	22	17.05
1	17	21.95
Total	39	39.00

```

      chi2(1) = 2.73
      Pr>chi2 = 0.0986
```

Also see

[ST] **ct** — Count-time data

[ST] **ctset** — Declare data to be count-time data

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).