

bayesfcast — Bayesian dynamic forecasts

Description

Quick start

Syntax

Also see

Description

`bayesfcast` computes and graphs Bayesian dynamic forecasts of the endogenous variables after `bayes: var`. `bayesfcast` has two subcommands. `bayesfcast compute` computes the posterior means or medians of dynamic forecasts, posterior standard deviations, and credible intervals. `bayesfcast graph` graphs Bayesian predictions, credible intervals, and observed values.

Quick start

Fit a Bayesian vector autoregression model

```
bayes, saving(bvarmcmc): var y1 y2 y3
```

Compute posterior means and credible intervals of dynamic forecast for 8 steps ahead

```
bayesfcast compute bf_, step(8)
```

Graph the posterior means, credible intervals, and observed values

```
bayesfcast graph bf_y1 bf_y2 bf_y3, observed
```

Syntax

<code>bayesfcast subcommand ... [, ...]</code>	
<i>subcommand</i>	Description
<code>compute</code>	obtain dynamic forecasts
<code>graph</code>	graph dynamic forecasts obtained from <code>bayesfcast compute</code>
<code>bayesfcast</code> can be used after <code>bayes: var</code> ; see [BAYES] <code>bayes: var</code> .	

Also see

[\[BAYES\]](#) `bayes: var` — Bayesian vector autoregressive models

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

