

bayes: mprobit — Bayesian multinomial probit regression

[Description](#)[Remarks and examples](#)[Quick start](#)[Stored results](#)[Menu](#)[Methods and formulas](#)[Syntax](#)[Also see](#)

Description

`bayes: mprobit` fits a Bayesian multinomial probit regression to a categorical outcome; see [\[BAYES\] bayes](#) and [\[R\] mprobit](#) for details.

Quick start

Bayesian multinomial probit regression of `y` on `x1` and `x2`, using default normal priors for regression coefficients

```
bayes: mprobit y x1 x2
```

Use a standard deviation of 10 instead of 100 for the default normal priors

```
bayes, normalprior(10): mprobit y x1 x2
```

Use uniform priors for the slopes and a normal prior for the intercept for the category 2

```
bayes, prior({2: x1 x2}, uniform(-10,10)) ///
prior({2:_cons}, normal(0,10)): mprobit y x1 x2
```

Save simulation results to `simdata.dta` and use a random-number seed for reproducibility

```
bayes, saving(simdata) rseed(123): mprobit y x1 x2
```

Specify 20,000 MCMC samples, set length of the burn-in period to 5,000, and request that a dot be displayed every 500 simulations

```
bayes, mcmcsample(20000) burnin(5000) dots(500): mprobit y x1 x2
```

In the above, request that the 90% HPD credible interval be displayed instead of the default 95% equal-tailed credible interval

```
bayes, clevel(90) hpd
```

Also see [Quick start](#) in [\[BAYES\] bayes](#) and [Quick start](#) in [\[R\] mprobit](#).

Menu

Statistics > Categorical outcomes > Bayesian multinomial probit regression

Syntax

```
bayes [, bayesopts] : mprobit depvar [indepvars] [if] [in] [weight] [, options]
```

<i>options</i>	Description
----------------	-------------

Model

<code>noconstant</code>	suppress constant term
<code>baseoutcome(#)</code>	value of <i>depvar</i> that will be the base outcome
<code>probitparam</code>	use the probit variance parameterization
<code>collinear</code>	keep collinear variables

Reporting

<code>display_options</code>	control spacing, line width, and base and empty cells
<code>level(#)</code>	set credible level; default is level(95)

indepvars may contain factor variables; see [U] 11.4.3 Factor variables.

fweights are allowed; see [U] 11.1.6 weight.

bayes: mprobit, level() is equivalent to bayes, clevel(): mprobit.

For a detailed description of *options*, see *Options* in [R] mprobit.

<i>bayesopts</i>	Description
------------------	-------------

Priors

* <code>normalprior(#)</code>	specify standard deviation of default normal priors for regression coefficients; default is normalprior(100)
<code>prior(priorspec)</code>	prior for model parameters; this option may be repeated
<code>dryrun</code>	show model summary without estimation

Simulation

<code>mcmcsize(#)</code>	MCMC sample size; default is mcmcsize(10000)
<code>burnin(#)</code>	burn-in period; default is burnin(2500)
<code>thinning(#)</code>	thinning interval; default is thinning(1)
<code>rseed(#)</code>	random-number seed
<code>exclude(paramref)</code>	specify model parameters to be excluded from the simulation results

Blocking

* <code>blocksize(#)</code>	maximum block size; default is blocksize(50)
<code>block(paramref[, blockopts])</code>	specify a block of model parameters; this option may be repeated
<code>blocksummary</code>	display block summary
* <code>noblocking</code>	do not block parameters by default

Initialization

<code>initial(initspec)</code>	initial values for model parameters
<code>nomleinitial</code>	suppress the use of maximum likelihood estimates as starting values
<code>inirandom</code>	specify random initial values
<code>initsummary</code>	display initial values used for simulation
* <code>noisily</code>	display output from the estimation command during initialization

Adaptation

`adaptation(adaptopts)` control the adaptive MCMC procedure
`scale(#)` initial multiplier for scale factor; default is `scale(2.38)`
`covariance(cov)` initial proposal covariance; default is the identity matrix

Reporting

`clevel(#)` set credible interval level; default is `clevel(95)`
`hpd` display HPD credible intervals instead of the default equal-tailed credible intervals
`eform[(string)]` report exponentiated coefficients and, optionally, label as *string*
`batch(#)` specify length of block for batch-means calculations; default is `batch(0)`
`saving(filename[, replace])` save simulation results to *filename.dta*
`nomodelsummary` suppress model summary
`[no]dots` suppress dots or display dots every 100 iterations and iteration numbers every 1,000 iterations; default is `nodots`
`dots(#[, every(#)])` display dots as simulation is performed
`[no]show(paramref)` specify model parameters to be excluded from or included in the output
`notable` suppress estimation table
`noheader` suppress output header
`title(string)` display *string* as title above the table of parameter estimates
`display_options` control spacing, line width, and base and empty cells

Advanced

`search(search_options)` control the search for feasible initial values
`corrlag(#)` specify maximum autocorrelation lag; default varies
`corrtol(#)` specify autocorrelation tolerance; default is `corrtol(0.01)`

*Starred options are specific to the `bayes` prefix; other options are common between `bayes` and `bayesmh`.

Options `prior()` and `block()` can be repeated.

`priorspec` and `paramref` are defined in [BAYES] `bayesmh`.

`paramref` may contain factor variables; see [U] 11.4.3 Factor variables.

See [U] 20 Estimation and postestimation commands for more capabilities of estimation commands.

Model parameters are regression coefficients `{outcome1:indepvars}`, `{outcome2:indepvars}`, and so on, where `outcome#`'s are the values of the dependent variable or the value labels of the dependent variable if they exist. Use the `dryrun` option to see the definitions of model parameters prior to estimation.

For a detailed description of `bayesopts`, see *Options* in [BAYES] `bayes`.

Remarks and examples

[stata.com](http://www.stata.com)

For a general introduction to Bayesian analysis, see [BAYES] `intro`. For a general introduction to Bayesian estimation using an adaptive Metropolis–Hastings algorithm, see [BAYES] `bayesmh`. For remarks and examples specific to the `bayes` prefix, see [BAYES] `bayes`. For details about the estimation command, see [R] `mprobit`.

For a simple example of the `bayes` prefix, see *Introductory example* in [BAYES] `bayes`. Also see *Multinomial logistic regression* in [BAYES] `bayes`.

Stored results

See *Stored results* in [BAYES] **bayesmh**.

Methods and formulas

See *Methods and formulas* in [BAYES] **bayesmh**.

Also see

[BAYES] **bayes** — Bayesian regression models using the bayes prefix

[R] **mprobit** — Multinomial probit regression

[BAYES] **bayesian postestimation** — Postestimation tools for bayesmh and the bayes prefix

[BAYES] **bayesian estimation** — Bayesian estimation commands

[BAYES] **bayesian commands** — Introduction to commands for Bayesian analysis

[BAYES] **intro** — Introduction to Bayesian analysis

[BAYES] **Glossary**