

bayes: tobit — Bayesian tobit regression

[Description](#)

[Remarks and examples](#)

[Quick start](#)

[Stored results](#)

[Menu](#)

[Methods and formulas](#)

[Syntax](#)

[Also see](#)

Description

`bayes: tobit` fits a Bayesian tobit regression to a censored continuous outcome; see [\[BAYES\] bayes](#) and [\[R\] tobit](#) for details.

Quick start

Bayesian tobit regression of `y` on `x1` and `x2`, using a lower censoring limit of 17 and using default normal priors for regression coefficients and default inverse-gamma prior for the variance

```
bayes: tobit y x1 x2, ll(17)
```

Use a standard deviation of 10 instead of 100 for the default normal priors

```
bayes, normalprior(10): tobit y x1 x2, ll(17)
```

Use a shape of 1 and a scale of 2 instead of values of 0.01 for the default inverse-gamma prior

```
bayes, igammaprior(1 2): tobit y x1 x2, ll(17)
```

Use uniform priors for the slopes and a normal prior for the intercept

```
bayes, prior({y: x1 x2}, uniform(-10,10)) ///
prior({y:_cons}, normal(0,10)): tobit y x1 x2, ll(17)
```

Save simulation results to `simdata.dta` and use a random-number seed for reproducibility

```
bayes, saving(simdata) rseed(123): tobit y x1 x2, ll(17)
```

Specify 20,000 MCMC samples, set length of the burn-in period to 5,000, and request that a dot be displayed every 500 simulations

```
bayes, mcmcsample(20000) burnin(5000) dots(500): tobit y x1 x2, ll(17)
```

In the above, request that the 90% HPD credible interval be displayed instead of the default 95% equal-tailed credible interval

```
bayes, clevel(90) hpd
```

Also see [Quick start](#) in [\[BAYES\] bayes](#) and [Quick start](#) in [\[R\] tobit](#).

Menu

Statistics > Linear models and related > Bayesian regression > Tobit regression

Syntax

```
bayes [, bayesopts] : tobit devar [indepvars] [if] [in] [weight] [, options]
```

<i>options</i>	Description
Model	
<u>noconstant</u>	suppress constant term
<u>ll</u> [<i>varname</i> #]	left-censoring variable or limit
<u>ul</u> [<i>varname</i> #]	right-censoring variable or limit
<u>offset</u> (<i>varname</i>)	include <i>varname</i> in model with coefficient constrained to 1
<u>collinear</u>	keep collinear variables
Reporting	
<u>display_options</u>	control spacing, line width, and base and empty cells
<u>level</u> (#)	set credible level; default is <code>level(95)</code>
<hr/>	
<i>indepvars</i> may contain factor variables; see [U] 11.4.3 Factor variables .	
<i>devar</i> and <i>indepvars</i> may contain time-series operators; see [U] 11.4.4 Time-series varlists .	
fweights are allowed; see [U] 11.1.6 weight .	
bayes: tobit, level() is equivalent to bayes, clevel(): tobit.	
For a detailed description of <i>options</i> , see <i>Options</i> in [R] tobit .	
<hr/>	
<i>bayesopts</i>	Description
Priors	
* <u>normalprior</u> (#)	specify standard deviation of default normal priors for regression coefficients; default is <code>normalprior(100)</code>
* <u>igammaprior</u> (# #)	specify shape and scale of default inverse-gamma prior for variance; default is <code>igammaprior(0.01 0.01)</code>
<u>prior</u> (<i>priorspec</i>)	prior for model parameters; this option may be repeated
<u>dryrun</u>	show model summary without estimation
Simulation	
<u>mcmcsize</u> (#)	MCMC sample size; default is <code>mcmcsize(10000)</code>
<u>burnin</u> (#)	burn-in period; default is <code>burnin(2500)</code>
<u>thinning</u> (#)	thinning interval; default is <code>thinning(1)</code>
<u>rseed</u> (#)	random-number seed
<u>exclude</u> (<i>paramref</i>)	specify model parameters to be excluded from the simulation results
Blocking	
* <u>blocksize</u> (#)	maximum block size; default is <code>blocksize(50)</code>
<u>block</u> (<i>paramref</i> [, <i>blockopts</i>])	specify a block of model parameters; this option may be repeated
<u>blocksummary</u>	display block summary
* <u>noblocking</u>	do not block parameters by default

Initialization

<code>initial(<i>initspec</i>)</code>	initial values for model parameters
<code>nomleinitial</code>	suppress the use of maximum likelihood estimates as starting values
<code>initransom</code>	specify random initial values
<code>initsummary</code>	display initial values used for simulation
* <code>noisily</code>	display output from the estimation command during initialization

Adaptation

<code>adaptation(<i>adaptopts</i>)</code>	control the adaptive MCMC procedure
<code>scale(#)</code>	initial multiplier for scale factor; default is <code>scale(2.38)</code>
<code>covariance(<i>cov</i>)</code>	initial proposal covariance; default is the identity matrix

Reporting

<code>clevel(#)</code>	set credible interval level; default is <code>clevel(95)</code>
<code>hpd</code>	display HPD credible intervals instead of the default equal-tailed credible intervals
<code>eform[(<i>string</i>)]</code>	report exponentiated coefficients and, optionally, label as <i>string</i>
<code>batch(#)</code>	specify length of block for batch-means calculations; default is <code>batch(0)</code>
<code>saving(<i>filename</i> [, <i>replace</i>])</code>	save simulation results to <i>filename.dta</i>
<code>nomodelsummary</code>	suppress model summary
<code>[no]dots</code>	suppress dots or display dots every 100 iterations and iteration numbers every 1,000 iterations; default is <code>nodots</code>
<code>dots(# [, <i>every</i>(#)])</code>	display dots as simulation is performed
<code>[no]show(<i>paramref</i>)</code>	specify model parameters to be excluded from or included in the output
<code>notable</code>	suppress estimation table
<code>noheader</code>	suppress output header
<code>title(<i>string</i>)</code>	display <i>string</i> as title above the table of parameter estimates
<code>display_options</code>	control spacing, line width, and base and empty cells

Advanced

<code>search(<i>search_options</i>)</code>	control the search for feasible initial values
<code>corrlag(#)</code>	specify maximum autocorrelation lag; default varies
<code>corrtol(#)</code>	specify autocorrelation tolerance; default is <code>corrtol(0.01)</code>

*Starred options are specific to the `bayes` prefix; other options are common between `bayes` and `bayesmh`. Options `prior()` and `block()` can be repeated.

priorspec and *paramref* are defined in [BAYES] `bayesmh`.

paramref may contain factor variables; see [U] 11.4.3 **Factor variables**.

See [U] 20 **Estimation and postestimation commands** for more capabilities of estimation commands.

Model parameters are regression coefficients `{depvar: indepvars}` and variance `{sigma2}`. Use the `dryrun` option to see the definitions of model parameters prior to estimation.

For a detailed description of *bayesopts*, see *Options* in [BAYES] `bayes`.

Remarks and examples

[stata.com](http://www.stata.com)

For a general introduction to Bayesian analysis, see [BAYES] `intro`. For a general introduction to Bayesian estimation using an adaptive Metropolis–Hastings algorithm, see [BAYES] `bayesmh`. For

remarks and examples specific to the `bayes` prefix, see [\[BAYES\] bayes](#). For details about the estimation command, see [\[R\] tobit](#).

For a simple example of the `bayes` prefix, see *Introductory example* in [\[BAYES\] bayes](#).

Stored results

See *Stored results* in [\[BAYES\] bayesmh](#).

Methods and formulas

See *Methods and formulas* in [\[BAYES\] bayesmh](#).

Also see

[\[BAYES\] bayes](#) — Bayesian regression models using the `bayes` prefix

[\[R\] tobit](#) — Tobit regression

[\[BAYES\] bayesian postestimation](#) — Postestimation tools for `bayesmh` and the `bayes` prefix

[\[BAYES\] bayesian estimation](#) — Bayesian estimation commands

[\[BAYES\] bayesian commands](#) — Introduction to commands for Bayesian analysis

[\[BAYES\] intro](#) — Introduction to Bayesian analysis

[\[BAYES\] Glossary](#)