

[Description](#)
[Options](#)

[Quick start](#)
[Remarks and examples](#)

[Menu](#)
[Stored results](#)

[Syntax](#)
[Also see](#)

Description

`estat greport` displays the estimated group IRT parameters.

Quick start

Group 2PL model for binary items b1 to b10

```
irt 2pl b1-b10, group(female)
```

Report results in a compact format

```
estat greport
```

Report standard errors in addition to coefficients

```
estat greport, se
```

Report results grouped by parameter type

```
estat greport, byparm
```

Same as above, and sort items by estimated difficulty

```
estat greport, byparm sort(b)
```

Menu

Statistics > IRT (item response theory)

Syntax

```
estat greport [ , options ]
```

```
sort(p [ , descending ])    sort items by the estimated p parameters; p may be a, b, or c
byparm                      arrange table rows by parameter rather than by item
```

Main

```
aLabel(string)             specify the a parameter label; the default is Discrim
bLabel(string)             specify the b parameter label; the default is Diff
cLabel(string)             specify the c parameter label; the default is Guess
seqLabel                    label parameters in sequential order
post                        post estimated IRT parameters and their VCE as estimation results
```

Reporting

```
b[ (%fmt) ]                how to format coefficients, which are always reported
se[ (%fmt) ]              report standard errors and use optional format
t[ (%fmt) ]              report t or z statistics and use optional format
p[ (%fmt) ]              report p-values and use optional format
parmwidth(#)             use # characters to display variable and parameter names
grwidth(#)               use # characters to display group names and statistics
style(online)            display vertical line after variable names; the default
style(columns)          display vertical lines separating columns
style(noline)           suppress all vertical lines
grLabel(string)         column labels for groups
title(string)           title for table
```

collect is allowed; see [U] 11.1.10 Prefix commands.

Options

sort(*p* [, *descending*]) requests that items be sorted according to parameter *p*, where *p* is one of a, b, or c.

sort(a) specifies that items be sorted according to the estimated discrimination parameters.

sort(b) specifies that items be sorted according to the estimated difficulty parameters.

sort(c) specifies that items be sorted according to the estimated pseudoguessing parameters. It is relevant only for a 3PL model when option `sepguessing` is specified.

`descending` requests that the sorted items be reported in descending order. Sorted items are reported in ascending order by default.

`byparm` requests that the table rows be grouped by parameter rather than by item.

Main

`aLabel(string)` labels the discrimination parameters with *string*. The default label is `Discrim`.

`bLabel(string)` labels the difficulty parameters with *string*. The default label is `Diff`.

`cLabel(string)` labels the pseudoguessing parameters with *string*. The default label is `Guess`. This option applies only to 3PL models.

`seqlabel` labels the estimated difficulty parameters within each categorical item sequentially, starting from 1. In NRM, `seqlabel` also labels the estimated discrimination parameters within each item sequentially, starting from 1. This option applies only to categorical models.

`post` causes `estat greport` to behave like a Stata estimation (`e-class`) command. `estat greport` posts the vector of estimated IRT parameters along with the corresponding variance–covariance matrix to `e()`, so that you can treat the estimated IRT parameters just as you would results from any other estimation command. For example, you could use `test` to perform simultaneous tests of hypotheses on the parameters, or you could use `lincom` to create linear combinations.

Reporting

`b(%fmt)` specifies how the coefficients are to be displayed. You might specify `b(%9.2f)` to make decimal points line up. There is also a `b` option, which specifies that coefficients be displayed, but that is just included for consistency with the `se`, `t`, and `p` options. Coefficients are always displayed.

`se`, `t`, and `p` specify that standard errors, t or z statistics, and p -values be displayed. The default is not to display them. `se(%fmt)`, `t(%fmt)`, and `p(%fmt)` specify that each be displayed and specify the display format to be used.

`parmwidth(#)` specifies the number of character positions used to display the names of the variables and parameters. The default is `parmwidth(12)`.

`grwidth(#)` specifies the number of character positions used to display the names of the groups and statistics. The default is `grwidth(12)`.

`style(stylespec)` specifies the style of the coefficient table.

`style(online)` specifies that a vertical line be displayed after the variables but not between the groups. This is the default.

`style(columns)` specifies that vertical lines be displayed after each column.

`style(noline)` specifies that no vertical lines be displayed.

`grlabel(string)` specifies the labels for the group columns. The default is to use value labels of the group variable or, if the group variable has no value labels, a factor-variable indicator for each level of the group variable.

`title(string)` specifies the title to appear above the table.

Remarks and examples

The following discussion is about how to use `estat greport` with `irt` estimation results. If you are new to the IRT features in Stata, we encourage you to read [\[IRT\] irt](#) first.

► Example 1: Sorting binary items

We illustrate the features of estat report on a group 2PL model we fit in example 1 of [IRT] irt, group(). First, we refit the model.

```
. use https://www.stata-press.com/data/r19/masc2
(Data from De Boeck & Wilson (2004))

. irt 2pl q1-q5, group(female)

Fitting fixed-effects model:
Iteration 0:  Log likelihood = -4594.5412
Iteration 1:  Log likelihood = -4590.4516
Iteration 2:  Log likelihood = -4590.4502
Iteration 3:  Log likelihood = -4590.4502
Group: Male
Group: Female
Fitting full model:
Iteration 0:  Log likelihood = -4503.5396 (not concave)
Iteration 1:  Log likelihood = -4479.7967
Iteration 2:  Log likelihood = -4476.3965
Iteration 3:  Log likelihood = -4476.3448
Iteration 4:  Log likelihood = -4476.3447

Two-parameter logistic model          Number of obs = 1,500
Log likelihood = -4476.3447
Group: Male
```

		Coefficient	Std. err.	z	P> z	[95% conf. interval]	
q1	Discrim	1.187923	.1804778	6.58	0.000	.8341933	1.541653
	Diff	-.5507796	.0894536	-6.16	0.000	-.7261054	-.3754538
q2	Discrim	.90663	.1318739	6.87	0.000	.6481618	1.165098
	Diff	-.0450698	.0761722	-0.59	0.554	-.1943645	.104225
q3	Discrim	.8828704	.1462984	6.03	0.000	.5961307	1.16961
	Diff	-1.703158	.2385734	-7.14	0.000	-2.170753	-1.235563
q4	Discrim	.8196789	.1221824	6.71	0.000	.5802057	1.059152
	Diff	.3770973	.0993197	3.80	0.000	.1824342	.5717603
q5	Discrim	1.439933	.2218141	6.49	0.000	1.005185	1.874681
	Diff	1.197739	.1437481	8.33	0.000	.9159978	1.47948
mean(Theta)		0 (omitted)					
var(Theta)		1 (constrained)					

Group: Female

	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
q1						
Discrim	1.187923	.1804778	6.58	0.000	.8341933	1.541653
Diff	-.5507796	.0894536	-6.16	0.000	-.7261054	-.3754538
q2						
Discrim	.90663	.1318739	6.87	0.000	.6481618	1.165098
Diff	-.0450698	.0761722	-0.59	0.554	-.1943645	.104225
q3						
Discrim	.8828704	.1462984	6.03	0.000	.5961307	1.16961
Diff	-1.703158	.2385734	-7.14	0.000	-2.170753	-1.235563
q4						
Discrim	.8196789	.1221824	6.71	0.000	.5802057	1.059152
Diff	.3770973	.0993197	3.80	0.000	.1824342	.5717603
q5						
Discrim	1.439933	.2218141	6.49	0.000	1.005185	1.874681
Diff	1.197739	.1437481	8.33	0.000	.9159978	1.47948
mean(Theta)	-.1348222	.0721434	-1.87	0.062	-.2762206	.0065763
var(Theta)	.6239155	.1239068			.4227474	.9208111

Group IRT models always produce a lot of output. The estimated parameters are reported separately for each group, and it is hard to visually compare estimates across groups. estat greport makes such comparisons a breeze.

. estat greport

Parameter	Male	Female
q1		
Discrim	1.1879233	1.1879233
Diff	-.55077963	-.55077963
q2		
Discrim	.90662997	.90662997
Diff	-.04506976	-.04506976
q3		
Discrim	.88287037	.88287037
Diff	-1.7031579	-1.7031579
q4		
Discrim	.81967885	.81967885
Diff	.37709727	.37709727
q5		
Discrim	1.4399331	1.4399331
Diff	1.1977389	1.1977389
mean(Theta)	0	-.13482217
var(Theta)	1	.6239155

For models with many items, it is often convenient to arrange the output according to highest or lowest difficulty (b) or discrimination (a). `estat greport` makes sorting in a desired order easy. Below, we specify option `sort(b)` to cause `estat greport` to display the items in ascending order of the estimated difficulty parameter. The sort is performed on the first group.

```
. estat greport, sort(b)
```

Parameter	Male	Female	
q3	Discrim	.88287037	.88287037
	Diff	-1.7031579	-1.7031579
q1	Discrim	1.1879233	1.1879233
	Diff	-.55077963	-.55077963
q2	Discrim	.90662997	.90662997
	Diff	-.04506976	-.04506976
q4	Discrim	.81967885	.81967885
	Diff	.37709727	.37709727
q5	Discrim	1.4399331	1.4399331
	Diff	1.1977389	1.1977389
mean(Theta)	0	-.13482217	
var(Theta)	1	.6239155	

Finally, we add the `byparm` option to cause `estat greport` to arrange the table rows by parameter type and then by item difficulty.

```
. estat greport, sort(b) byparm
```

Parameter	Male	Female	
Discrim	q3	.88287037	.88287037
	q1	1.1879233	1.1879233
	q2	.90662997	.90662997
	q4	.81967885	.81967885
	q5	1.4399331	1.4399331
	Diff	q3	-1.7031579
q1		-.55077963	-.55077963
q2		-.04506976	-.04506976
q4		.37709727	.37709727
q5		1.1977389	1.1977389
mean(Theta)		0	-.13482217
var(Theta)	1	.6239155	

Stored results

estat greport stores the following in `r()`:

Macros

`r(names)` labels used for group names

Matrices

`r(b)` vector of estimated IRT parameters

`r(b_pclass)` parameter class

`r(V)` variance–covariance matrix of the estimated IRT parameters

estat greport with the `post` option also stores the following in `e()`:

Macros

`e(properties)` `b V`

Matrices

`e(b)` vector of estimated IRT parameters

`e(V)` variance–covariance matrix of the estimated IRT parameters

Also see

[IRT] [irt](#) — Introduction to IRT models

[IRT] [irt, group\(\)](#) — IRT models for multiple groups

[IRT] [irt 1pl](#) — One-parameter logistic model

[IRT] [irt 2pl](#) — Two-parameter logistic model

[IRT] [irt 3pl](#) — Three-parameter logistic model

[IRT] [irt grm](#) — Graded response model

[IRT] [irt hybrid](#) — Hybrid IRT models

[IRT] [irt nrm](#) — Nominal response model

[IRT] [irt pcm](#) — Partial credit model

[IRT] [irt rsm](#) — Rating scale model

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).