

Description

Lasso, square-root lasso, and elastic net treat collinear covariates differently from traditional estimators. With these models, you specify variables that might be included in the model, and they choose the variables to be included. When you specify those variables, it is important that you present them with all possible alternatives. This means that, when including factor variables, you must include the full collinear set of indicators.

If you use Stata's factor-variable notation, it is handled automatically for you. If you create indicator variables for yourself, you must create and include them all.

Remarks and examples

Remarks are presented under the following headings:

Summary

Explanation

Applies to inferential commands

Does not apply to `alwaysvars`

Summary

Consider factor variable `group` that takes on the values 1, 2, and 3. If you type

```
. lasso linear y i.group ...
```

`lasso` will know that separate covariates for `group` 1, 2, and 3 are to be included among the variables to be potentially included in the model.

If you create your own indicator variables, you need to create and specify indicators for all the values of the factor variable:

```
. generate g1 = (group==1)
. generate g2 = (group==2)
. generate g3 = (group==3)
. lasso linear y g1 g2 g3 ...
```

It is important that you do not omit one of them, say `g1`, and instead type

```
. lasso linear y g2 g3 ...
```

Explanation

With no loss of generality, we will focus on lasso for this explanation. Assume lasso has just found the best model for λ_i with k covariates and is now searching for the best model for λ_{i+1} , where $\lambda_{i+1} < \lambda_i$.

The λ_{i+1} model will not always be the same λ_i model with new covariates added, but this is often the case. (Sometimes, covariates in the λ_i model are removed.) Assume this is a case of adding only new covariates. Also assume that `g1`, `g2`, and `g3` have not been chosen yet and that lasso chooses `g1`.

But what if we did not specify `g1` among the potential covariates? What if rather than typing

```
. lasso linear y g1 g2 g3 ...
```

we typed

```
. lasso linear y g2 g3 ...
```

In that case, lasso would not choose `g1` because it could not. It would choose some other covariate or covariates, perhaps `g2`, perhaps `g3`, perhaps `g2` and `g3`, or perhaps other covariates. And lasso is on an inferior path because `g1` was not among the potential covariates.

Although selecting both `g2` and `g3` in place of `g1` gives an equivalent model for prediction, it may have wasted an extra penalty on the coefficients for `g2` and `g3`. A model with only `g1` may have a smaller penalty and allow other covariates to be included, which a model with `g2` and `g3` would not. By eliminating `g1`, we have denied lasso the opportunity to find a more parsimonious model.

Applies to inferential commands

You must also specify full collinear sets of potential covariates with the inferential commands. Specify full sets in the `controls()` option, such as

```
. dsregress y z1 z2, controls(g1 g2 g3 ...)
```

Likewise for the high-dimensional instruments in `poivregress` and `xpoivregress`:

```
. poivregress y ... (z1 z2 = g1 g2 g3 ...), controls(...)
```

Just as with `lasso`, the issue is handled automatically if you use factor-variable notation:

```
. dsregress y z1 z2, controls(i.region ...)
```

Does not apply to `alwaysvars`

With any lasso, you can specify covariates that will always appear in the model. You specify them in parentheses. For example, for `lasso`, type

```
. lasso linear y (x1 x2) x3 x4 ...
```

and for the inference commands, type

```
. dsregress y z1 z2, controls((x1 x2) x3 x4 ...)
```

We call the covariates that always appear in the model *alwaysvars*. The *alwaysvars* do not need to be full collinear sets. Indeed, collinear variables among the *alwaysvars* will be omitted.

Factor-variable notation handles the problem automatically in both cases:

```
. lasso linear (i.region ...) i.group ...
```

A base level will be set for `i.region` (or you can set it explicitly). For `i.group`, all levels will be included. If you try to set a base level for `i.group`, it will be ignored.

Also see

[LASSO] [lasso](#) — Lasso for prediction and model selection

[LASSO] [lasso examples](#) — Examples of lasso for prediction

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).