

st_rclear() — Clear `r()`, `e()`, or `s()`

Description Diagnostics	Syntax Also see	Remarks and examples	Conformability
----------------------------	--------------------	----------------------	----------------

Description

`st_rclear()` clears Stata's `r()` stored results.

`st_eclear()` clears Stata's `e()` stored results.

`st_sclear()` clears Stata's `s()` stored results.

Syntax

```
void st_rclear()
```

```
void st_eclear()
```

```
void st_sclear()
```

Remarks and examples

stata.com

Returning results in `r()`, `e()`, or `s()` is one way of communicating results calculated in Mata back to Stata; see [M-1] [ado](#). See [R] [stored results](#) for a description of `e()`, `r()`, and `s()`.

Use `st_rclear()`, `st_eclear()`, or `st_sclear()` to clear results, and then use `st_global()` to define macros, `st_numscalar()` to define scalars, and `st_matrix()` to define Stata matrices in `r()`, `e()`, or `s()`. For example,

```
st_rclear()
st_global("r(name)", "tab")    see [M-5] st_global()
st_numscalar("r(N)", n1+n2)   see [M-5] st_numscalar()
st_matrix("r(table)", X+Y)    see [M-5] st_matrix()
```

It is not necessary to clear before saving, but it is considered good style unless it is your intention to add to previously stored results.

If a stored result already exists, `st_global()`, `st_numscalar()`, and `st_matrix()` may be used to redefine it and even to redefine it to a different type. For instance, continuing with our example, later in the same code might appear

```
if (...) {
    st_matrix("r(name)", X)
}
```

Stored result `r(name)` was previously defined as a macro containing "tab", and, even so, can now be redefined to become a matrix.

If you want to eliminate a particular stored result, use `st_global()` to change its contents to "":

```
st_global("r(name)", "")
```

Do this regardless of the type of the stored result. Here we use `st_global()` to clear stored result `r(name)`, which might be a macro and might be a matrix.

Conformability

`st_rclear()`, `st_eclear()`, and `st_sclear()` take no arguments and return void.

Diagnostics

`st_rclear()`, `st_eclear()`, and `st_sclear()` cannot fail.

Also see

[M-5] [st_global\(\)](#) — Obtain strings from and put strings into global macros

[M-5] [st_numscalar\(\)](#) — Obtain values from and put values into Stata scalars

[M-5] [st_matrix\(\)](#) — Obtain and put Stata matrices

[M-4] [stata](#) — Stata interface functions