

st_vartype() — Storage type of Stata variable

[Description](#) [Syntax](#) [Remarks and examples](#) [Conformability](#)
[Diagnostics](#) [Also see](#)

Description

In all the functions, if *var* is specified as a name, abbreviations are not allowed.

`st_vartype(var)` returns the [storage type](#) of the *var*, such as `float`, `double`, or `str18`.

`st_isnumvar(var)` returns 1 if *var* is a numeric variable and 0 otherwise.

`st_isstrvar(var)` returns 1 if *var* is a string variable and 0 otherwise.

Syntax

string scalar `st_vartype(scalar var)`

real scalar `st_isnumvar(scalar var)`

real scalar `st_isstrvar(scalar var)`

where *var* contains a Stata variable name or a Stata variable index.

Remarks and examples

[stata.com](#)

`st_isstrvar(var)` and `st_isnumvar(var)` are antonyms. Both functions are provided merely for convenience; they tell you nothing that you cannot discover from `st_vartype(var)`.

Conformability

```
st_vartype(var):
  var:      1 × 1
  result:   1 × 1
```

```
st_isnumvar(var), st_isstrvar(var):
  var:      1 × 1
  result:   1 × 1
```

Diagnostics

All functions abort with error if *var* is not a valid Stata variable.

Also see

[M-4] [stata](#) — Stata interface functions