Title

strdup() — String duplication

Description Syntax Conformability Diagnostics Also see

Description

There is no `strdup()` function. Instead, the multiplication operator is used:

```
3*"example" = "exampleexampleexample"
"café"*2 = "cafécafé"
0*"this" = ""
```

Syntax

n * *s*

s * *n*

n :* *s*

s :* *n*

where *n* is real and *s* is string.

Conformability

*n**s*, *s**n*:

n:	1×1
s:	$r \times c$
result:	$r \times c$

n:*s*, *s*:*n*:

n:	$r_1 \times c_1$
s:	$r_2 \times c_2$, *n* and *s* c-conformable
result:	$\max(r_1,r_2) \times \max(c_1,c_2)$

Diagnostics

If $n < 0$, the result is as if $n = 0$: `""` is returned.

If *n* is not an integer, the result is as if `trunc(`*n*`)` were specified.

Also see

[M-4] **String** — String manipulation functions

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.