

**mecloglog postestimation** — Postestimation tools for mecloglog

[Postestimation commands](#)
[predict](#)
[margins](#)
[Remarks and examples](#)
[Methods and formulas](#)
[Also see](#)

## Postestimation commands

The following postestimation command is of special interest after `mecloglog`:

Command	Description
<code>estat group</code>	summarize the composition of the nested groups
<code>estat sd</code>	display variance components as standard deviations and correlations

The following standard postestimation commands are also available:

Command	Description
<code>contrast</code>	contrasts and ANOVA-style joint tests of estimates
<code>estat ic</code>	Akaike's and Schwarz's Bayesian information criteria (AIC and BIC)
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance–covariance matrix of the estimators (VCE)
<code>estat (svy)</code>	postestimation statistics for survey data
<code>estimates</code>	cataloging estimation results
* <code>hausman</code>	Hausman's specification test
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of coefficients
* <code>lrtest</code>	likelihood-ratio test
<code>margins</code>	marginal means, predictive margins, marginal effects, and average marginal effects
<code>marginsplot</code>	graph the results from margins (profile plots, interaction plots, etc.)
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of coefficients
<code>predict</code>	predictions, residuals, influence statistics, and other diagnostic measures
<code>predictnl</code>	point estimates, standard errors, testing, and inference for generalized predictions
<code>pwcompare</code>	pairwise comparisons of estimates
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

\* `hausman` and `lrtest` are not appropriate with `svy` estimation results.

# predict

## Description for predict

`predict` creates a new variable containing predictions such as mean responses; linear predictions; density and distribution functions; standard errors; and Pearson, deviance, and Anscombe residuals.

## Menu for predict

Statistics > Postestimation

## Syntax for predict

*Syntax for obtaining predictions of the outcome and other statistics*

```
predict [type] newvarsspec [if] [in] [, statistic options]
```

*Syntax for obtaining estimated random effects and their standard errors*

```
predict [type] newvarsspec [if] [in], reffects [re_options]
```

*Syntax for obtaining ML scores*

```
predict [type] newvarsspec [if] [in], scores
```

*newvarsspec* is *stub\** or *newvarlist*.

<i>statistic</i>	Description
------------------	-------------

Main

<code>mu</code>	mean response; the default
<code>eta</code>	fitted linear predictor
<code>xb</code>	linear predictor for the fixed portion of the model only
<code>stdp</code>	standard error of the fixed-portion linear prediction
<code>density</code>	predicted density function
<code>distribution</code>	predicted distribution function
<code>pearson</code>	Pearson residuals
<code>deviance</code>	deviance residuals
<code>anscombe</code>	Anscombe residuals

These statistics are available both in and out of sample; type `predict ... if e(sample) ...` if wanted only for the estimation sample.

<i>options</i>	Description
Main	
<u>conditional</u> ( <i>ctype</i> )	compute <i>statistic</i> conditional on estimated random effects; default is <code>conditional(ebmeans)</code>
<u>marginal</u>	compute <i>statistic</i> marginally with respect to the random effects
<u>nooffset</u>	make calculation ignoring offset or exposure
Integration	
<u>int_options</u>	integration options
pearson, deviance, anscombe may not be combined with marginal.	
<i>ctype</i>	Description
<u>ebmeans</u>	empirical Bayes means of random effects; the default
<u>ebmodes</u>	empirical Bayes modes of random effects
<u>fixedonly</u>	prediction for the fixed portion of the model only
<i>re_options</i>	Description
Main	
<u>ebmeans</u>	use empirical Bayes means of random effects; the default
<u>ebmodes</u>	use empirical Bayes modes of random effects
<u>reses</u> ( <i>stub*</i>   <i>newvarlist</i> )	calculate standard errors of empirical Bayes estimates
Integration	
<u>int_options</u>	integration options
<i>int_options</i>	Description
<u>intpoints</u> (#)	use # quadrature points to compute marginal predictions and empirical Bayes means
<u>iterate</u> (#)	set maximum number of iterations in computing statistics involving empirical Bayes estimators
<u>tolerance</u> (#)	set convergence tolerance for computing statistics involving empirical Bayes estimators

## Options for predict

### Main

`mu`, the default, calculates the predicted mean, that is, the probability of a positive outcome.  
`eta`, `xb`, `stdp`, `density`, `distribution`, `pearson`, `deviance`, `anscombe`, `scores`, `conditional()`, `marginal`, and `nooffset`; see [ME] [meglm postestimation](#).  
`reffects`, `ebmeans`, `ebmodes`, and `reses()`; see [ME] [meglm postestimation](#).

### Integration

`intpoints()`, `iterate()`, and `tolerance()`; see [ME] [meglm postestimation](#).

## margins

### Description for margins

`margins` estimates margins of response for mean responses and linear predictions.

### Menu for margins

Statistics > Postestimation

### Syntax for margins

```
margins [marginlist] [, options]
```

```
margins [marginlist] , predict(statistic ...) [predict(statistic ...) ...] [options]
```

<i>statistic</i>	Description
<code>mu</code>	mean response; the default
<code>eta</code>	fitted linear predictor
<code>xb</code>	linear predictor for the fixed portion of the model only
<code>stdp</code>	not allowed with <code>margins</code>
<code>density</code>	not allowed with <code>margins</code>
<code>distribution</code>	not allowed with <code>margins</code>
<code>pearson</code>	not allowed with <code>margins</code>
<code>deviance</code>	not allowed with <code>margins</code>
<code>anscombe</code>	not allowed with <code>margins</code>
<code>reffects</code>	not allowed with <code>margins</code>
<code>scores</code>	not allowed with <code>margins</code>

Options `conditional(ebmeans)` and `conditional(ebmodes)` are not allowed with `margins`.

Option `marginal` is assumed where applicable if `conditional(fixedonly)` is not specified.

Statistics not allowed with `margins` are functions of stochastic quantities other than  $e(b)$ .

For the full syntax, see [R] [margins](#).

### Remarks and examples

[stata.com](#)

Various predictions, statistics, and diagnostic measures are available after fitting a mixed-effects complementary log-log model with `mecloglog`. Here we show a short example of predicted probabilities and predicted random effects; refer to [ME] [meglm postestimation](#) for additional examples.

#### ► Example 1: Obtaining predicted probabilities and random effects

In [example 2](#) of [ME] [mecloglog](#), we analyzed the cognitive ability (`dtlm`) of patients with schizophrenia compared with their relatives and control subjects, by using a three-level complementary log-log model with random effects at the family and subject levels. Cognitive ability was measured as the successful completion of the “Tower of London”, a computerized task, measured at three levels of difficulty.



Here we list the data for family 16:

```
. list family subject dtlm pr re1 re2 if family==16, sepby(subject)
```

	family	subject	dtlm	pr	re1	re2
208.	16	5	1	.486453	.4184933	.2760492
209.	16	5	0	.1597047	.4184933	.2760492
210.	16	5	0	.0444156	.4184933	.2760492
211.	16	34	1	.9659582	.4184933	1.261488
212.	16	34	1	.5862808	.4184933	1.261488
213.	16	34	1	.205816	.4184933	1.261488
214.	16	35	0	.5571261	.4184933	-.1616545
215.	16	35	1	.1915688	.4184933	-.1616545
216.	16	35	0	.0540124	.4184933	-.1616545

We can see that the predicted random effects (**re1**) at the family level are the same for all members of the family. Similarly, the predicted random effects (**re2**) at the individual level are constant within each individual.

◀

## Methods and formulas

Methods and formulas for predicting random effects and other statistics are given in *Methods and formulas* of [ME] **meglm postestimation**.

## Also see

[ME] **mecloglog** — Multilevel mixed-effects complementary log-log regression

[ME] **meglm postestimation** — Postestimation tools for meglm

[U] **20 Estimation and postestimation commands**