

[Description](#)[Remarks and examples](#)[Quick start](#)[Stored results](#)[Menu for estat](#)[Methods and formulas](#)[Syntax](#)[References](#)[Options](#)[Also see](#)

## Description

`estat classification` reports various summary statistics, including the classification table.

`estat classification` requires that the current estimation results be from `logistic`, `logit`, `probit`, or `ivprobit`; see [\[R\] logistic](#), [\[R\] logit](#), [\[R\] probit](#), or [\[R\] ivprobit](#).

## Quick start

Display classification table and related statistics for current estimation results

```
estat classification
```

Change probability threshold for assignment to positive outcome to 75%

```
estat classification, cutoff(.75)
```

Classification for observations with `catvar = 2`

```
estat classification if catvar==2
```

## Menu for estat

Statistics > Postestimation

## Syntax

```
estat classification [if] [in] [weight] [, options]
```

<i>options</i>	Description
Main	
<code>all</code>	display summary statistics for all observations in the data
<code>cutoff(#)</code>	positive outcome threshold; default is <code>cutoff(0.5)</code>
<code>estat classification</code> is not appropriate with <code>svy</code> estimation results.	
<code>collect</code> is allowed; see <a href="#">[U] 11.1.10 Prefix commands</a> .	
<code>fweights</code> are allowed; see <a href="#">[U] 11.1.6 weight</a> .	

## Options

Main

`all` requests that the statistic be computed for all observations in the data, ignoring any `if` or `in` restrictions specified by the estimation command.

`cutoff(#)` specifies the value for determining whether an observation has a predicted positive outcome. An observation is classified as positive if its predicted probability is  $\geq \#$ . The default is 0.5.

## Remarks and examples

`estat classification` presents the classification statistics and classification table after `logistic`, `logit`, `probit`, or `ivprobit`.

Statistics are produced either for the estimation sample (the default) or for any set of observations. When weights, `if`, or `in` is used with the estimation command, it is not necessary to repeat the qualifier when you want statistics computed for the estimation sample. Specify `if`, `in`, or the `all` option only when you want statistics computed for a set of observations other than the estimation sample. Specify `weights` only when you want to use a different set of weights.

## ► Example 1

We illustrate `estat classification` after `logistic`; see [\[R\] logistic](#).

```
. use https://www.stata-press.com/data/r19/lbw
(Hosmer & Lemeshow data)
```

```
. logistic low age lwt i.race smoke ptl ht ui
(output omitted)
```

```
. estat classification
```

Logistic model for low

Classified	True		Total
	D	~D	
+	21	12	33
-	38	118	156
Total	59	130	189

Classified + if predicted  $\Pr(D) \geq .5$

True D defined as low != 0

Sensitivity	$\Pr(+ D)$	35.59%
Specificity	$\Pr(- \sim D)$	90.77%
Positive predictive value	$\Pr(D +)$	63.64%
Negative predictive value	$\Pr(\sim D -)$	75.64%

False + rate for true ~D	$\Pr(+ \sim D)$	9.23%
False - rate for true D	$\Pr(- D)$	64.41%
False + rate for classified +	$\Pr(\sim D +)$	36.36%
False - rate for classified -	$\Pr(D -)$	24.36%

Correctly classified	73.54%
----------------------	--------

The overall rate of correct classification is estimated to be 73.54, with 90.77% of the normal weight group correctly classified (specificity) and only 35.59% of the low weight group correctly classified (sensitivity). Classification is sensitive to the relative sizes of each component group, and always favors classification into the larger group. This phenomenon is evident here.

By default, `estat classification` uses a cutoff of 0.5, although you can vary this with the `cutoff()` option. You can use the `lsens` command to review the potential cutoffs; see [\[R\] lsens](#).

## Stored results

`estat classification` stores the following in `r()`:

### Scalars

<code>r(P_corr)</code>	percent correctly classified
<code>r(P_p1)</code>	sensitivity
<code>r(P_n0)</code>	specificity
<code>r(P_p0)</code>	false-positive rate given true negative
<code>r(P_n1)</code>	false-negative rate given true positive
<code>r(P_1p)</code>	positive predictive value
<code>r(P_0n)</code>	negative predictive value
<code>r(P_0p)</code>	false-positive rate given classified positive
<code>r(P_1n)</code>	false-negative rate given classified negative

### Matrices

<code>r(ctable)</code>	classification table
------------------------	----------------------

## Methods and formulas

Let  $j$  index observations. Define  $c$  as the `cutoff()` specified by the user or, if not specified, as 0.5. Let  $p_j$  be the predicted probability of a positive outcome and  $y_j$  be the actual outcome, which we will treat as 0 or 1, although Stata treats it as 0 and non-0, excluding missing observations.

A prediction is classified as *positive* if  $p_j \geq c$  and otherwise is classified as *negative*. The classification is *correct* if it is *positive* and  $y_j = 1$  or if it is *negative* and  $y_j = 0$ .

*Sensitivity* is the fraction of  $y_j = 1$  observations that are correctly classified. *Specificity* is the percentage of  $y_j = 0$  observations that are correctly classified.

## References

- Hosmer, D. W., Jr., S. A. Lemeshow, and R. X. Sturdivant. 2013. *Applied Logistic Regression*. 3rd ed. Hoboken, NJ: Wiley.
- Kohler, U., and F. Kreuter. 2012. *Data Analysis Using Stata*. 3rd ed. College Station, TX: Stata Press.

## Also see

- [R] **logistic** — Logistic regression, reporting odds ratios
- [R] **logit** — Logistic regression, reporting coefficients
- [R] **probit** — Probit regression
- [R] **ivprobit** — Probit model with continuous endogenous covariates
- [R] **lroc** — Compute area under ROC curve and graph the curve
- [R] **lsens** — Graph sensitivity and specificity versus probability cutoff
- [R] **estat gof** — Pearson or Hosmer–Lemeshow goodness-of-fit test
- [R] **roc** — Receiver operating characteristic (ROC) analysis

### [U] 20 Estimation and postestimation commands

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).