

**rreg postestimation** — Postestimation tools for rreg

[Postestimation commands](#)   
 [predict](#)   
 [margins](#)   
 [Also see](#)

## Postestimation commands

The following postestimation commands are available after `rreg`:

Command	Description
<code>contrast</code>	contrasts and ANOVA-style joint tests of estimates
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance-covariance matrix of the estimators (VCE)
<code>estimates</code>	cataloging estimation results
* <code>forecast</code>	dynamic forecasts and simulations
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of coefficients
<code>margins</code>	marginal means, predictive margins, marginal effects, and average marginal effects
<code>marginsplot</code>	graph the results from margins (profile plots, interaction plots, etc.)
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of coefficients
<code>predict</code>	predictions, residuals, influence statistics, and other diagnostic measures
<code>predictnl</code>	point estimates, standard errors, testing, and inference for generalized predictions
<code>pwcompare</code>	pairwise comparisons of estimates
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

\* `forecast` is not appropriate with `mi` estimation results.

## predict

### Description for predict

`predict` creates a new variable containing predictions such as linear predictions, standard errors, residuals, and diagonal elements of the hat matrix.

### Menu for predict

Statistics > Postestimation

### Syntax for predict

```
predict [type] newvar [if] [in] [, statistic]
```

<i>statistic</i>	Description
------------------	-------------

---

Main

<code>xb</code>	linear prediction; the default
<code>stdp</code>	standard error of the linear prediction
<code>residuals</code>	residuals
<code>hat</code>	diagonal elements of the hat matrix

---

These statistics are available both in and out of sample; type `predict ... if e(sample) ...` if wanted only for the estimation sample.

### Options for predict

Main

---

`xb`, the default, calculates the linear prediction.

`stdp` calculates the standard error of the linear prediction.

`residuals` calculates the residuals.

`hat` calculates the diagonal elements of the hat matrix. You must have run the `rreg` command with the `genwt()` option.

# margins

## Description for margins

`margins` estimates margins of response for linear predictions.

## Menu for margins

Statistics > Postestimation

## Syntax for margins

```

margins [marginlist] [, options]
margins [marginlist] , predict(statistic ...) [options]

```

<i>statistic</i>	Description
<code>xb</code>	linear prediction; the default
<code>stdp</code>	not allowed with <code>margins</code>
<code><u>r</u>esiduals</code>	not allowed with <code>margins</code>
<code>hat</code>	not allowed with <code>margins</code>

Statistics not allowed with `margins` are functions of stochastic quantities other than  $e(b)$ .

For the full syntax, see [R] [margins](#).

## Also see

[R] [rreg](#) — Robust regression

[U] [20 Estimation and postestimation commands](#)