

Description

`simulate` eases the programming task of performing Monte Carlo–type simulations. Typing

```
. simulate exp_list, reps(#): command
```

runs *command* for # replications and collects the results in *exp_list*.

command defines the command that performs one simulation. Most Stata commands and user-written programs can be used with `simulate`, as long as they follow standard Stata syntax; see [\[U\] 11 Language syntax](#). The `by` prefix may not be part of *command*.

exp_list specifies the expression to be calculated from the execution of *command*. If no expressions are given, *exp_list* assumes a default, depending upon whether *command* changes results in `e()` or `r()`. If *command* changes results in `e()`, the default is `_b`. If *command* changes results in `r()` (but not `e()`), the default is all the scalars posted to `r()`. It is an error not to specify an expression in *exp_list* otherwise.

Quick start

Simple program for use with simulate

Define program `myreg` to generate data and fit a linear regression

```
program myreg, eclass
    drop _all
    set obs 25
    generate x = rnormal()
    generate y = 3*x + 1 + rnormal()
    regress y x
end
```

Perform simulation

Record coefficients and SEs from 1,000 simulated replications of program `myreg`

```
simulate _b _se, reps(1000): myreg
```

Same as above, and set random-number seed to 5,762 for reproducible results

```
simulate _b _se, reps(1000) seed(5762): myreg
```

Syntax

```
simulate [exp_list], reps(#) [options] : command
```

options	Description
nodots	suppress replication dots
dots(#)	display dots every # replications
noisily	display any output from <i>command</i>
trace	trace <i>command</i>
saving(<i>filename</i> , ...)	save results to <i>filename</i>
nolegend	suppress table legend
verbose	display the full table legend
seed(#)	set random-number seed to #

All weight types supported by *command* are allowed; see [U] 11.1.6 [weight](#).

<i>exp_list</i> contains	(<i>name</i> : <i>elist</i>) <i>elist</i> <i>eexp</i>
<i>elist</i> contains	<i>newvar</i> = (<i>exp</i>) (<i>exp</i>)
<i>eexp</i> is	<i>specname</i> [<i>eqno</i>] <i>specname</i>
<i>specname</i> is	_b _b [] _se _se []
<i>eqno</i> is	# # <i>name</i>

exp is a standard Stata expression; see [U] 13 [Functions and expressions](#).

Distinguish between [], which are to be typed, and [], which indicate optional arguments.

Options

reps(#) is required—it specifies the number of replications to be performed.

nodots and dots(#) specify whether to display replication dots. By default, one dot character is displayed for each successful replication. An “x” is displayed if *command* returns an error or if any value in *exp_list* is missing. You can also control whether dots are displayed using set dots; see [R] [set](#).

nodots suppresses display of the replication dots.

dots(#) displays dots every # replications. dots(0) is a synonym for nodots.

noisily requests that any output from *command* be displayed. This option implies the nodots option.

trace causes a trace of the execution of *command* to be displayed. This option implies the noisily option.

`saving(filename[, suboptions])` creates a Stata data file (`.dta` file) consisting of (for each statistic in *exp_list*) a variable containing the replicates.

`double` specifies that the results for each replication be saved as doubles, meaning 8-byte reals. By default, they are saved as floats, meaning 4-byte reals.

`every(#)` specifies that results be written to disk every *#*th replication. `every()` should be specified only in conjunction with `saving()` when *command* takes a long time for each replication. This will allow recovery of partial results should some other software crash your computer. See [P] [postfile](#).

`replace` specifies that *filename* be overwritten if it exists.

`nolegend` suppresses display of the table legend. The table legend identifies the rows of the table with the expressions they represent.

`verbose` requests that the full table legend be displayed. By default, coefficients and standard errors are not displayed.

`seed(#)` sets the random-number seed. Specifying this option is equivalent to typing the following command before calling `simulate`:

```
. set seed #
```

Remarks and examples

For an introduction to Monte Carlo methods, see [Cameron and Trivedi \(2022, chap. 5\)](#). [White \(2010\)](#) provides a command for analyzing results of simulation studies.

► Example 1: Simulating basic summary statistics

We have a dataset containing means and variances of 100-observation samples from a lognormal distribution (as a first step in evaluating, say, the coverage of a 95%, *t*-based confidence interval). Then we perform the experiment 1,000 times.

The following command definition will generate 100 independent observations from a lognormal distribution and compute the summary statistics for this sample.

```
program lnsim, rclass
    version 19.5      // (or version 19 if you do not have StataNow)
    drop _all
    set obs 100
    generate z = exp(rnormal())
    summarize z
    return scalar mean = r(mean)
    return scalar Var  = r(Var)
end
```

We can save 1,000 simulated means and variances from `lnsim` by typing

```
. set seed 1234
. simulate mean=r(mean) var=r(Var), reps(1000) nodots: lnsim

Command: lnsim
       mean: r(mean)
       var: r(Var)
```

```
. describe *
```

Variable name	Storage type	Display format	Value label	Variable label
mean	float	%9.0g		r(mean)
var	float	%9.0g		r(Var)

```
. summarize
```

Variable	Obs	Mean	Std. dev.	Min	Max
mean	1,000	1.630648	.2173062	1.106372	2.612052
var	1,000	4.60798	4.502166	.966087	70.5597



□ Technical note

Before executing our `lnsim` simulator, we can verify that it works by executing it interactively.

```
. set seed 1234
. lnsim
Number of observations (_N) was 0, now 100.
```

Variable	Obs	Mean	Std. dev.	Min	Max
z	100	1.534256	1.584568	.0400387	9.818309

```
. return list
scalars:
      r(Var) = 2.510857086217961
      r(mean) = 1.53425569280982
```



▷ Example 2: Simulating a regression model

Consider a more complicated problem. Let's experiment with fitting $y_j = a + bx_j + u_j$ when the true model has $a = 1$, $b = 2$, $u_j = z_j + cx_j$, and when z_j is $N(0, 1)$. We will save the parameter estimates and standard errors and experiment with varying c . x_j will be fixed across experiments but will originally be generated as $N(0, 1)$. We begin by interactively making the true data:

```
. drop _all
. set obs 100
Number of observations (_N) was 0, now 100.
. set seed 54321
. generate x = rnormal()
. generate true_y = 1+2*x
. save truth
file truth.dta saved
```

Our program is

```
program hetero1
    version 19.5        // (or version 19 if you do not have StataNow)
    args c
    use truth, clear
    generate y = true_y + (rnormal() + 'c'*x)
    regress y x
end
```

Note the use of ‘c’ in our statement for generating y. c is a local macro generated from args c and thus refers to the first argument supplied to hetero1. If we want $c = 3$ for our experiment, we type

```
. simulate _b _se, reps(10000): hetero1 3
(output omitted)
```

Our program hetero1 could, however, be more efficient because it rereads the file truth once every replication. It would be better if we could read the data just once. In fact, if we read in the data right before running simulate, we really should not have to reread for each subsequent replication. A faster version reads

```
program hetero2
    version 19.5          // (or version 19 if you do not have StataNow)
    args c
    capture drop y
    generate y = true_y + (rnormal() + 'c'*x)
    regress y x
end
```

Requiring that the current dataset has the variables true_y and x may become inconvenient. Another improvement would be to require that the user supply variable names, such as in

```
program hetero3
    version 19.5          // (or version 19 if you do not have StataNow)
    args truey x c
    capture drop y
    generate y = 'truey' + (rnormal() + 'c'*'x')
    regress y x
end
```

Thus, we can type

```
. simulate _b _se, reps(10000): hetero3 true_y x 3
(output omitted)
```

◀

▷ Example 3: Simulating a ratio of statistics

Now, let's consider the problem of simulating the ratio of two medians. Suppose that each sample of size n_i comes from a normal population with a mean μ_i and standard deviation σ_i , where $i = 1, 2$. We write the program below and save it as a text file called myratio.ado (see [\[U\] 17 Ado-files](#)). Our program is an rclass command that requires six arguments as input, identified by the local macros n1, mu1, sigma1, n2, mu2, and sigma2, which correspond to n_1 , μ_1 , σ_1 , n_2 , μ_2 , and σ_2 , respectively. With these arguments, myratio will generate the data for the two samples, use summarize to compute the two medians and store the ratio of the medians in r(ratio).

```
program myratio, rclass
    version 19.5          // (or version 19 if you do not have StataNow)
    args n1 mu1 sigma1 n2 mu2 sigma2
    // generate the data
    drop _all
    local N = 'n1'+ 'n2'
    set obs 'N'
    tempvar y
    generate 'y' = rnormal()
    replace 'y' = cond(_n<='n1', 'mu1'+ 'y'*'sigma1', 'mu2'+ 'y'*'sigma2')
    // calculate the medians
    tempname m1
```

```

        summarize 'y' if _n<='n1', detail
        scalar 'm1' = r(p50)
        summarize 'y' if _n>'n1', detail
        // store the results
        return scalar ratio = 'm1' / r(p50)
    end

```

The result of running our simulation is

```

. set seed 19192
. simulate ratio=r(ratio), reps(1000) nodots: myratio 5 3 1 10 3 2
    Command: myratio 5 3 1 10 3 2
           ratio: r(ratio)

. summarize

```

Variable	Obs	Mean	Std. dev.	Min	Max
ratio	1,000	1.10875	.5219166	.3606606	9.857285

◀

□ Technical note

Stata lets us do simulations of simulations and simulations of bootstraps. Stata's `bootstrap` command (see [R] [bootstrap](#)) works much like `simulate`, except that it feeds the user-written program a bootstrap sample. Say that we want to evaluate the bootstrap estimator of the standard error of the median when applied to lognormally distributed data. We want to perform a simulation, resulting in a dataset of medians and bootstrap estimated standard errors.

As background, `summarize` (see [R] [summarize](#)) calculates summary statistics, leaving the mean in `r(mean)` and the standard deviation in `r(sd)`. `summarize` with the `detail` option also calculates summary statistics, but more of them, and leaves the median in `r(p50)`.

Thus, our plan is to perform simulations by randomly drawing a dataset: we calculate the median of our random sample, we use `bootstrap` to obtain a dataset of medians calculated from bootstrap samples of our random sample, the standard deviation of those medians is our estimate of the standard error, and the summary statistics are stored in the results of `summarize`.

Our simulator is

```

program define bsse, rclass
    version 19.5          // (or version 19 if you do not have StataNow)
    drop _all
    set obs 100
    generate x = rnormal()
    tempfile bsfile
    bootstrap midp=r(p50), rep(100) saving('bsfile'): summarize x, detail
    use 'bsfile', clear
    summarize midp
    return scalar mean = r(mean)
    return scalar sd   = r(sd)
end

```

We can obtain final results, running our simulation 1,000 times, by typing

```
. set seed 48901
. simulate med=r(mean) bs_se=r(sd), reps(1000): bsse
      Command: bsse
              med: r(mean)
              bs_se: r(sd)

Simulations (1,000): .....10.....20.....30.....40.....50....
> .....60.....70.....80.....90.....100.....110.....120..
> .....130.....140.....150.....160.....170.....180.....
> .....190.....200.....210.....220.....230.....240.....250..
> .....260.....270.....280.....290.....300.....310.....
> .....320.....330.....340.....350.....360.....370.....380..
> .....390.....400.....410.....420.....430.....440.....
> .....450.....460.....470.....480.....490.....500.....510..
> .....520.....530.....540.....550.....560.....570.....
> .....580.....590.....600.....610.....620.....630.....640..
> .....650.....660.....670.....680.....690.....700.....
> .....710.....720.....730.....740.....750.....760.....770..
> .....780.....790.....800.....810.....820.....830.....
> .....840.....850.....860.....870.....880.....890.....900..
> .....910.....920.....930.....940.....950.....960.....
> .....970.....980.....990.....1,000 done

. summarize
```

Variable	Obs	Mean	Std. dev.	Min	Max
med	1,000	-.0013359	.1221602	-.3795549	.3656219
bs_se	1,000	.1278773	.0303109	.0614031	.2484805

This is a case where the simulation dots (drawn by default, unless the `nodots` option is specified) will give us an idea of how long this simulation will take to finish as it runs.



References

Cameron, A. C., and P. K. Trivedi. 2022. *Microeconometrics Using Stata*. 2nd ed. College Station, TX: Stata Press.

Hilbe, J. M. 2010. [Creating synthetic discrete-response regression models](#). *Stata Journal* 10: 104–124.

Taylor, M. A. 2018. [Simulating the central limit theorem](#). *Stata Journal* 18: 345–356.

White, I. R. 2010. [simsum: Analyses of simulation studies including Monte Carlo error](#). *Stata Journal* 10: 369–385.

Also see

- [R] [bootstrap](#) — Bootstrap sampling and estimation
- [R] [jackknife](#) — Jackknife estimation
- [R] [permute](#) — Permutation tests
- [R] [set rngstream](#) — Specify the stream for the stream random-number generator

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).