#### arimasoc - Obtain lag-order selection statistics for ARMAs

Description	Quick start
Options	Remarks and examples
References	Also see

Menu Stored results Syntax Methods and formulas

# Description

arimasoc reports Akaike's information criterion (AIC), Schwarz's Bayesian information criterion (BIC), and the Hannan and Quinn information criterion (HQIC) for a series of autoregressive movingaverage (ARMA) models. These criteria are used to select the number of autoregressive (AR) and movingaverage (MA) lags to be used in the ARMA model.

# **Quick start**

Compute AIC, BIC, and HQIC for ARMA models of y with up to 2 AR and 2 MA lags arimasoc y

Same as above, but compare ARMA models of y with up to 7 AR lags and 1 MA lag arimasoc y, maxar(7) maxma(1)

Pass the option condition to the underlying arima estimation

arimasocy, arimaopts(condition)

```
Limit the number of iterations in arima estimation to 50
```

arimasoc y, arimaopts(iterate(50))

Compute AIC, BIC, and HQIC for ARMAX models of y with exogenous regressor x, and with up to 2 AR lags and 2 MA lags

 $\verb|arimasocyx||$ 

Compute information criteria for ARMA models in the difference of y arimasoc d.y

### Menu

Statistics > Time series > ARIMA and ARMAX > Lag-order selection

## Syntax

options	Description	
Main		
maxar(#)	set maximum AR order to #; default is maxar(2)	
maxma(#)	set maximum MA order to #; default is maxma(2)	
n(#)	use $N$ when calculating BIC and HOIC	
arimaopts( <i>opts</i> )	specify options of arima for model estimation	

arimasoc depvar [indepvars] [if] [in] [, options]

You must tsset your data before using arimasoc; see [TS] tsset. depvar and indepvars may contain time-series operators; see [U] 11.4.4 Time-series varlists.

# Options

\_ Main

- maxar(#) specifies the maximum AR lag order for which the information criteria are to be calculated. The default is maxar(2).
- maxma(#) specifies the maximum MA lag order for which the information criteria are to be calculated. The default is maxma(2).
- n(#) sets N to be used when calculating BIC and HQIC; see [R] IC note.
- arimaopts(opts) specifies options of arima to include in the ARMAs fit by arimasoc. opts
  may be noconstant, sarima(), mar(), mma(), condition, savespace, diffuse, difficult,
  technique(), iterate(), tolerance(), ltolerance(), nrtolerance(), gtolerance(),
  nonrtolerance, and collinear. See [TS] arima for a description of these options.

## **Remarks and examples**

Information criteria are statistics that help researchers choose the best model. In general, these statistics balance goodness of fit against parsimony. The statistics decrease with the model's goodness of fit, as assessed by the likelihood function, and increase with the number of parameters. Therefore, the selected model is the one that minimizes the information criterion, or equivalently, the model that best fits the data while using the fewest parameters possible.

arimasoc computes three information criteria (AIC, BIC, and HQIC) that help researchers determine the correct number of AR and MA lags to be included in an ARMA model. arimasoc calculates these criteria for ARMA models with up to p AR lags and q MA lags, where p and q are predetermined numbers. arimasoc keeps the sample and option specifications the same in the estimation of all the different ARMA models.

Different information criteria may choose different models. Among the three information criteria available, the BIC and HQIC have the advantage that they are consistent. This means that as the sample size grows, they select the correct number of lags with probability approaching one. However, there is a positive probability that AIC will select more lags than necessary, even with an infinite sample size. See Brockwell and Davis (2016, 149–151).

#### Example 1: Basic example

We use arimasoc on US macro data to fit several ARMA models of the output gap.

```
. use https://www.stata-press.com/data/r19/usmacro
(Federal Reserve Economic Data - St. Louis Fed)
. arimasoc ogap
Fitting models (9): ..... done
Lag-order selection criteria
Sample: 1954q3 thru 2010q4 Number of obs = 226
Model LL df AIC BIC HOIC
```

Model	LL	df	AIC	BIC	HQIC
ARMA(0,0)	-549.4036	2	1102.807	1109.648	1105.568
ARMA(0,1)	-435.0753	3	876.1507	886.4123	880.2919
ARMA(0,2)	-361.249	4	730.4981	744.1802	736.0196
ARMA(1,0)	-292.3313	3	590.6625	600.9241	594.8037
ARMA(1,1)	-281.5762	4	571.1524	584.8345	576.6739
ARMA(1,2)	-275.3697	5	560.7395	577.8422	567.6414
ARMA(2,0)	-276.5956	4	561.1912	574.8733	566.7127
ARMA(2,1)	-273.9052	5	557.8104	574.9131	564.7123
ARMA(2,2)	-273.2799	6	558.5599	579.0831	566.8422
Selected (max)	) LL: ARMA(2.)	2)			

Selected (min) AIC: ARMA(2,1) Selected (min) BIC: ARMA(2,0) Selected (min) HQIC: ARMA(2,1)

The default maximum AR lag p and MA lag q are both 2. The table provides results for each AR and MA combination, beginning with a constant-only model ARMA(0,0). The column LL reports the log likelihood, and the column df reports the number of estimated parameters. In this example, the log likelihood is maximized with the most complex model, ARMA(2,2). AIC and HQIC select a model with two AR lags and one MA lag. BIC has selected a model with two AR lags and no MA terms. Model selection criteria can disagree because they put different penalties on the complexity of the model, as measured by the number of parameters estimated. All selection criteria here suggest two AR lags, but they differ in their recommendation of MA terms.

4

### Example 2: Changing the maximum order

Continuing with example 1, we want to change the maximum lag order for both AR and MA. We will use the maxar() and maxma() options for this. We include up to three AR lags and up to one MA lag.

. arimasoc oga Fitting models	p, maxar(3) maxma (8): do	a(1) one			
Lag-order sele	ction criteria				
Sample: 1954q3	thru 2010q4			Number of	obs = 226
Model	LL	df	AIC	BIC	HQIC
ARMA(0,0)	-549.4036	2	1102.807	1109.648	1105.568
ARMA(0,1)	-435.0753	3	876.1507	886.4123	880.2919
ARMA(1,0)	-292.3313	3	590.6625	600.9241	594.8037
ARMA(1,1)	-281.5762	4	571.1524	584.8345	576.6739
ARMA(2,0)	-276.5956	4	561.1912	574.8733	566.7127
ARMA(2,1)	-273.9052	5	557.8104	574.9131	564.7123
ARMA(3,0)	-273.2421	5	556.4843	573.587	563.3862
ARMA(3,1)	-273.1883	6	558.3766	578.8998	566.6589
Selected (max) Selected (min)	LL: ARMA(3,1) AIC: ARMA(3,0)				
Selected (min)	BIC: ARMA(3,0)				
Selected (min)	HQIC: ARMA(3,0)				

Again, the log likelihood is maximized with the most complex model, using the full three AR lags and one MA lag. The information criteria all select the model with three AR lags and zero MA lags. Because the selected model is on the boundary of the range of AR terms, it may be worthwhile to consider an even larger range of AR terms to ensure that we have found the true minimum of the information criteria.

## **Stored results**

arimasoc stores the following in r():

Scalars

r(N	1)	number of observations
r(a	ar_max)	maximum AR lag order
r(m	na_max)	maximum MA lag order
Macros		
r(d	lepvar)	name of endogenous variable
r(c	covariates)	names of exogenous variables
r(a	aic_sel)	selected ARMA model by AIC
r(b	oic_sel)	selected ARMA model by BIC
r(h	nqic_sel)	selected ARMA model by HQIC
r(1	ll_sel)	selected ARMA model by LL
r(a	aic_cmd)	selected ARMA command by AIC
r(b	pic_cmd)	selected ARMA command by BIC
r(h	nqic_cmd)	selected ARMA command by HQIC
r(1	ll_cmd)	selected ARMA command by LL
Matrices	ŝ	
r(t	able)	table of results
r(d	converged)	1 if converged, 0 otherwise

## Methods and formulas

Akaike's (1974) information criterion is defined as

$$AIC = -2\ln L + 2k$$

where  $\ln L$  is the maximized log likelihood of the model and k is the number of parameters estimated. Some authors define AIC as the expression above divided by the sample size.

Schwarz's (1978) Bayesian information criterion is another measure of fit. It is defined as

 $\mathrm{BIC} = -2\ln\!L + k\ln\!N$ 

where N is the sample size. See [R] IC note for additional information on calculating and interpreting BIC.

The Hannan and Quinn (1979) information criterion is another measure of fit. It is defined as

$$HQIC = -2\ln L + 2k\ln\ln N$$

### References

- Akaike, H. 1974. A new look at the statistical model identification. *IEEE Transactions on Automatic Control* 19: 716–723. https://doi.org/10.1109/TAC.1974.1100705.
- Brockwell, P. J., and R. A. Davis. 2016. Introduction to Time Series and Forecasting. 3rd ed. Cham, Switzerland: Springer.
- Hannan, E. J., and B. G. Quinn. 1979. The determination of the order of an autoregression. Journal of the Royal Statistical Society, B ser., 41: 190–195. https://doi.org/10.1111/j.2517-6161.1979.tb01072.x.
- Schwarz, G. 1978. Estimating the dimension of a model. Annals of Statistics 6: 461–464. https://doi.org/10.1214/aos/1176344136.

### Also see

- [TS] arima ARIMA, ARMAX, and other dynamic regression models
- [TS] arfimasoc Obtain lag-order selection statistics for ARFIMAs
- [TS] varsoc Obtain lag-order selection statistics for VAR and VEC models

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on citing Stata documentation.