

veclmar — LM test for residual autocorrelation after `vec`

[Description](#)
[Options](#)
[Reference](#)

[Quick start](#)
[Remarks and examples](#)
[Also see](#)

[Menu](#)
[Stored results](#)

[Syntax](#)
[Methods and formulas](#)

Description

`veclmar` implements a Lagrange multiplier (LM) test for autocorrelation in the residuals of vector error-correction models (VECMs).

Quick start

Test of residual autocorrelation for the first two lags of the residuals after `vec`
`veclmar`

Same as above, but test the first 5 lags
`veclmar, mlag(5)`

Same as above, but perform test using stored estimates `myest` from a VECM
`veclmar, mlag(5) estimates(myest)`

Menu

Statistics > Multivariate time series > VEC diagnostics and tests > LM test for residual autocorrelation

Syntax

```
veclmar [ , options ]
```

<i>options</i>	Description
<code>m^{lag}(#)</code>	use # for the maximum order of autocorrelation; default is <code>m^{lag}(2)</code>
<code>estimates(estname)</code>	use previously stored results <i>estname</i> ; default is to use active results
<code>separator(#)</code>	draw separator line after every # rows

`veclmar` can be used only after `vec`; see [TS] [vec](#).

You must `tsset` your data before using `veclmar`; see [TS] [tsset](#).

`collect` is allowed; see [U] [11.1.10 Prefix commands](#).

Options

`mlag(#)` specifies the maximum order of autocorrelation to be tested. The integer specified in `mlag(#)` must be greater than 0; the default is 2.

`estimates(estname)` requests that `veclmar` use the previously obtained set of `vec` estimates stored as *estname*. By default, `veclmar` uses the active results. See [R] [estimates](#) for information on manipulating estimation results.

`separator(#)` specifies how many rows should appear in the table between separator lines. By default, separator lines do not appear. For example, `separator(1)` would draw a line between each row, `separator(2)` between every other row, and so on.

Remarks and examples

[stata.com](http://www.stata.com)

Estimation, inference, and postestimation analysis of VECMs is predicated on the errors' not being autocorrelated. `veclmar` implements the LM test for autocorrelation in the residuals of a VECM discussed in [Johansen \(1995, 21–22\)](#). The test is performed at lags $j = 1, \dots, m^{lag}(#)$. For each j , the null hypothesis of the test is that there is no autocorrelation at lag j .

► Example 1

We fit a VECM using the regional income data described in [TS] [vec](#) and then call `veclmar` to test for autocorrelation.

```
. use https://www.stata-press.com/data/r18/rdinc
. vec ln_ne ln_se
  (output omitted)
. veclmar, mlag(4)

Lagrange-multiplier test
```

lag	chi2	df	Prob > chi2
1	8.9586	4	0.06214
2	4.9809	4	0.28926
3	4.8519	4	0.30284
4	0.3270	4	0.98801

H0: no autocorrelation at lag order

At the 5% level, we cannot reject the null hypothesis that there is no autocorrelation in the residuals for any of the orders tested. Thus this test finds no evidence of model misspecification.

◀

Stored results

veclmar stores the following in `r()`:

Matrices

`r(1m)` χ^2 , df, and p -values

Methods and formulas

Consider a VECM without any trend:

$$\Delta \mathbf{y}_t = \alpha \beta \mathbf{y}_{t-1} + \sum_{i=1}^{p-1} \Gamma_i \Delta \mathbf{y}_{t-i} + \epsilon_t$$

As discussed in [TS] `vec`, as long as the parameters in the cointegrating vectors, β , are exactly identified or overidentified, the estimates of these parameters are superconsistent. This implies that the $r \times 1$ vector of estimated cointegrating relations

$$\widehat{\mathbf{E}}_t = \widehat{\beta} \mathbf{y}_t \tag{1}$$

can be used as data with standard estimation and inference methods. When the parameters of the cointegrating equations are not identified, (1) does not provide consistent estimates of $\widehat{\mathbf{E}}_t$; in these cases, `veclmar` exits with an error message.

The VECM above can be rewritten as

$$\Delta \mathbf{y}_t = \alpha \widehat{\mathbf{E}}_t + \sum_{i=1}^{p-1} \Gamma_i \Delta \mathbf{y}_{t-i} + \epsilon_t$$

which is just a VAR with $p - 1$ lags where the endogenous variables have been first-differenced and is augmented with the exogenous variables $\widehat{\mathbf{E}}$. `veclmar` fits this VAR and then calls `varlmar` to compute the LM test for autocorrelation.

The above discussion assumes no trend and implicitly ignores constraints on the parameters in α . As discussed in `vec`, the other four trend specifications considered by Johansen (1995, sec. 5.7) complicate the estimation of the free parameters in β but do not alter the basic result that the $\widehat{\mathbf{E}}_t$ can be used as data in the subsequent VAR. Similarly, constraints on the parameters in α imply that the subsequent VAR must be estimated with these constraints applied, but $\widehat{\mathbf{E}}_t$ can still be used as data in the VAR.

See [TS] `varlmar` for more information on the Johansen LM test.

Reference

Johansen, S. 1995. *Likelihood-Based Inference in Cointegrated Vector Autoregressive Models*. Oxford: Oxford University Press.

Also see

[TS] **varlmar** — LM test for residual autocorrelation after var or svar

[TS] **vec** — Vector error-correction models

[TS] **vec intro** — Introduction to vector error-correction models

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

