

Postestimation commands

The following postestimation commands are available after xtnloglog:

Command	Description
<code>contrast</code>	contrasts and ANOVA-style joint tests of parameters
* <code>estat ic</code>	Akaike's, consistent Akaike's, corrected Akaike's, and Schwarz's Bayesian information criteria (AIC, CAIC, AICc, and BIC, respectively)
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance–covariance matrix of the estimators (VCE)
<code>estimates</code>	cataloging estimation results
<code>etable</code>	table of estimation results
† <code>forecast</code>	dynamic forecasts and simulations
<code>hausman</code>	Hausman's specification test
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of parameters
<code>lrtest</code>	likelihood-ratio test
<code>margins</code>	marginal means, predictive margins, marginal effects, and average marginal effects
<code>marginsplot</code>	graph the results from margins (profile plots, interaction plots, etc.)
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of parameters
<code>predict</code>	linear predictions and their SEs, probabilities
<code>predictnl</code>	point estimates, standard errors, testing, and inference for generalized predictions
<code>pwcompare</code>	pairwise comparisons of parameters
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

*`estat ic` is not appropriate after xtnloglog, `pa`.

†`forecast` is not appropriate with `mi` estimation results.

predict

Description for predict

predict creates a new variable containing predictions such as probabilities, linear predictions, standard errors, and the equation-level score.

Menu for predict

Statistics > Postestimation

Syntax for predict

Random-effects (RE) model

```
predict [type] newvar [if] [in] [ , RE_statistic nooffset ]
```

Population-averaged (PA) model

```
predict [type] newvar [if] [in] [ , PA_statistic nooffset ]
```

RE_statistic	Description
Main	
xb	linear prediction; the default
pr	marginal probability of a positive outcome
pu0	probability of a positive outcome
stdp	standard error of the linear prediction

PA_statistic	Description
Main	
mu	predicted probability of <i>depvar</i> ; considers the <code>offset()</code> ; the default
rate	predicted probability of <i>depvar</i>
xb	linear prediction
stdp	standard error of the linear prediction
score	first derivative of the log likelihood with respect to $\mathbf{x}_{it}\beta$

These statistics are available both in and out of sample; type `predict ... if e(sample)` ... if wanted only for the estimation sample.

Options for predict

Main

`xb` calculates the linear prediction, which is $\mathbf{x}_{it}\beta$ if `offset()` was not specified when the model was fit and $\mathbf{x}_{it}\beta + \text{offset}_{it}$ if `offset()` was specified. This is the default for the random-effects model.

`pr` calculates the probability of a positive outcome that is marginal with respect to the random effect, which means that the probability is calculated by integrating the prediction function with respect to the random effect over its entire support.

`pu0` calculates the probability of a positive outcome, assuming that the random effect for that observation's panel is zero ($\nu_i = 0$). This may not be similar to the proportion of observed outcomes in the group.

`stdp` calculates the standard error of the linear prediction.

`mu` and `rate` both calculate the predicted probability of *depvar*. `mu` takes into account the `offset()`. `rate` ignores those adjustments. `mu` and `rate` are equivalent if you did not specify `offset()`. `mu` is the default for the population-averaged model.

`score` calculates the equation-level score, $u_{it} = \partial \ln L(\mathbf{x}_{it}\beta) / \partial (\mathbf{x}_{it}\beta)$.

`nooffset` is relevant only if you specified `offset(varname)` for `xtcloglog`. It modifies the calculations made by `predict` so that they ignore the offset variable; the linear prediction is treated as $\mathbf{x}_{it}\beta$ rather than $\mathbf{x}_{it}\beta + \text{offset}_{it}$.

margins

Description for margins

`margins` estimates margins of responses for probabilities and linear predictions.

Menu for margins

Statistics > Postestimation

Syntax for margins

```
margins [marginlist] [, options]  
margins [marginlist] , predict(statistic ...) [predict(statistic ...) ...] [options]
```

Random-effects (RE) model

<i>statistic</i>	Description
<code>pr</code>	marginal probability of a positive outcome; the default
<code>pu0</code>	probability of a positive outcome
<code>xb</code>	linear prediction
<code>stdp</code>	not allowed with margins

Population-averaged (PA) model

<i>statistic</i>	Description
<code>mu</code>	predicted probability of <i>depvar</i> ; considers the <code>offset()</code> ; the default
<code>rate</code>	predicted probability of <i>depvar</i>
<code>xb</code>	linear prediction
<code>stdp</code>	not allowed with margins
<code>score</code>	not allowed with margins

Statistics not allowed with margins are functions of stochastic quantities other than $e(b)$.

For the full syntax, see [\[R\] margins](#).

Remarks and examples

▷ Example 1: Average marginal effects

In [example 1](#) of [\[XT\] xtcloglog](#), we fit the model

```
. use https://www.stata-press.com/data/r19/union
(NLS Women 14-24 in 1968)

. xtcloglog union age grade not_smsa south##c.year, pa
(output omitted)
```

Here we use margins to determine the average effect each regressor has on the probability of a positive response in the sample.

```
. margins, dydx(*)
Average marginal effects                                Number of obs = 26,200
Model VCE: Conventional
Expression: Pr(union != 0), predict()
dy/dx wrt:  age grade not_smsa 1.south year
```

	Delta-method		z	P> z	[95% conf. interval]	
	dy/dx	std. err.				
age	.0028297	.0014952	1.89	0.058	-.000101	.0057603
grade	.0101144	.0017498	5.78	0.000	.0066848	.013544
not_smsa	-.0192384	.0079304	-2.43	0.015	-.0347818	-.0036951
1.south	-.0913197	.0073101	-12.49	0.000	-.1056473	-.0769921
year	-.0012694	.001534	-0.83	0.408	-.004276	.0017371

Note: dy/dx for factor levels is the discrete change from the base level.

We see that an additional year of schooling (covariate grade) increases the probability that a woman belongs to a union by an average of about one percentage point.

◀

Also see

[\[XT\] xtcloglog](#) — Random-effects and population-averaged cloglog models

[\[U\] 20 Estimation and postestimation commands](#)

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).