

describe — Describe data in memory or in file

[Syntax](#)[Description](#)[Options to describe data in file](#)[Stored results](#)[Also see](#)[Menu](#)[Options to describe data in memory](#)[Remarks and examples](#)[References](#)

Syntax

Describe data in memory

```
describe [varlist] [, memory_options]
```

Describe data in file

```
describe [varlist] using filename [, file_options]
```

<i>memory_options</i>	Description
<u>s</u> imple	display only variable names
<u>s</u> hort	display only general information
<u>f</u> ullnames	do not abbreviate variable names
<u>n</u> umbers	display variable number along with name
<u>r</u> eplace	make dataset, not written report, of description
<u>c</u> lear	for use with <code>replace</code>
<u>v</u> arlist	store <code>r(varlist)</code> and <code>r(sortlist)</code> in addition to usual stored results; programmer's option

`varlist` does not appear in the dialog box.

<i>file_options</i>	Description
<u>s</u> hort	display only general information
<u>s</u> imple	display only variable names
<u>v</u> arlist	store <code>r(varlist)</code> and <code>r(sortlist)</code> in addition to usual stored results; programmer's option

`varlist` does not appear in the dialog box.

Menu

Data > Describe data > Describe data in memory or in a file

Description

`describe` produces a summary of the dataset in memory or of the data stored in a Stata-format dataset.

For a compact listing of variable names, use `describe, simple`.

Options to describe data in memory

`simple` displays only the variable names in a compact format. `simple` may not be combined with other options.

`short` suppresses the specific information for each variable. Only the general information (number of observations, number of variables, size, and sort order) is displayed.

`fullnames` specifies that `describe` display the full names of the variables. The default is to present an abbreviation when the variable name is longer than 15 characters. `describe using` always shows the full names of the variables, so `fullnames` may not be specified with `describe using`.

`numbers` specifies that `describe` present the variable number with the variable name. If `numbers` is specified, variable names are abbreviated when the name is longer than eight characters. The `numbers` and `fullnames` options may not be specified together. `numbers` may not be specified with `describe using`.

`replace` and `clear` are alternatives to the options above. `describe` usually produces a written report, and the options above specify what the report is to contain. If you specify `replace`, however, no report is produced; the data in memory are instead replaced with data containing the information that the report would have presented. Each observation of the new data describes a variable in the original data; see [describe, replace](#) below.

`clear` may be specified only when `replace` is specified. `clear` specifies that the data in memory be cleared and replaced with the description information, even if the original data have not been saved to disk.

The following option is available with `describe` but is not shown in the dialog box:

`varlist`, an option for programmers, specifies that, in addition to the usual stored results, `r(varlist)` and `r(sortlist)` be stored, too. `r(varlist)` will contain the names of the variables in the dataset. `r(sortlist)` will contain the names of the variables by which the data are sorted.

Options to describe data in file

`short` suppresses the specific information for each variable. Only the general information (number of observations, number of variables, size, and sort order) is displayed.

`simple` displays only the variable names in a compact format. `simple` may not be combined with other options.

The following option is available with `describe` but is not shown in the dialog box:

`varlist`, an option for programmers, specifies that, in addition to the usual stored results, `r(varlist)` and `r(sortlist)` be stored, too. `r(varlist)` will contain the names of the variables in the dataset. `r(sortlist)` will contain the names of the variables by which the data are sorted.

Because Stata/MP and Stata/SE can create truly large datasets, there might be too many variables in a dataset for their names to be stored in `r(varlist)`, given the current maximum length of macros, as determined by `set maxvar`. Should that occur, `describe using` will issue the error message “too many variables”, `r(103)`.

Remarks and examples

[stata.com](http://www.stata.com)

Remarks are presented under the following headings:

describe
describe, replace

describe

If `describe` is typed with no operands, the contents of the dataset currently in memory are described.

The *varlist* in the `describe using` syntax differs from standard Stata varlists in two ways. First, you cannot abbreviate variable names; that is, you have to type `displacement` rather than `displ`. However, you can use the abbreviation character (`~`) to indicate abbreviations, for example, `displ~`. Second, you may not refer to a range of variables; specifying `price-trunk` is considered an error.

► Example 1

The basic description includes some general information on the number of variables and observations, along with a description of every variable in the dataset:

```
. use http://www.stata-press.com/data/r13/states
(State data)
. describe, numbers
Contains data from http://www.stata-press.com/data/r13/states.dta
obs:          50          State data
vars:          5          3 Jan 2013 15:17
size:         1,100      (_dta has notes)
```

	variable name	storage type	display format	value label	variable label
1.	state	str8	%9s		
2.	region	int	%8.0g	reg	Census Region
3.	median~e	float	%9.0g		Median Age
4.	marria~e	long	%12.0g		Marriages per 100,000
5.	divorc~e	long	%12.0g		Divorces per 100,000

Sorted by: region

In this example, the dataset in memory comes from the file `states.dta` and contains 50 observations on 5 variables. The dataset is labeled “State data” and was last modified on January 3, 2013, at 15:17 (3:17 p.m.). The “_dta has notes” message indicates that a note is attached to the dataset; see [U] [12.7 Notes attached to data](#).

The first variable, `state`, is stored as a `str8` and has a display format of `%9s`.

The next variable, `region`, is stored as an `int` and has a display format of `%8.0g`. This variable has associated with it a *value label* called `reg`, and the variable is labeled `Census Region`.

The third variable, which is abbreviated `median-e`, is stored as a `float`, has a display format of `%9.0g`, has no value label, and has a variable label of `Median Age`. The variables that are abbreviated `marria-e` and `divorc-e` are both stored as `longs` and have display formats of `%12.0g`. These last two variables are labeled `Marriages per 100,000` and `Divorces per 100,000`, respectively.

The data are sorted by `region`.

Because we specified the `numbers` option, the variables are numbered; for example, `region` is variable 2 in this dataset.

◀

▶ Example 2

To view the full variable names, we could omit the `numbers` option and specify the `fullnames` option.

```
. describe, fullnames
Contains data from http://www.stata-press.com/data/r13/states.dta
  obs:           50             State data
  vars:           5             3 Jan 2013 15:17
  size:          1,100         (_dta has notes)
```

variable name	storage type	display format	value label	variable label
<code>state</code>	<code>str8</code>	<code>%9s</code>		
<code>region</code>	<code>int</code>	<code>%8.0g</code>	<code>reg</code>	<code>Census Region</code>
<code>median_age</code>	<code>float</code>	<code>%9.0g</code>		<code>Median Age</code>
<code>marriage_rate</code>	<code>long</code>	<code>%12.0g</code>		<code>Marriages per 100,000</code>
<code>divorce_rate</code>	<code>long</code>	<code>%12.0g</code>		<code>Divorces per 100,000</code>

Sorted by: `region`

Here we did not need to specify the `fullnames` option to see the unabbreviated variable names because the longest variable name is 13 characters. Omitting the `numbers` option results in 15-character variable names being displayed.

◀

□ Technical note

The `describe` listing above also shows that the size of the dataset is 1,100. If you are curious,

$$(8 + 2 + 4 + 4 + 4) \times 50 = 1100$$

The numbers 8, 2, 4, 4, and 4 are the storage requirements for a `str8`, `int`, `float`, `long`, and `long`, respectively; see [U] [12.2.2 Numeric storage types](#). Fifty is the number of observations in the dataset.

□

▷ Example 3

If we specify the short option, only general information about the data is presented:

```
. describe, short
Contains data from http://www.stata-press.com/data/r13/states.dta
  obs:          50                State data
  vars:          5                3 Jan 2013 15:17
  size:         1,100
Sorted by:  region
```

◀

If we specify a *varlist*, only the variables in that *varlist* are described.

▷ Example 4

Let's change datasets. The `describe varlist` command is particularly useful when combined with the `*` wildcard character. For instance, we can describe all the variables whose names start with `pop` by typing `describe pop*`:

```
. use http://www.stata-press.com/data/r13/census
(1980 Census data by state)
. describe pop*

variable name      storage   display   value   variable label
                  type     format   label
-----
pop                long     %12.0gc   Population
poplt5            long     %12.0gc   Pop, < 5 year
pop5_17           long     %12.0gc   Pop, 5 to 17 years
pop18p            long     %12.0gc   Pop, 18 and older
pop65p            long     %12.0gc   Pop, 65 and older
popurban          long     %12.0gc   Urban population
```

We can describe the variables `state`, `region`, and `pop18p` by specifying them:

```
. describe state region pop18p

variable name      storage   display   value   variable label
                  type     format   label
-----
state              str14    %-14s    State
region             int      %-8.0g   cenreg   Census region
pop18p             long     %12.0gc   Pop, 18 and older
```

◀

Typing `describe` using *filename* describes the data stored in *filename*. If an extension is not specified, `.dta` is assumed.

▷ Example 5

We can describe the contents of `states.dta` without disturbing the data that we currently have in memory by typing

```
. describe using http://www.stata-press.com/data/r13/states
Contains data                               State data
  obs:           50                          3 Jan 2013 15:17
  vars:           5
  size:          1,300
```

variable name	storage type	display format	value label	variable label
state	str8	%9s		
region	int	%8.0g	reg	Census Region
median_age	float	%9.0g		Median Age
marriage_rate	long	%12.0g		Marriages per 100,000
divorce_rate	long	%12.0g		Divorces per 100,000

Sorted by: region



describe, replace

`describe` with the `replace` option is rarely used, although you may sometimes find it convenient.

Think of `describe, replace` as separate from but related to `describe` without the `replace` option. Rather than producing a written report, `describe, replace` produces a new dataset that contains the same information a written report would. For instance, try the following:

```
. sysuse auto, clear
. describe
(report appears; data in memory unchanged)
. list
(visual proof that data are unchanged)
. describe, replace
(no report appears, but the data in memory are changed!)
. list
(visual proof that data are changed)
```

`describe, replace` changes the original data in memory into a dataset containing an observation for each variable in the original data. Each observation in the new data describes a variable in the original data. The new variables are

1. `position`, a variable containing the numeric position of the original variable (1, 2, 3, ...).
2. `name`, a variable containing the name of the original variable, such as "make", "price", "mpg",
3. `type`, a variable containing the storage type of the original variable, such as "str18", "int", "float",
4. `isnumeric`, a variable equal to 1 if the original variable was numeric and equal to 0 if it was string.
5. `format`, a variable containing the display format of the original variable, such as "%-18s", "%8.0gc",

6. `vallab`, a variable containing the name of the value label associated with the original variable, if any.
7. `varlab`, a variable containing the variable label of the original variable, such as "Make and Model", "Price", "Mileage (mpg)",

In addition, the data contain the following characteristics:

- `_dta[_d_filename]`, the name of the file containing the original data.
- `_dta[_d_filedate]`, the date and time the file was written.
- `_dta[_d_N]`, the number of observations in the original data.
- `_dta[_d_sortedby]`, the variables on which the original data were sorted, if any.

Stored results

`describe` stores the following in `r()`:

Scalars

<code>r(N)</code>	number of observations
<code>r(k)</code>	number of variables
<code>r(width)</code>	width of dataset
<code>r(changed)</code>	flag indicating data have changed since last saved

Macros

<code>r(varlist)</code>	variables in dataset (if <code>varlist</code> specified)
<code>r(sortlist)</code>	variables by which data are sorted (if <code>varlist</code> specified)

`describe`, `replace` stores nothing in `r()`.

References

- Cox, N. J. 1999. [dm67: Numbers of missing and present values](#). *Stata Technical Bulletin* 49: 7–8. Reprinted in *Stata Technical Bulletin Reprints*, vol. 9, pp. 26–27. College Station, TX: Stata Press.
- . 2001. [dm67.1: Enhancements to numbers of missing and present values](#). *Stata Technical Bulletin* 60: 2–3. Reprinted in *Stata Technical Bulletin Reprints*, vol. 10, pp. 7–9. College Station, TX: Stata Press.
- . 2003. [Software Updates: Numbers of present and missing values](#). *Stata Journal* 3: 449.
- . 2005. [Software Updates: Numbers of present and missing values](#). *Stata Journal* 5: 607.
- Gleason, J. R. 1998. [dm61: A tool for exploring Stata datasets \(Windows and Macintosh only\)](#). *Stata Technical Bulletin* 45: 2–5. Reprinted in *Stata Technical Bulletin Reprints*, vol. 8, pp. 22–27. College Station, TX: Stata Press.
- . 1999. [dm61.1: Update to varxplor](#). *Stata Technical Bulletin* 51: 2. Reprinted in *Stata Technical Bulletin Reprints*, vol. 9, p. 15. College Station, TX: Stata Press.

Also see

- [D] **ds** — List variables matching name patterns or other characteristics
- [D] **varmanage** — Manage variable labels, formats, and other properties
- [D] **cf** — Compare two datasets
- [D] **codebook** — Describe data contents
- [D] **compare** — Compare two variables
- [D] **compress** — Compress data in memory
- [D] **format** — Set variables' output format
- [D] **label** — Manipulate labels
- [D] **lookfor** — Search for string in variable names and labels
- [D] **notes** — Place notes in data
- [D] **order** — Reorder variables in dataset
- [D] **rename** — Rename variable
- [SVY] **svydescribe** — Describe survey data
- [U] **6 Managing memory**