

*fitarea\_options* — Options for specifying the look of confidence interval areas

Syntax    Description    Options    Remarks and examples

## Syntax

<i>fitarea_options</i>	Description
<u>a</u> color( <i>colorstyle</i> )	outline and fill color
<u>f</u> color( <i>colorstyle</i> )	fill color
<u>f</u> intensity( <i>intensitystyle</i> )	fill intensity
<u>a</u> lcolor( <i>colorstyle</i> )	outline color
<u>a</u> lwidth( <i>linewidthstyle</i> )	thickness of outline
<u>a</u> lpattern( <i>linepatternstyle</i> )	outline pattern (solid, dashed, etc.)
<u>a</u> lstyle( <i>linestyle</i> )	overall look of outline
<u>a</u> style( <i>areastyle</i> )	overall look of area, all settings above
<u>p</u> style( <i>pstyle</i> )	overall plot style, including areastyle

See [G-4] [colorstyle](#), [G-4] [intensitystyle](#), [G-4] [linewidthstyle](#), [G-4] [linepatternstyle](#), [G-4] [linestyle](#), [G-4] [areastyle](#), [G-4] [pstyle](#), and [G-3] [advanced\\_options](#).

All options are *merged-implicit*; see [G-4] [concept: repeated options](#).

## Description

The *fitarea\_options* determine the look of, for instance, the confidence interval areas created by `twoway fppfitci`, `twoway lfifitci`, `twoway lppolyci`, and `twoway qffitci`; see [G-2] [graph twoway fppfitci](#), [G-2] [graph twoway lfifitci](#), [G-2] [graph twoway lppolyci](#), and [G-2] [graph twoway lfifitci](#).

## Options

`a`color(*colorstyle*) specifies one color to be used both to outline the shape of the area and to fill its interior. See [G-4] [colorstyle](#) for a list of color choices.

`f`color(*colorstyle*) specifies the color to be used to fill the interior of the area. See [G-4] [colorstyle](#) for a list of color choices.

`f`intensity(*intensitystyle*) specifies the intensity of the color used to fill the interior of the area. See [G-4] [intensitystyle](#) for a list of intensity choices.

`a`lcolor(*colorstyle*) specifies the color to be used to outline the area. See [G-4] [colorstyle](#) for a list of color choices.

`a`lwidth(*linewidthstyle*) specifies the thickness of the line to be used to outline the area. See [G-4] [linewidthstyle](#) for a list of choices.

`a`lpattern(*linepatternstyle*) specifies whether the line used to outline the area is solid, dashed, etc. See [G-4] [linepatternstyle](#) for a list of pattern choices.

`alstyle(linestyle)` specifies the overall style of the line used to outline the area, including its pattern (solid, dashed, etc.), thickness, and color. The three options listed above allow you to change the line's attributes, but `lstyle()` is the starting point. See [G-4] [linestyle](#) for a list of choices.

`astyle(areastyle)` specifies the overall look of the area. The options listed above allow you to change each attribute, but `style()` provides a starting point.

You need not specify `style()` just because there is something you want to change. You specify `style()` when another style exists that is exactly what you desire or when another style would allow you to specify fewer changes to obtain what you want.

See [G-4] [areastyle](#) for a list of available area styles.

`pstyle(pstyle)` specifies the overall style of the plot, including not only the [areastyle](#), but all other settings for the look of the plot. Only the [areastyle](#) affects the look of areas. See [G-4] [pstyle](#) for a list of available plot styles.

## Remarks and examples

[stata.com](http://stata.com)

*fitarea\_options* are allowed as options with any `graph twoway` plotype that creates shaded confidence interval areas, for example, `graph twoway lfitci`, as in

```
. graph twoway lfitci yvar xvar, acolor(blue)
```

The above would set the area enclosed by *yvar* and the *x* axis to be blue; see [G-2] [graph twoway area](#) and [G-2] [graph twoway rarea](#).