

**st\_varindex()** — Obtain variable indices from variable names

Syntax Diagnostics	Description Also see	Remarks and examples	Conformability
-----------------------	-------------------------	----------------------	----------------

## Syntax

```

real rowvector    st_varindex(string rowvector s)

real rowvector    st_varindex(string rowvector s, real scalar abbrev)

real rowvector    _st_varindex(string rowvector s)

real rowvector    _st_varindex(string rowvector s, real scalar abbrev)

```

## Description

`st_varindex(s)` returns the variable index associated with each variable name recorded in *s*. `st_varindex(s)` does not allow variable-name abbreviations such as "pr" for "price".

`st_varindex(s, abbrev)` does the same thing but allows you to specify whether variable-name abbreviations are to be allowed. Abbreviations are allowed if *abbrev* ≠ 0. `st_varindex(s)` is equivalent to `st_varindex(s, 0)`.

`_st_varindex()` does the same thing as `st_varindex()`. The two functions differ in how they respond when a name is not found. `st_varindex()` aborts with error, and `_st_varindex()` places missing in the appropriate element of the returned result.

## Remarks and examples

stata.com

These functions require that each element of *s* contain a variable name, such as

```
s = ("price", "mpg", "weight")
```

If you have one string containing multiple names

```
s = ("price mpg weight")
```

then use `tokens()` to split it into the desired form, as in

```
k = st_varindex(tokens(s))
```

See [M-5] [tokens\(\)](#).

## Conformability

`st_varindex(s, abbrev)`, `_st_varindex(s, abbrev)`:

<i>s</i> :	$1 \times k$	
<i>abbrev</i> :	$1 \times 1$	(optional)
<i>result</i> :	$1 \times k$	

## Diagnostics

`st_varindex()` aborts with error if any name is not found.

`_st_varindex()` puts missing in the appropriate element of the returned result for any name that is not found.

## Also see

[M-5] [st\\_varname\(\)](#) — Obtain variable names from variable indices

[M-5] [tokens\(\)](#) — Obtain tokens from string

[M-4] [stata](#) — Stata interface functions