

estimates describe — Describe estimation results

Syntax Remarks and examples	Menu Stored results	Description Also see	Option
--	--	---	------------------------

Syntax

```

estimates describe
estimates describe name
estimates describe using filename [ , number(#) ]

```

Menu

Statistics > Postestimation > Manage estimation results > Describe results

Description

`estimates describe` describes the current (active) estimates. Reported are the command line that produced the estimates, any title that was set by `estimates title` (see [R] [estimates title](#)), and any notes that were added by `estimates notes` (see [R] [estimates notes](#)).

`estimates describe name` does the same but reports results for estimates stored by `estimates store` (see [R] [estimates store](#)).

`estimates describe using filename` does the same but reports results for estimates saved by `estimates save` (see [R] [estimates save](#)). If *filename* contains multiple sets of estimates (saved in it by `estimates save, append`), the number of sets of estimates is also reported. If *filename* is specified without an extension, `.ster` is assumed.

Option

`number(#)` specifies that the *#*th set of estimation results from *filename* be described. This assumes that multiple sets of estimation results have been saved in *filename* by `estimates save, append`. The default is `number(1)`.

Remarks and examples

[stata.com](#)

`estimates describe` can be used to describe the estimation results currently in memory,

```

. estimates describe
Estimation results produced by
. regress mpg weight displ if foreign

```

or to describe results saved by `estimates save` in a `.ster` file:

```
. estimates describe using final
Estimation results "Final results" saved on 12apr2013 14:20, produced by
. logistic myopic age sex drug1 drug2 if complete==1
Notes:
1. Used file patient.dta
2. "datasignature myopic age sex drug1 drug2 if complete==1"
   reports 148:5(58763):2252897466:3722318443
3. must be reviewed by rgg
```

► Example 1

```
. use http://www.stata-press.com/data/r13/auto
(1978 Automobile Data)
. regress mpg weight displ if foreign
(output omitted)
. estimates notes: file 'c(filename)'
. datasignature
74:12(71728):3831085005:1395876116
. estimates notes: datasignature report 'r(datasignature)'
. estimates save foreign
file foreign.ster saved
. regress mpg weight displ if !foreign
(output omitted)
. estimates describe using foreign
Estimation results saved on 02may2013 10:33, produced by
. regress mpg weight displ if foreign
Notes:
1. file http://www.stata-press.com/data/r13/auto.dta
2. datasignature report 74:12(71728):3831085005:1395876116
```

◀

Stored results

`estimates describe` and `estimates describe name` store the following in `r()`:

Macros

<code>r(title)</code>	title
<code>r(cmdline)</code>	original command line

`estimates describe using filename` stores the above and the following in `r()`:

Scalars

<code>r(datetime)</code>	%tc value of date/time file saved
<code>r(nestresults)</code>	number of sets of estimation results in file

Also see

[R] [estimates](#) — Save and manipulate estimation results