

stata — Stata interface functions

[Contents](#)
[Also see](#)

[Description](#)

[Remarks and examples](#)

[Reference](#)

Contents

[M-5] Manual entry	Function	Purpose
<div style="border: 1px solid black; padding: 2px; display: inline-block; margin-bottom: 10px;">Access to data</div>		
st_nvar()	st_nvar() st_nobs()	number of variables number of observations
st_data()	st_data() st_sdata()	load numeric data from Stata into matrix load string data from Stata into matrix
st_store()	st_store() st_sstore()	store numeric data in Stata dataset store string data in Stata dataset
st_view()	st_view() st_sview()	make view onto Stata dataset same; string variables
st_subview()	st_subview()	make view from view
st_viewvars()	st_viewvars() st_viewobs()	identify variables and observations corresponding to view
<div style="border: 1px solid black; padding: 2px; display: inline-block; margin-bottom: 10px;">Variable names & indices</div>		
st_varindex()	st_varindex()	variable indices from variable names
st_varname()	st_varname()	variable names from variable indices

Variable characteristics

st_varrename()	st_varrename()	rename Stata variable
st_vartype()	st_vartype()	storage type of Stata variable
	st_isnumvar()	whether variable is numeric
	st_isstrvar()	whether variable is string
st_varformat()	st_varformat()	obtain/set format of Stata variable
	st_varlabel()	obtain/set variable label
	st_varvalue label()	obtain/set value label
st_vlexists()	st_vlexists()	whether value label exists
	st_vldrop()	drop value
	st_vlmap()	map values
	st_vlsearch()	map text
	st_vlload()	load value label
	st_vlmodify()	create or modify value label

Temporary variables & time-series operators

st_tempname()	st_tempname()	temporary variable name
	st_tempfilename()	temporary filename
st_tsrevar()	st_tsrevar()	create time-series op.varname
	_st_tsrevar()	same

Adding & removing variables & observations
--

st_addobs()	st_addobs()	add observations to Stata dataset
st_addvar()	st_addvar()	add variable to Stata dataset
st_dropvar()	st_dropvar()	drop variables
	st_dropobsin()	drop specified observations
	st_dropobsif()	drop selected observations
	st_keepvar()	keep variables
	st_keepobsin()	keep specified observations
	st_keepobsif()	keep selected observations
st_updata()	st_updata()	query/set data-have-changed flag

Executing Stata commands

stata()	stata()	execute Stata command
st_macroexpand()	st_macroexpand()	expand Stata macros

Accessing e(), r(), s(), macros, matrices, etc.

st_global()	<code>st_global()</code> <code>st_global_hcat()</code>	obtain/set Stata global obtain hidden/historical status
st_local()	<code>st_local()</code>	obtain/set local Stata macro
st_numscalar()	<code>st_numscalar()</code> <code>st_numscalar_hcat()</code> <code>st_strscalar()</code>	obtain/set Stata numeric scalar obtain hidden/historical status obtain/set Stata string scalar
st_matrix()	<code>st_matrix()</code> <code>st_matrix_hcat()</code> <code>st_matrixrowstripe()</code> <code>st_matrixcolstripe()</code> <code>st_replacematrix()</code>	obtain/set Stata matrix obtain hidden/historical status obtain/set row labels obtain/set column labels replace existing Stata matrix
st_dir()	<code>st_dir()</code>	obtain list of Stata objects
st_rclear()	<code>st_rclear()</code> <code>st_eclear()</code> <code>st_sclear()</code>	clear r() clear e() clear s()

Parsing & verification

st_isname()	<code>st_isname()</code> <code>st_islname()</code>	whether valid Stata name whether valid local macro name
st_isfmt()	<code>st_isfmt()</code> <code>st_isnumfmt()</code> <code>st_isstrfmt()</code>	whether valid <i>%fmt</i> whether valid numeric <i>%fmt</i> whether valid string <i>%fmt</i>
abbrev()	<code>abbrev()</code>	abbreviate strings
strtoname()	<code>strtoname()</code>	translate strings to Stata names

Description

The above functions interface with Stata.

Remarks and examples

[stata.com](http://www.stata.com)

The following manual entries have to do with getting data from or putting data into Stata:

[M-5] st_data()	Load copy of current Stata dataset
[M-5] st_view()	Make matrix that is a view onto current Stata dataset
[M-5] st_store()	Modify values stored in current Stata dataset
[M-5] st_nvar()	Numbers of variables and observations

In some cases, you may find yourself needing to translate variable names into variable indices and vice versa:

[M-5] <code>st_varname()</code>	Obtain variable names from variable indices
[M-5] <code>st_varindex()</code>	Obtain variable indices from variable names
[M-5] <code>st_tsrevar()</code>	Create time-series <code>op.varname</code> variables

The other functions mostly have to do with getting and putting Stata's scalars, matrices, and returned results:

[M-5] <code>st_local()</code>	Obtain strings from and put strings into Stata
[M-5] <code>st_global()</code>	Obtain strings from and put strings into global macros
[M-5] <code>st_numscalar()</code>	Obtain values from and put values into Stata scalars
[M-5] <code>st_matrix()</code>	Obtain and put Stata matrices

The `stata()` function, documented in

[M-5] <code>stata()</code>	Execute Stata command
----------------------------	-----------------------

allows you to cause Stata to execute a command that you construct in a string.

Reference

Gould, W. W. 2008. *Mata Matters: Macros*. *Stata Journal* 8: 401–412.

Also see

[M-4] [intro](#) — Index and guide to functions