

menbreg postestimation — Postestimation tools for menbreg

Postestimation commands
 estat
 Also see

predict
 Remarks and examples

margins
 Methods and formulas

Postestimation commands

The following postestimation command is of special interest after `menbreg`:

Command	Description
<code>estat group</code>	summarize the composition of the nested groups

The following standard postestimation commands are also available:

Command	Description
<code>contrast</code>	contrasts and ANOVA-style joint tests of estimates
<code>estat ic</code>	Akaike's and Schwarz's Bayesian information criteria (AIC and BIC)
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance–covariance matrix of the estimators (VCE)
<code>estat (svy)</code>	postestimation statistics for survey data
<code>estimates</code>	cataloging estimation results
* <code>hausman</code>	Hausman's specification test
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of coefficients
* <code>lrtest</code>	likelihood-ratio test
<code>margins</code>	marginal means, predictive margins, marginal effects, and average marginal effects
<code>marginsplot</code>	graph the results from margins (profile plots, interaction plots, etc.)
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of coefficients
<code>predict</code>	predictions, residuals, influence statistics, and other diagnostic measures
<code>predictnl</code>	point estimates, standard errors, testing, and inference for generalized predictions
<code>pwcompare</code>	pairwise comparisons of estimates
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

* `hausman` and `lrtest` are not appropriate with `svy` estimation results.

predict

Description for predict

`predict` creates a new variable containing predictions such as mean responses; linear predictions; density and distribution functions; standard errors; and Pearson, deviance, and Anscombe residuals.

Menu for predict

Statistics > Postestimation

Syntax for predict

Syntax for obtaining predictions of the outcome and other statistics

```
predict [type] newvarsspec [if] [in] [, statistic options]
```

Syntax for obtaining estimated random effects and their standard errors

```
predict [type] newvarsspec [if] [in], reffects [re_options]
```

Syntax for obtaining ML scores

```
predict [type] newvarsspec [if] [in], scores
```

newvarsspec is *stub** or *newvarlist*.

<i>statistic</i>	Description
------------------	-------------

Main

<code>mu</code>	mean response; the default
<code>eta</code>	fitted linear predictor
<code>xb</code>	linear predictor for the fixed portion of the model only
<code>stdp</code>	standard error of the fixed-portion linear prediction
<code>density</code>	predicted density function
<code>distribution</code>	predicted distribution function
<code>pearson</code>	Pearson residuals
<code>deviance</code>	deviance residuals
<code>anscombe</code>	Anscombe residuals

These statistics are available both in and out of sample; type `predict ... if e(sample) ...` if wanted only for the estimation sample.

<i>options</i>	Description
Main	
<code>conditional(<i>ctype</i>)</code>	compute <i>statistic</i> conditional on estimated random effects; default is <code>conditional(ebmeans)</code>
<code>marginal</code>	compute <i>statistic</i> marginally with respect to the random effects
<code>nooffset</code>	make calculation ignoring offset or exposure
Integration	
<code>int_options</code>	integration options
pearson, deviance, anscombe may not be combined with marginal.	
<i>ctype</i>	Description
<code>ebmeans</code>	empirical Bayes means of random effects; the default
<code>ebmodes</code>	empirical Bayes modes of random effects
<code>fixedonly</code>	prediction for the fixed portion of the model only
<i>re_options</i>	Description
Main	
<code>ebmeans</code>	use empirical Bayes means of random effects; the default
<code>ebmodes</code>	use empirical Bayes modes of random effects
<code>reses(<i>stub*</i> <i>newvarlist</i>)</code>	calculate standard errors of empirical Bayes estimates
Integration	
<code>int_options</code>	integration options
<i>int_options</i>	Description
<code>intpoints(#)</code>	use # quadrature points to compute marginal predictions and empirical Bayes means
<code>iterate(#)</code>	set maximum number of iterations in computing statistics involving empirical Bayes estimators
<code>tolerance(#)</code>	set convergence tolerance for computing statistics involving empirical Bayes estimators

Options for predict

Main

`mu`, the default, calculates the predicted mean, that is, the predicted number of events.

`eta`, `xb`, `stdp`, `density`, `distribution`, `pearson`, `deviance`, `anscombe`, `scores`, `conditional()`, `marginal`, and `nooffset`; see [ME] [meglm postestimation](#).

`reffects`, `ebmeans`, `ebmodes`, and `reses()`; see [ME] [meglm postestimation](#).

Integration

`intpoints()`, `iterate()`, and `tolerance()`; see [ME] [meglm postestimation](#).

margins

Description for margins

`margins` estimates margins of response for mean responses and linear predictions.

Menu for margins

Statistics > Postestimation

Syntax for margins

```
margins [marginlist] [, options]
```

```
margins [marginlist] , predict(statistic ...) [predict(statistic ...) ...] [options]
```

<i>statistic</i>	Description
<code>mu</code>	mean response; the default
<code>eta</code>	fitted linear predictor
<code>xb</code>	linear predictor for the fixed portion of the model only
<code>stdp</code>	not allowed with <code>margins</code>
<code>density</code>	not allowed with <code>margins</code>
<code>distribution</code>	not allowed with <code>margins</code>
<code>pearson</code>	not allowed with <code>margins</code>
<code>deviance</code>	not allowed with <code>margins</code>
<code>anscombe</code>	not allowed with <code>margins</code>
<code>reffects</code>	not allowed with <code>margins</code>
<code>scores</code>	not allowed with <code>margins</code>

Options `conditional(ebmeans)` and `conditional(ebmodes)` are not allowed with `margins`.

Option `marginal` is assumed where applicable if `conditional(fixedonly)` is not specified.

Statistics not allowed with `margins` are functions of stochastic quantities other than $e(b)$.

For the full syntax, see [R] [margins](#).

estat

Description for estat

`estat group` reports the number of groups and minimum, average, and maximum group sizes for each level of the model. Model levels are identified by the corresponding group variable in the data. Because groups are treated as nested, the information in this summary may differ from what you would get if you used the `tabulate` command on each group variable individually.

Menu for estat

Statistics > Postestimation

Syntax for estat

```
estat group
```

Remarks and examples

[stata.com](https://www.stata.com)

Various predictions, statistics, and diagnostic measures are available after fitting a mixed-effects negative binomial model with `menbreg`. For the most part, calculation centers around obtaining estimates of the subject/group-specific random effects. Random effects are not estimated when the model is fit but instead need to be predicted after estimation.

Here we show a short example of predicted counts and predicted random effects; refer to [ME] [meglm postestimation](#) for additional examples applicable to mixed-effects generalized linear models.

▷ Example 1

In [example 2](#) of [ME] `menbreg`, we modeled the number of deaths among males in nine European nations as a function of exposure to ultraviolet radiation (`uv`). We used a three-level negative binomial model with random effects at the nation and region levels.

```
. use http://www.stata-press.com/data/r14/melanoma
(Skin cancer (melanoma) data)
. menbreg deaths uv, exposure(expected) || nation: || region:
(output omitted)
```

We can use `predict` to obtain the predicted counts as well as the estimates of the random effects at the nation and region levels.

```
. predict mu
(predictions based on fixed effects and posterior means of random effects)
(option mu assumed)
(using 7 quadrature points)
. predict re_nat re_reg, reffects
(calculating posterior means of random effects)
(using 7 quadrature points)
```

Stata displays a note that the predicted values of `mu` are based on the posterior means of random effects. You can use option `modes` to obtain predictions based on the posterior modes of random effects.

Here we list the data for the first nation in the dataset, which happens to be Belgium:

```
. list nation region deaths mu re_nat re_reg if nation==1, sepby(region)
```

	nation	region	deaths	mu	re_nat	re_reg
1.	Belgium	1	79	64.4892	-.0819939	.2937711
2.	Belgium	2	80	77.64736	-.0819939	.024005
3.	Belgium	2	51	44.56528	-.0819939	.024005
4.	Belgium	2	43	53.10434	-.0819939	.024005
5.	Belgium	2	89	65.35963	-.0819939	.024005
6.	Belgium	2	19	35.18457	-.0819939	.024005
7.	Belgium	3	19	8.770186	-.0819939	-.3434432
8.	Belgium	3	15	43.95521	-.0819939	-.3434432
9.	Belgium	3	33	34.17878	-.0819939	-.3434432
10.	Belgium	3	9	7.332448	-.0819939	-.3434432
11.	Belgium	3	12	12.93873	-.0819939	-.3434432

We can see that the predicted random effects at the nation level, `re_nat`, are the same for all the observations. Similarly, the predicted random effects at the region level, `re_reg`, are the same within each region. The predicted counts, `mu`, are not as close to the observed deaths as the predicted counts from the mixed-effects Poisson model in [example 1](#) of [\[ME\] mepoisson postestimation](#).

◀

Methods and formulas

Methods and formulas for predicting random effects and other statistics are given in [Methods and formulas](#) of [\[ME\] meglm postestimation](#).

Also see

[\[ME\] menbreg](#) — Multilevel mixed-effects negative binomial regression

[\[ME\] meglm postestimation](#) — Postestimation tools for meglm

[\[U\] 20 Estimation and postestimation commands](#)