

**postfile** — Post results in Stata dataset

[Description](#)

[Syntax](#)

[Options](#)

[Remarks and examples](#)

[References](#)

[Also see](#)

## Description

These commands are utilities to assist Stata programmers in performing Monte Carlo–type experiments.

`postfile` declares the variable names and the filename of a (new) Stata dataset where results will be saved.

`post` adds a new observation to the declared dataset.

`postclose` declares an end to the posting of observations. After `postclose`, the new dataset contains the posted results and may be loaded using `use`; see [\[D\] use](#).

`postutil dir` lists all open postfiles. `postutil clear` closes all open postfiles.

All five commands manipulate the new dataset without disturbing the data in memory.

If *filename* is specified without an extension, `.dta` is assumed.

## Syntax

*Declare variable names and filename of dataset where results will be saved*

```
postfile postname newvarlist using filename [ , every(#) replace ]
```

*Add new observation to declared dataset*

```
post postname (exp) (exp) ... (exp)
```

*Declare end to posting of observations*

```
postclose postname
```

*List all open postfiles*

```
postutil dir
```

*Close all open postfiles*

```
postutil clear
```

## Options

`every(#)` specifies that results be written to disk every `#`th call to `post`. `post` temporarily holds results in memory and periodically opens the Stata dataset being built to append the saved results. `every()` should typically not be specified, because you are unlikely to choose a value for `#` that is as efficient as the number `post` chooses on its own, which is a function of the number of results being written and their storage type.

`replace` indicates that the file specified may already exist, and if it does, that `postfile` may erase the file and create a new one.

## Remarks and examples

[stata.com](http://stata.com)

The typical use of the `post` commands is

```
tempname memhold
tempfile results
...
postfile `memhold' ... using "results"
...
while ... {
    ...
    post `memhold' ...
    ...
}
postclose `memhold'
...
use "results", clear
...
```

Two names are specified with `postfile`: *postname* is a name assigned to internal memory buffers, and *filename* is the name of the file to be created. Subsequent `posts` and the `postclose` are followed by *postname* so that Stata will know to what file they refer.

In our sample, we obtain both names from Stata's temporary name facility (see [P] [macro](#)), although, in some programming situations, you may wish to substitute a hard-coded *filename*. We recommend that *postname* always be obtained from `tempname`. This ensures that your program can be nested within any other program and ensures that the memory used by `post` is freed if anything goes wrong. Using a temporary filename, too, ensures that the file will be erased if the user presses *Break*. Sometimes, however, you may wish to leave the file of incomplete results behind. That is allowed, but remember that the file is not fully up to date if `postclose` has not been executed. `post` buffers results in memory and only periodically updates the file.

Because `postfile` accepts a *newvarlist*, storage types may be interspersed, so you could have

```
postfile `memhold' a b str20 c double(d e f) using "results"
```

### ► Example 1

We wish to write a program to collect means and variances from 10,000 randomly constructed 100-observation samples of lognormal data and save the results in `results.dta`. Suppose that we are evaluating the coverage of the 95%, *t*-based confidence interval when applied to lognormal data. As background, we can obtain a 100-observation lognormal sample by typing

```
drop _all
set obs 100
generate z = exp(rnormal())
```

We can obtain the mean and standard deviation by typing

```
summarize z
```

Moreover, `summarize` stores the sample mean in `r(mean)` and variance in `r(Var)`. It is those two values we wish to collect. Our program is

```
program lnsim
  version 14.1
  tempname sim
  postfile 'sim' mean var using results, replace
  quietly {
    forvalues i = 1/10000 {
      drop _all
      set obs 100
      generate z = exp(rnormal())
      summarize z
      post 'sim' (r(mean)) (r(Var))
    }
  }
  postclose 'sim'
end
```

The `postfile` command begins the accumulation of results. `'sim'` is the name assigned to the internal memory buffers where results will be held; `mean` and `var` are the names to be given to the two variables that will contain the information we collect; and variables will be saved in the file named `results.dta`. Because two variable names were specified on the `postfile` line, two expressions must be specified following `post`. Here the expressions are simply `r(mean)` and `r(Var)`. If we had wanted, however, to store the mean divided by the standard deviation and the standard deviation, we could have typed

```
post 'sim' (r(mean)/r(sd)) (r(sd))
```

Finally, `postclose 'sim'` concluded the simulation. The dataset `results.dta` is now complete.

```
. set seed 12345
. lnsim
. use results, clear
. describe
Contains data from results.dta
  obs:      10,000
  vars:      2                               12 Nov 2014 10:23
  size:      80,000
```

variable name	storage type	display format	value label	variable label
mean	float	%9.0g		
var	float	%9.0g		

Sorted by:

```
. summarize
```

Variable	Obs	Mean	Std. Dev.	Min	Max
mean	10,000	1.649184	.217526	.9933856	3.087867
var	10,000	4.624283	4.144868	.6665277	97.41853

We set the random-number seed to an arbitrary value, 12345, so that this example would be reproducible.

## References

Gould, W. W. 1994. [ssi6: Routines to speed Monte Carlo experiments](#). *Stata Technical Bulletin* 20: 18–22. Reprinted in *Stata Technical Bulletin Reprints*, vol. 4, pp. 202–207. College Station, TX: Stata Press.

Van Kerm, P. 2007. [Stata tip 54: Post your results](#). *Stata Journal* 7: 587–589.

## Also see

[P] [putexcel](#) — Export results to an Excel file

[R] [bootstrap](#) — Bootstrap sampling and estimation

[R] [simulate](#) — Monte Carlo simulations