

irf rename — Rename an IRF result in an IRF file

Description
Option

Quick start
Remarks and examples

Menu
Stored results

Syntax
Also see

Description

`irf rename` changes the name of a set of IRF results saved in the active IRF file.

Quick start

Rename impulse–response function `oldirf` in the current file to `newirf`

```
irf rename oldirf newirf
```

As above, but for IRF file `myirfs.irf`

```
irf rename oldirf newirf, set(myirfs)
```

Note: `irf` commands can be used after `var`, `svar`, `vec`, `arma`, or `arfima`; see [\[TS\] var](#), [\[TS\] var svar](#), [\[TS\] vec](#), [\[TS\] arma](#), or [\[TS\] arfima](#).

Menu

Statistics > Multivariate time series > Manage IRF results and files > Rename IRF results

Syntax

```
irf rename oldname newname [, set(filename) ]
```

Option

`set(filename)` specifies the file to be made active; see [\[TS\] irf set](#). If `set()` is not specified, the active file is used.

Remarks and examples

[stata.com](#)

If you have not read [\[TS\] irf](#), please do so.

▷ Example 1

```
. use http://www.stata-press.com/data/r14/lutkepohl2
(Quarterly SA West German macro data, Bil DM, from Lutkepohl 1993 Table E.1)
. var dln_inv dln_inc dln_consump if qtr<=tq(1978q4), lags(1/2) dfk
(output omitted)
```

We create three sets of IRF results:

```
. irf create original, set(myirfs, replace)
(file myirfs.irf created)
(file myirfs.irf now active)
(file myirfs.irf updated)
. irf create order2, order(dln_inc dln_inv dln_consump)
(file myirfs.irf updated)
. irf create order3, order(dln_inc dln_consump dln_inv)
(file myirfs.irf updated)
. irf describe
Contains irf results from myirfs.irf (dated 11 Nov 2014 09:22)
```

irfname	model	endogenous variables and order (*)
original	var	dln_inv dln_inc dln_consump
order2	var	dln_inc dln_inv dln_consump
order3	var	dln_inc dln_consump dln_inv

(*) order is relevant only when model is var

Now let's rename IRF result original to order1.

```
. irf rename original order1
(81 real changes made)
original renamed to order1
. irf describe
Contains irf results from myirfs.irf (dated 11 Nov 2014 09:22)
```

irfname	model	endogenous variables and order (*)
order1	var	dln_inv dln_inc dln_consump
order2	var	dln_inc dln_inv dln_consump
order3	var	dln_inc dln_consump dln_inv

(*) order is relevant only when model is var

original has been renamed to order1.



Stored results

`irf rename` stores the following in `r()`:

```
Macros
  r(irfnames)    irfnames after rename
  r(oldnew)      oldname newname
```

Also see

- [TS] **irf** — Create and analyze IRFs, dynamic-multiplier functions, and FEVDs
- [TS] **var intro** — Introduction to vector autoregressive models
- [TS] **vec intro** — Introduction to vector error-correction models