

minmax() — Minimums and maximums[Description](#)[Syntax](#)[Conformability](#)[Diagnostics](#)[Also see](#)

Description

These functions return the indicated minimums and maximums of X .

`rowmin(X)` returns the minimum of each row of X , `colmin(X)` returns the minimum of each column, and `min(X)` returns the overall minimum. Elements of X that contain missing values are ignored.

`rowmax(X)` returns the maximum of each row of X , `colmax(X)` returns the maximum of each column, and `max(X)` returns the overall maximum. Elements of X that contain missing values are ignored.

`rowminmax(X)` returns the minimum and maximum of each row of X in an $r \times 2$ matrix; `colminmax(X)` returns the minimum and maximum of each column in a $2 \times c$ matrix; and `minmax(X)` returns the overall minimum and maximum. Elements of X that contain missing values are ignored.

The two-argument versions of `rowminmax()`, `colminmax()`, and `minmax()` allow you to specify how missing values are to be treated. Specifying a second argument with value 0 is the same as using the single-argument versions of the functions. In the two-argument versions, if the second argument is not zero, missing values are treated like all other values in determining the minimums and maximums: *nonmissing* < . < .a < .b < ... < .z.

`rowmaxabs(A)` and `colmaxabs(A)` return the same result as `rowmax(abs(A))` and `colmax(abs(A))`. The advantage is that matrix `abs(A)` is never formed or stored, and so these functions use less memory.

Syntax

real colvector `rowmin(real matrix X)`

real rowvector `colmin(real matrix X)`

real scalar `min(real matrix X)`

real colvector `rowmax(real matrix X)`

real rowvector `colmax(real matrix X)`

real scalar `max(real matrix X)`

real matrix `rowminmax(real matrix X)`

real matrix `colminmax(real matrix X)`

real rowvector `minmax(real matrix X)`

real matrix `rowminmax(real matrix X, real scalar usemiss)`

real matrix `colminmax(real matrix X, real scalar usemiss)`

real rowvector `minmax(real matrix X, real scalar usemiss)`

real colvector `rowmaxabs(numeric matrix A)`

real rowvector `colmaxabs(numeric matrix A)`

Conformability

`rowmin(X)`, `rowmax(X)`:

X: $r \times c$
result: $r \times 1$

`colmin(X)`, `colmax(X)`:

X: $r \times c$
result: $1 \times c$

`min(X)`, `max(X)`:

X: $r \times c$
result: 1×1

`rowminmax(X, usemiss)`:

X: $r \times c$
usemiss: 1×1
result: $r \times 2$

`colminmax(X, usemiss)`

X: $r \times c$
usemiss: 1×1
result: $2 \times c$

`minmax(X, usemiss)`

X: $r \times c$
usemiss: 1×1
result: 1×2

`rowmaxabs(A)`:

A: $r \times c$
result: $r \times 1$

`colmaxabs(A)`:

A: $r \times c$
result: $1 \times c$

Diagnostics

`row*()` functions return missing values for the corresponding minimum or maximum when the entire row contains missing.

`col*()` functions return missing values for the corresponding minimum or maximum when the entire column contains missing.

`min()` and `max()` return missing values when the entire matrix contains missing values.

Also see

[M-5] [minindex\(\)](#) — Indices of minimums and maximums

[M-4] [Mathematical](#) — Important mathematical functions

[M-4] [Utility](#) — Matrix utility functions

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).