

estat teffects — Decomposition of effects into total, direct, and indirect

Description
Remarks and examples

Menu
Stored results

Syntax
References

Options
Also see

Description

`estat teffects` is for use after `sem` but not `gsem`.

`estat teffects` reports direct, indirect, and total effects for each path (Sobel 1987), along with standard errors obtained by the delta method.

Menu

Statistics > SEM (structural equation modeling) > Testing and CIs > Direct and indirect effects

Syntax

```
estat teffects [ , options ]
```

<i>options</i>	Description
<code>compact</code>	do not display effects with no path
<code>standardized</code>	report standardized effects
<code>nolabel</code>	display <code>group</code> values, not labels
<code>nodirect</code>	do not display direct effects
<code>noindirect</code>	do not display indirect effects
<code>nototal</code>	do not display total effects
<code>display_<i>options</i></code>	control columns and column formats, row spacing, and display of omitted paths

`collect` is allowed; see [U] 11.1.10 Prefix commands.

Options

`compact` is a popular option. Consider the following model:

```
. sem (y1<-y2 x1) (y2<-x2)
```

`x2` has no direct effect on `y1` but does have an indirect effect. `estat teffects` formats all its effects tables the same way by default, so there will be a row for the direct effect of `x2` on `y1` just because there is a row for the indirect effect of `x2` on `y1`. The value reported for the direct effect, of course, will be 0. `compact` says to omit these unnecessary rows.

`standardized` reports effects in standardized form, but standard errors of the standardized effects are not reported.

`noLabel` is relevant only if estimation was with `sem`'s `group()` option and the group variable has a value label. Groups are identified by group value rather than label.

`nodirect`, `noindirect`, and `nototal` suppress the display of the indicated effect. The default is to display all effects.

display_options: `nocl`, `novalues`, `noomitted`, `vsquish`, `cformat(%fmt)`, `pformat(%fmt)`, `sformat(%fmt)`, and `no1stretch`; see [R] [Estimation options](#). Although `estat teffects` is not an estimation command, it allows these options.

Remarks and examples

[stata.com](http://www.stata.com)

See [SEM] [Example 7](#).

Direct effects are the path coefficients in the model.

Indirect effects are all mediating effects. For instance, consider

```
. sem ... (y1<-y2) (y1<-x2) (y2<-x3) ..., ...
```

The direct effect of `y2` on `y1` is the path coefficient (`y1<-y2`).

In this example, changes in `x3` affect `y1`, too. That is called the indirect effect and is the product of the path coefficients (`y2<-x3`) and (`y1<-y2`). If there were other paths in the model such that `y1` changed when `x3` changed, those effects would be added to the indirect effect as well. `estat teffects` reports total indirect effects.

The total effect is the sum of the direct and indirect effects.

When feedback loops are present in the model, such as

```
. sem ... (y1<-y2) (y1<-x2) (y2<-x3 y1) ..., ...
```

care must be taken when interpreting indirect effects. The feedback loop is when a variable indirectly affects itself, as `y1` does in the example; `y1` affects `y2` and `y2` affects `y1`. Thus in calculating the indirect effect, the sum has an infinite number of terms although the term values get smaller and smaller and thus usually converge to a finite result. It is important that you check nonrecursive models for stability; see [Bollen \(1989, 397\)](#) and see [SEM] [estat stable](#). Caution: if the model is unstable, the calculation of the indirect effect can sometimes still converge to a finite result.

Stored results

`estat teffects` stores the following in `r()`:

Scalars

<code>r(N_groups)</code>	number of groups
--------------------------	------------------

Matrices

<code>r(nobs)</code>	sample size for each group
<code>r(direct)</code>	direct effects
<code>r(indirect)</code>	indirect effects
<code>r(total)</code>	total effects
<code>r(V_direct)</code>	covariance matrix of the direct effects
<code>r(V_indirect)</code>	covariance matrix of the indirect effects
<code>r(V_total)</code>	covariance matrix of the total effects

estat teffects with the standardized option additionally stores the following in `r()`:

Matrices

<code>r(direct_std)</code>	standardized direct effects
<code>r(indirect_std)</code>	standardized indirect effects
<code>r(total_std)</code>	standardized total effects

References

- Bollen, K. A. 1989. *Structural Equations with Latent Variables*. New York: Wiley.
- Sobel, M. E. 1987. Direct and indirect effects in linear structural equation models. *Sociological Methods and Research* 16: 155–176. <https://doi.org/10.1177/0049124187016001006>.

Also see

- [SEM] [sem](#) — Structural equation model estimation command
- [SEM] [sem postestimation](#) — Postestimation tools for sem
- [SEM] [estat stable](#) — Check stability of nonrecursive system
- [SEM] [Methods and formulas for sem](#) — Methods and formulas for sem

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).