

collect style html — Collection styles for HTML files

Description
Options

Quick start
Remarks and examples

Menu
Stored results

Syntax
Also see

Description

`collect style html` specifies styles to be used when exporting a table from a collection to an HTML file.

`collect style html`, typed without any options, will clear the existing HTML appearance styles for the current collection.

Quick start

Specify that tables exported from the current collection to a HyperText Markup Language (HTML) file use tag `<th>` for header cells.

```
collect style html, usesth
```

Clear the current HTML appearance styles

```
collect style html
```

Menu

Statistics > Summaries, tables, and tests > Tables and collections > Collect styles > Styles for HTML

Syntax

Specify styles to be used when exporting a collection to an HTML file

```
collect style html [ , options ]
```

Clear existing HTML appearance styles

```
collect style html [ , name(cname) ]
```

options

Description

<code>name(<i>cname</i>)</code>	apply HTML styles to collection <i>cname</i>
<code>[no]bcollapse</code>	collapse adjacent cell borders
<code>[no]usesth</code>	use HTML tag <code><th></code> for header cells

Options

`name(cname)` specifies that the HTML styles be applied to collection *cname*.

When `name(cname)` is specified without any other options, HTML styles are cleared from collection *cname*.

The default in both cases is to apply the style changes to the current collection.

`bcollapse` and `nobcollapse` control whether adjacent cell borders are collapsed into a single border.

`bcollapse`, the default, specifies that `collect export` collapse adjacent cell borders into a single border.

`nobcollapse` specifies that `collect export` not collapse adjacent cell borders into a single border.

`useth` and `nouseth` control which HTML tag to use for header cells.

`useth` specifies that `collect export` use the HTML tag `<th>` for header cells.

`nouseth`, the default, specifies that `collect export` use the HTML tag `<td>` rather than `<th>` for header cells.

Remarks and examples

[stata.com](http://www.stata.com)

`collect style html` allows you to specify styles for the table that you will export to an HTML file with `collect export`. If you do not like the change you have made, you can clear the HTML appearance styles by typing the following:

```
. collect style html
```

This change will be applied to the current collection. To make this change for another collection, specify the collection name with the `name()` option.

Stored results

`collect style html` stores the following in `s()`:

```
Macros
      s(collection)  name of collection
```

Also see

[TABLES] [collect export](#) — Export table from a collection

[TABLES] [collect query](#) — Query collection style properties

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).