bayes: hetoprobit — Bayesian heteroskedastic ordered probit regression

Description | Quick start | Menu | Syntax
Remarks and examples | Stored results | Methods and formulas | Also see

Description

`bayes: hetoprobit` fits a Bayesian heteroskedastic ordered probit regression to an ordinal outcome; see [BAYES] **bayes** and [R] **hetoprobit** for details.

Quick start

Bayesian heteroskedastic ordered probit regression of `y` on `x1` and `x2`, using `z1` to model the variance, and using default normal priors for regression coefficients and log-standard-deviation coefficients and flat priors for cutpoints

```
bayes: hetoprobit y x1 x2, het(z1)
```

Use a standard deviation of 10 instead of 100 for the default normal priors

```
bayes, normalprior(10): hetoprobit y x1 x2, het(z1)
```

Use uniform priors for the slopes and a normal prior for the intercept of the main regression

```
bayes, prior({y: x1 x2}, uniform(-10,10)) ///
prior({y:_cons}, normal(0,10)): hetoprobit y x1 x2, het(z1)
```

Save simulation results to `simdata.dta`, and use a random-number seed for reproducibility

```
bayes, saving(simdata) rseed(123): ///
hetoprobit y x1 x2, het(z1)
```

Specify 20,000 Markov chain Monte Carlo (MCMC) samples, set length of the burn-in period to 5,000, and request that a dot be displayed every 500 simulations

```
bayes, mcmcsize(20000) burnin(5000) dots(500): ///
hetoprobit y x1 x2, het(z1)
```

In the above, request that the 90% highest posterior density (HPD) credible interval be displayed instead of the default 95% equal-tailed credible interval

```
bayes, clevel(90) hpd
```

Also see *Quick start* in [BAYES] **bayes** and *Quick start* in [R] **hetoprobit**.

Menu

Statistics > Ordinal outcomes > Bayesian regression > Heteroskedastic ordered probit regression

Syntax

```
bayes [ , bayesopts ] : hetoprobit depvar [ indepvars ] [ if ] [ in ] [ weight ] ,
    het(varlist[ , offset(varname_o) ]) [ options ]
```

options	Description
Model	
* `het(`*varlist*`[...])`	independent variables to model the variance and possible offset variable
`offset(`*varname*`)`	include *varname* in model with coefficient constrained to 1
Reporting	
display_options	control spacing, line width, and base and empty cells
`level(#)`	set credible level; default is `level(95)`

*`het()` is required. The full specification is `het(`*varlist* [`, offset(`*varname*$_o$`)`]`)`.
indepvars and *varlist* may contain factor variables; see **[U] 11.4.3 Factor variables**.
depvar, *indepvars*, and *varlist* may contain time-series operators; see **[U] 11.4.4 Time-series varlists**.
`fweights` are allowed; see **[U] 11.1.6 weight**.
`bayes: hetoprobit, level()` is equivalent to `bayes, clevel(): hetoprobit`.
For a detailed description of *options*, see *Options* in [R] **hetoprobit**.

bayesopts	Description
Priors	
* `normalprior(#)`	specify standard deviation of default normal priors for regression coefficients and log-standard-deviation coefficients; default is `normalprior(100)`
`prior(`*priorspec*`)`	prior for model parameters; this option may be repeated
`dryrun`	show model summary without estimation
Simulation	
`nchains(#)`	number of chains; default is to simulate one chain
`mcmcsize(#)`	MCMC sample size; default is `mcmcsize(10000)`
`burnin(#)`	burn-in period; default is `burnin(2500)`
`thinning(#)`	thinning interval; default is `thinning(1)`
`rseed(#)`	random-number seed
`exclude(`*paramref*`)`	specify model parameters to be excluded from the simulation results
Blocking	
* `blocksize(#)`	maximum block size; default is `blocksize(50)`
`block(`*paramref*`[ , `*blockopts*`])`	specify a block of model parameters; this option may be repeated
`blocksummary`	display block summary
* `noblocking`	do not block parameters by default

Initialization

initial(*initspec*)	specify initial values for model parameters with a single chain
init#(*initspec*)	specify initial values for #th chain; requires nchains()
initall(*initspec*)	specify initial values for all chains; requires nchains()
nomleinitial	suppress the use of maximum likelihood estimates as starting values
initrandom	specify random initial values
initsummary	display initial values used for simulation
* noisily	display output from the estimation command during initialization

Adaptation

adaptation(*adaptopts*)	control the adaptive MCMC procedure
scale(#)	initial multiplier for scale factor; default is scale(2.38)
covariance(*cov*)	initial proposal covariance; default is the identity matrix

Reporting

clevel(#)	set credible interval level; default is clevel(95)
hpd	display HPD credible intervals instead of the default equal-tailed credible intervals
eform[(*string*)]	report exponentiated coefficients and, optionally, label as *string*
batch(#)	specify length of block for batch-means calculations; default is batch(0)
saving(*filename*[, replace])	save simulation results to *filename*.dta
nomodelsummary	suppress model summary
chainsdetail	display detailed simulation summary for each chain
[no]dots	suppress dots or display dots every 100 iterations and iteration numbers every 1,000 iterations; default is nodots
dots(#[, every(#)])	display dots as simulation is performed
[no]show(*paramref*)	specify model parameters to be excluded from or included in the output
notable	suppress estimation table
noheader	suppress output header
title(*string*)	display *string* as title above the table of parameter estimates
display_options	control spacing, line width, and base and empty cells

Advanced

search(*search_options*)	control the search for feasible initial values
corrlag(#)	specify maximum autocorrelation lag; default varies
corrtol(#)	specify autocorrelation tolerance; default is corrtol(0.01)

* Starred options are specific to the bayes prefix; other options are common between bayes and bayesmh.

Options prior() and block() may be repeated.

priorspec and *paramref* are defined in [BAYES] **bayesmh**.

paramref may contain factor variables; see **[U] 11.4.3 Factor variables**.

collect is allowed; see **[U] 11.1.10 Prefix commands**.

See **[U] 20 Estimation and postestimation commands** for more capabilities of estimation commands.

Model parameters are regression coefficients {*depvar*:*indepvars*} for the main regression and {lnsigma:*varlist*} for the log-standard-deviation equation and cutpoints {cut1}, {cut2}, and so on. Use the dryrun option to see the definitions of model parameters prior to estimation.

Flat priors, flat, are used by default for cutpoints.

For a detailed description of *bayesopts*, see *Options* in [BAYES] **bayes**.

Remarks and examples

For a general introduction to Bayesian analysis, see [BAYES] **Intro**. For a general introduction to Bayesian estimation using an adaptive Metropolis–Hastings algorithm, see [BAYES] **bayesmh**. For remarks and examples specific to the `bayes` prefix, see [BAYES] **bayes**. For details about the estimation command, see [R] **hetoprobit**.

For a simple example of the `bayes` prefix, see *Introductory example* in [BAYES] **bayes**.

Stored results

See *Stored results* in [BAYES] **bayes**.

Methods and formulas

See *Methods and formulas* in [BAYES] **bayesmh**.

Also see

[BAYES] **bayes** — Bayesian regression models using the bayes prefix

[R] **hetoprobit** — Heteroskedastic ordered probit regression

[BAYES] **Bayesian postestimation** — Postestimation tools after Bayesian estimation

[BAYES] **Bayesian estimation** — Bayesian estimation commands

[BAYES] **Bayesian commands** — Introduction to commands for Bayesian analysis

[BAYES] **Intro** — Introduction to Bayesian analysis

[BAYES] **Glossary**

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on citing Stata documentation.