

bayes: melogit — Bayesian multilevel logistic regression

[Description](#)[Remarks and examples](#)[Quick start](#)[Stored results](#)[Menu](#)[Methods and formulas](#)[Syntax](#)[Also see](#)

Description

`bayes: melogit` fits a Bayesian multilevel logistic regression to a binary outcome; see [\[BAYES\] bayes](#) and [\[ME\] melogit](#) for details.

Quick start

Bayesian two-level logistic regression of `y` on `x1` and `x2` with random intercepts by `id`, using default normal priors for regression coefficients and default inverse-gamma prior for the variance of random intercepts

```
bayes: melogit y x1 x2 || id:
```

Use a standard deviation of 10 instead of 100 for the default normal priors

```
bayes, normalprior(10): melogit y x1 x2 || id:
```

Use uniform priors for the slopes and a normal prior for the intercept

```
bayes, prior({y: x1 x2}, uniform(-10,10)) ///
prior({y:_cons}, normal(0,10)): melogit y x1 x2 || id:
```

Save simulation results to `simdata.dta`, and use a random-number seed for reproducibility

```
bayes, saving(simdata) rseed(123): melogit y x1 x2 || id:
```

Specify 20,000 MCMC samples, set length of the burn-in period to 5,000, and request that a dot be displayed every 500 simulations

```
bayes, mcmcsample(20000) burnin(5000) dots(500): melogit y x1 x2 || id:
```

In the above, request that the 90% HPD credible interval be displayed instead of the default 95% equal-tailed credible interval

```
bayes, clevel(90) hpd
```

Display odds ratios instead of coefficients

```
bayes: melogit y x1 x2 || id: , or
```

Display odds ratios on replay

```
bayes, or
```

Also see [Quick start](#) in [\[BAYES\] bayes](#) and [Quick start](#) in [\[ME\] melogit](#).

Menu

Statistics > Multilevel mixed-effects models > Bayesian regression > Logistic regression

Syntax

```
bayes [ , bayesopts ] : melogit depvar fe_equation
      [ || re_equation ] [ || re_equation ... ] [ , options ]
```

where the syntax of *fe_equation* is

```
[ indepvars ] [ if ] [ in ] [ weight ] [ , fe_options ]
```

and the syntax of *re_equation* is one of the following:

for random coefficients and intercepts

```
levelvar: [ varlist ] [ , re_options ]
```

for random effects among the values of a factor variable

```
levelvar: R.varname
```

levelvar either is a variable identifying the group structure for the random effects at that level or is `_all`, representing one group comprising all observations.

<i>fe_options</i>	Description
Model	
noconstant	suppress constant term from the fixed-effects equation
offset (<i>varname</i>)	include <i>varname</i> in model with coefficient constrained to 1
asis	retain perfect predictor variables

<i>re_options</i>	Description
Model	
covariance (<i>vartype</i>)	variance–covariance structure of the random effects ; only structures independent , identity , and unstructured supported
noconstant	suppress constant term from the random-effects equation

<i>options</i>	Description
Model	
binomial (<i>varname</i> #)	set binomial trials if data are in binomial form
collinear	keep collinear variables
Reporting	
or	report odds ratios
notable	suppress coefficient table
noheader	suppress output header
nogroup	suppress table summarizing groups
display_options	control spacing, line width, and base and empty cells
level (#)	set credible level; default is <code>level(95)</code>

indepvars may contain factor variables; see [U] 11.4.3 **Factor variables**.

depvar, *indepvars*, and *varlist* may contain time-series operators; see [U] 11.4.4 **Time-series varlists**.

fweights are allowed; see [U] 11.1.6 **weight**.

bayes: *melogit*, *level()* is equivalent to *bayes*, *clevel()*: *melogit*.

For a detailed description of *options*, see *Options* in [ME] *melogit*.

<i>bayesopts</i>	Description
Priors	
* <u>normalprior</u> (#)	specify standard deviation of default normal priors for regression coefficients; default is <code>normalprior(100)</code>
* <u>igammaprior</u> (# #)	specify shape and scale of default inverse-gamma prior for variance components; default is <code>igammaprior(0.01 0.01)</code>
* <u>iwishartprior</u> (# [...])	specify degrees of freedom and, optionally, scale matrix of default inverse-Wishart prior for unstructured random-effects covariance
<u>prior</u> (<i>priorspec</i>)	prior for model parameters; this option may be repeated
<u>dryrun</u>	show model summary without estimation
Simulation	
<u>mcmcsize</u> (#)	MCMC sample size; default is <code>mcmcsize(10000)</code>
<u>burnin</u> (#)	burn-in period; default is <code>burnin(2500)</code>
<u>thinning</u> (#)	thinning interval; default is <code>thinning(1)</code>
<u>rseed</u> (#)	random-number seed
<u>exclude</u> (<i>paramref</i>)	specify model parameters to be excluded from the simulation results
<u>restubs</u> (<i>restub1 restub2 ...</i>)	specify stubs for random-effects parameters for all levels
Blocking	
* <u>blocksize</u> (#)	maximum block size; default is <code>blocksize(50)</code>
<u>block</u> (<i>paramref</i> [, <i>blockopts</i>])	specify a block of model parameters; this option may be repeated
<u>blocksummary</u>	display block summary
* <u>noblocking</u>	do not block parameters by default
Initialization	
<u>initial</u> (<i>initspec</i>)	initial values for model parameters
<u>nomleinitial</u>	suppress the use of maximum likelihood estimates as starting values
<u>initrandom</u>	specify random initial values
<u>initsummary</u>	display initial values used for simulation
* <u>noisily</u>	display output from the estimation command during initialization
Adaptation	
<u>adaptation</u> (<i>adaptopts</i>)	control the adaptive MCMC procedure
<u>scale</u> (#)	initial multiplier for scale factor; default is <code>scale(2.38)</code>
<u>covariance</u> (<i>cov</i>)	initial proposal covariance; default is the identity matrix

Reporting

<code>clevel(#)</code>	set credible interval level; default is <code>clevel(95)</code>
<code>hpd</code>	display HPD credible intervals instead of the default equal-tailed credible intervals
* or	report odds ratios
<code>eform[<i>(string)</i>]</code>	report exponentiated coefficients and, optionally, label as <i>string</i>
<code>remargl</code>	compute log marginal likelihood
<code>batch(#)</code>	specify length of block for batch-means calculations; default is <code>batch(0)</code>
<code>saving(filename[, replace])</code>	save simulation results to <i>filename.dta</i>
<code>nomodelsummary</code>	suppress model summary
<code>nomesummary</code>	suppress multilevel-structure summary
<code>[no]dots</code>	suppress dots or display dots every 100 iterations and iteration numbers every 1,000 iterations; default is <code>dots</code>
<code>dots(#[, every(#)])</code>	display dots as simulation is performed
<code>[no]show(paramref)</code>	specify model parameters to be excluded from or included in the output
<code>showeffects[<i>(ref)</i>]</code>	specify that all or a subset of random-effects parameters be included in the output
<code>melabel</code>	display estimation table using the same row labels as <code>melogit</code>
<code>nogroup</code>	suppress table summarizing groups
<code>notable</code>	suppress estimation table
<code>noheader</code>	suppress output header
<code>title(string)</code>	display <i>string</i> as title above the table of parameter estimates
<code>display_options</code>	control spacing, line width, and base and empty cells

Advanced

<code>search(search_options)</code>	control the search for feasible initial values
<code>corrlag(#)</code>	specify maximum autocorrelation lag; default varies
<code>corrctl(#)</code>	specify autocorrelation tolerance; default is <code>corrctl(0.01)</code>

* Starred options are specific to the `bayes` prefix; other options are common between `bayes` and `bayesmh`.

Options `prior()` and `block()` can be repeated.

`priorspec` and `paramref` are defined in [BAYES] `bayesmh`.

`paramref` may contain factor variables; see [U] 11.4.3 Factor variables.

See [U] 20 Estimation and postestimation commands for more capabilities of estimation commands.

Model parameters are regression coefficients `{depvar: indepvars}`, random effects `{rename}`, and either variance components `{rename:sigma2}` or, if option `covariance(unstructured)` is specified, matrix parameter `{restub:Sigma,matrix}`; see *Likelihood model* in [BAYES] `bayes` for how `renames` and `restub` are defined. Use the `dryrun` option to see the definitions of model parameters prior to estimation.

For a detailed description of `bayesopts`, see *Options* in [BAYES] `bayes`.

Remarks and examples

[stata.com](http://www.stata.com)

For a general introduction to Bayesian analysis, see [BAYES] `intro`. For a general introduction to Bayesian estimation using an adaptive Metropolis–Hastings algorithm, see [BAYES] `bayesmh`. For remarks and examples specific to the `bayes` prefix, see [BAYES] `bayes`. For details about the estimation command, see [ME] `melogit`.

For a simple example of the `bayes` prefix, see *Introductory example* in [BAYES] `bayes`. For multilevel examples, see *Multilevel models* in [BAYES] `bayes`.

Stored results

See *Stored results* in [BAYES] `bayesmh`.

Methods and formulas

See *Methods and formulas* in [BAYES] `bayesmh`.

Also see

[BAYES] `bayes` — Bayesian regression models using the `bayes` prefix

[ME] `melogit` — Multilevel mixed-effects logistic regression

[BAYES] `bayesian postestimation` — Postestimation tools for `bayesmh` and the `bayes` prefix

[BAYES] `bayesian estimation` — Bayesian estimation commands

[BAYES] `bayesian commands` — Introduction to commands for Bayesian analysis

[BAYES] `intro` — Introduction to Bayesian analysis

[BAYES] `Glossary`