

[Description](#)[Remarks and examples](#)[Quick start](#)[Stored results](#)[Menu](#)[Methods and formulas](#)[Syntax](#)[Also see](#)

Description

`bayes: xtprobit` fits a Bayesian panel-data random-effects probit model to a binary outcome; see [\[BAYES\] bayes](#) and [\[XT\] xtprobit](#) for details.

Quick start

Bayesian random-effects probit model of `y` on `x1` and `x2` with random intercepts by `id` (after `xtsetting` on panel variable `id`), using default normal priors for regression coefficients and default inverse-gamma prior for the variance of random intercepts

```
bayes: xtprobit y x1 x2
```

Use a standard deviation of 10 instead of 100 for the default normal priors

```
bayes, normalprior(10): xtprobit y x1 x2
```

Use a shape of 1 and a scale of 2 instead of values of 0.01 for the default inverse-gamma prior

```
bayes, igammaprior(1 2): xtprobit y x1 x2
```

Use uniform priors for the slopes and a normal prior for the intercept

```
bayes, prior({y: x1 x2}, uniform(-10,10)) ///  
prior({y: _cons}, normal(0,10)): xtprobit y x1 x2
```

Save simulation results to `simdata.dta`, and use a random-number seed for reproducibility

```
bayes, saving(simdata) rseed(123): xtprobit y x1 x2
```

Specify 20,000 Markov chain Monte Carlo (MCMC) samples, set length of the burn-in period to 5,000, and request that a dot be displayed every 500 simulations

```
bayes, mcmcsample(20000) burnin(5000) dots(500): xtprobit y x1 x2
```

In the above, request that the 90% highest posterior density (HPD) credible interval be displayed instead of the default 95% equal-tailed credible interval

```
bayes, clevel(90) hpd
```

Also see [Quick start](#) in [\[BAYES\] bayes](#) and [Quick start](#) in [\[XT\] xtprobit](#).

Menu

Statistics > Longitudinal/panel data > Binary outcomes > Bayesian regression > Probit regression

Syntax

bayes [, bayesopts] : xtprobit *depvar* [*indepvars*] [*if*] [*in*] [, options]

<i>options</i>	Description
Model	
<u>noconstant</u>	suppress constant term
<u>offset</u> (<i>varname</i>)	include <i>varname</i> in model with coefficient constrained to 1
<u>asis</u>	retain perfect predictor variables
Reporting	
<u>display_options</u>	control spacing, line width, and base and empty cells
<u>level</u> (#)	set credible level; default is level(95)
<p>A panel variable must be specified; see [XT] xtset.</p> <p><i>indepvars</i> may contain factor variables; see [U] 11.4.3 Factor variables.</p> <p><i>depvar</i> and <i>indepvars</i> may contain time-series operators; see [U] 11.4.4 Time-series varlists.</p> <p>bayes: xtprobit, level() is equivalent to bayes, clevel(): xtprobit.</p> <p>For a detailed description of options, see Options in [XT] xtprobit.</p>	
<i>bayesopts</i>	Description
Priors	
* <u>normalprior</u> (#)	specify standard deviation of default normal priors for regression coefficients; default is normalprior(100)
* <u>igammaprior</u> (# #)	specify shape and scale of default inverse-gamma prior for variance components; default is igammaprior(0.01 0.01)
<u>prior</u> (<i>priorspec</i>)	prior for model parameters; this option may be repeated
<u>dryrun</u>	show model summary without estimation
Simulation	
<u>nchains</u> (#)	number of chains; default is to simulate one chain
<u>mcmcsize</u> (#)	MCMC sample size; default is mcmcsize(10000)
<u>burnin</u> (#)	burn-in period; default is burnin(2500)
<u>thinning</u> (#)	thinning interval; default is thinning(1)
<u>rseed</u> (#)	random-number seed
<u>exclude</u> (<i>paramref</i>)	specify model parameters to be excluded from the simulation results
Blocking	
<u>block</u> (<i>paramref</i> [, <i>blockopts</i>])	specify a block of model parameters; this option may be repeated
<u>blocksummary</u>	display block summary
Initialization	
<u>initial</u> (<i>initspec</i>)	specify initial values for model parameters with a single chain
<u>init</u> #(<i>initspec</i>)	specify initial values for #th chain; requires nchains()
<u>initall</u> (<i>initspec</i>)	specify initial values for all chains; requires nchains()
<u>nomleinitial</u>	suppress the use of maximum likelihood estimates as starting values
<u>initrandom</u>	specify random initial values
<u>initsummary</u>	display initial values used for simulation
* <u>noisily</u>	display output from the estimation command during initialization

Adaptation

<code>adaptation(<i>adaptopts</i>)</code>	control the adaptive MCMC procedure
<code>scale(#)</code>	initial multiplier for scale factor; default is <code>scale(2.38)</code>
<code>covariance(cov)</code>	initial proposal covariance; default is the identity matrix

Reporting

<code>clevel(#)</code>	set credible interval level; default is <code>clevel(95)</code>
<code>hpd</code>	display HPD credible intervals instead of the default equal-tailed credible intervals
<code>eform(<i>string</i>)</code>	report exponentiated coefficients and, optionally, label as <i>string</i>
<code>remargl</code>	compute log marginal-likelihood; suppressed by default
<code>batch(#)</code>	specify length of block for batch-means calculations; default is <code>batch(0)</code>
<code>saving(filename[, replace])</code>	save simulation results to <i>filename.dta</i>
<code>nomodelsummary</code>	suppress model summary
<code>chainsdetail</code>	display detailed simulation summary for each chain
<code>[no]dots</code>	suppress dots or display dots every 100 iterations and iteration numbers every 1,000 iterations; default is <code>nodots</code>
<code>dots([#, every(#)])</code>	display dots as simulation is performed
<code>[no]show(<i>paramref</i>)</code>	specify model parameters to be excluded from or included in the output
<code>showeffects(<i>reref</i>)</code>	specify that all or a subset of random-effects parameters be included in the output
<code>notable</code>	suppress estimation table
<code>noheader</code>	suppress output header
<code>title(<i>string</i>)</code>	display <i>string</i> as title above the table of parameter estimates
<code>display_options</code>	control spacing, line width, and base and empty cells

Advanced

<code>search(<i>search_options</i>)</code>	control the search for feasible initial values
<code>corrlag(#)</code>	specify maximum autocorrelation lag; default varies
<code>corrtol(#)</code>	specify autocorrelation tolerance; default is <code>corrtol(0.01)</code>

* Starred options are specific to the `bayer` prefix; other options are common between `bayer` and `bayermh`.

Options `prior()` and `block()` may be repeated.

priorspec and *paramref* are defined in [BAYES] `bayermh`.

paramref may contain factor variables; see [U] 11.4.3 Factor variables.

`collect` is allowed; see [U] 11.1.10 Prefix commands.

See [U] 20 Estimation and postestimation commands for more capabilities of estimation commands.

Model parameters are regression coefficients `{depvar: indepvars}`, random effects `{U[panelvar]}` or simply `{U}`, and random-effects variance `{var_U}`. Use the `dryrun` option to see the definitions of model parameters prior to estimation.

For a detailed description of *bayeropts*, see *Options* in [BAYES] `bayer`.

Remarks and examples

For a general introduction to Bayesian analysis, see [BAYES] `Intro`. For a general introduction to Bayesian estimation using an adaptive Metropolis–Hastings algorithm, see [BAYES] `bayermh`. For remarks and examples specific to the `bayer` prefix, see [BAYES] `bayer`. For details about the estimation command, see [XT] `xtprobit`.

For a simple example of the bayes prefix, see *Introductory example* in [BAYES] **bayes**. Also see *Panel-data models* in [BAYES] **bayes**.

Stored results

See *Stored results* in [BAYES] **bayes**. In addition, bayes: xtprobit also stores the following results:

Macros

e(ivar)	variable denoting groups
e(redistrib)	distribution of random effects

Methods and formulas

See *Methods and formulas* in [BAYES] **bayesmh**.

Also see

[BAYES] **bayes** — Bayesian regression models using the bayes prefix

[XT] **xtprobit** — Random-effects and population-averaged probit models

[BAYES] **Bayesian postestimation** — Postestimation tools after Bayesian estimation

[BAYES] **Bayesian estimation** — Bayesian estimation commands

[BAYES] **Bayesian commands** — Introduction to commands for Bayesian analysis

[BAYES] **Intro** — Introduction to Bayesian analysis

[BAYES] **Glossary**

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).