

Postestimation commands

The following postestimation commands are available after `cmrologit`:

Command	Description
<code>contrast</code>	contrasts and ANOVA-style joint tests of parameters
<code>estat ic</code>	Akaike's, consistent Akaike's, corrected Akaike's, and Schwarz's Bayesian information criteria (AIC, CAIC, AICc, and BIC, respectively)
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance–covariance matrix of the estimators (VCE)
<code>estimates</code>	cataloging estimation results
<code>etable</code>	table of estimation results
<code>hausman</code>	Hausman's specification test
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of parameters
<code>linktest</code>	link test for model specification
<code>lrtest</code>	likelihood-ratio test
<code>margins</code>	marginal means, predictive margins, marginal effects, and average marginal effects
<code>marginsplot</code>	graph the results from margins (profile plots, interaction plots, etc.)
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of parameters
<code>predict</code>	probabilities, linear predictions and their SEs, etc.
<code>predictnl</code>	point estimates, standard errors, testing, and inference for generalized predictions
<code>pwcompare</code>	pairwise comparisons of parameters
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

predict

Description for predict

predict creates a new variable containing predictions such as probabilities, linear predictions, and standard errors.

Menu for predict

Statistics > Postestimation

Syntax for predict

```
predict [type] newvar [if] [in] [, statistic nooffset]
```

statistic	Description
Main	
pr	probability that alternatives are ranked first; the default
xb	linear prediction
stdp	standard error of the linear prediction

These statistics are available both in and out of sample; type `predict ... if e(sample) ...` if wanted only for the estimation sample.

`predict` omits missing values casewise if `cmrologit` used casewise deletion (the default); if `cmrologit` used alternativewise deletion (option `altwise`), `predict` uses alternativewise deletion.

Options for predict

Main

`pr`, the default, calculates the probability that alternatives are ranked first.

`xb` calculates the linear prediction.

`stdp` calculates the standard error of the linear prediction.

`nooffset` is relevant only if you specified `offset(varname)` for `cmrologit`. It modifies the calculations made by `predict` so that they ignore the offset variable; the linear prediction is treated as $\mathbf{x}_j\mathbf{b}$ rather than as $\mathbf{x}_j\mathbf{b} + \text{offset}_j$.

margins

Description for margins

`margins` estimates margins of response for linear predictions.

Menu for margins

Statistics > Postestimation

Syntax for margins

```
margins [marginlist] [ , options ]
margins [marginlist] , predict(statistic ...) [options]
```

<i>statistic</i>	Description
------------------	-------------

<code>xb</code>	linear prediction; the default
<code>pr</code>	not allowed with margins
<code>stdp</code>	not allowed with margins

Statistics not allowed with margins are functions of stochastic quantities other than $e(b)$.

Because `cmrologit` does not explicitly identify alternatives (that is, there is no alternatives variable), the alternative-specific features of [\[CM\] margins](#) do not apply to `cmrologit`. See [\[R\] margins](#) for the full syntax of margins available after `cmrologit`.

Remarks and examples

See [Comparing respondents](#) and [Clustered choice data](#) in [\[CM\] cmrologit](#) for examples of the use of `testparm`, an alternative to the `test` command.

See [Comparison of cmrologit and clogit](#) and [On reversals of rankings](#) in [\[CM\] cmrologit](#) for examples of the use of estimates.

See [Comparison of cmrologit and clogit](#) in [\[CM\] cmrologit](#) for an example of the use of `hausman`.

Also see

[\[CM\] cmrologit](#) — Rank-ordered logit choice model

[\[U\] 20 Estimation and postestimation commands](#)

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

