

`rmdir` — Remove directory

[Description](#)[Quick start](#)[Syntax](#)[Remarks and examples](#)[Also see](#)

Description

`rmdir` removes an empty directory (folder).

Quick start

Remove empty `myfolder` from the current working directory

```
rmdir myfolder
```

Remove `myfolder` from `C:\mydir` using Stata for Windows

```
rmdir c:\mydir\myfolder
```

Remove `myfolder` from `~/mydir` using Stata for Mac or Unix

```
rmdir ~/mydir/myfolder
```

Remove `my folder` from `C:\my dir` using Stata for Windows

```
rmdir "c:\my dir\my folder"
```

Syntax

```
rmdir directory_name
```

Double quotes may be used to enclose the directory name, and the quotes must be used if the directory name contains embedded blanks.

Remarks and examples

stata.com

Examples:

Windows

```
. rmdir myproj
. rmdir c:\projects\myproj
. rmdir "c:\My Projects\Project 1"
```

Mac and Unix

```
. rmdir myproj
. rmdir ~/projects/myproj
```

Also see

- [D] **cd** — Change directory
- [D] **copy** — Copy file from disk or URL
- [D] **dir** — Display filenames
- [D] **erase** — Erase a disk file
- [D] **mkdir** — Create directory
- [D] **shell** — Temporarily invoke operating system
- [D] **type** — Display contents of a file
- [U] **11.6 Filenaming conventions**

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

