

[Description](#)  
[Options](#)  
[Also see](#)

[Quick start](#)  
[Remarks and examples](#)

[Menu for estat](#)  
[Stored results](#)

[Syntax](#)  
[Methods and formulas](#)

## Description

`estat policy` displays the estimated policy matrix of the state-space form of a DSGE model.

## Quick start

Display the estimated policy matrix

```
estat policy
```

Same as above, but with 90% confidence intervals

```
estat policy, level(90)
```

## Menu for estat

Statistics > Postestimation

## Syntax

```
estat policy [ , compact post level(#) display_options ]
```

`collect` is allowed; see [\[U\] 11.1.10 Prefix commands](#).

## Options

`compact` reports only the coefficient values of the estimated policy matrix and displays these coefficients in matrix form.

`post` causes `estat policy` to behave like a Stata estimation (e-class) command. `estat policy` posts the policy matrix parameters along with the estimated variance–covariance matrix to `e()`, so you can treat the estimated policy matrix as you would results from any other estimation command.

`level(#)` specifies the confidence level, as a percentage, for confidence intervals. The default is `level(95)` or as set by `set level`; see [\[U\] 20.8 Specifying the width of confidence intervals](#).

*display\_options*: `nocl`, `nopvalues`, `cformat(%fmt)`, `pformat(%fmt)`, `sformat(%fmt)`, and `nolstretch`; see [\[R\] Estimation options](#).

## Remarks and examples

The policy matrix is part of the state-space form of a DSGE model. It specifies the model's control variables as a function of the model's state variables.

For examples, see [\[DSGE\] Intro 1](#), [\[DSGE\] Intro 3a](#), and [\[DSGE\] Intro 3c](#).

## Stored results

`estat policy` stores the following in `r()`:

Matrices

<code>r(policy)</code>	estimated policy matrix
<code>r(b)</code>	estimates
<code>r(V)</code>	variance–covariance matrix of the estimates

If `post` is specified, `estat policy` also stores the following in `e()`:

Macros

<code>e(properties)</code>	<code>b V</code>
----------------------------	------------------

Matrices

<code>e(policy)</code>	estimated policy matrix
<code>e(b)</code>	estimates
<code>e(V)</code>	variance–covariance matrix of the estimates

## Methods and formulas

Entries in the policy matrix  $\mathbf{G}$  are functions of the structural parameter vector  $\theta$ . Standard errors for  $\widehat{\mathbf{G}}$  are calculated using the delta method.

## Also see

[\[DSGE\] dsge](#) — Linear dynamic stochastic general equilibrium models

[\[DSGE\] dsge postestimation](#) — Postestimation tools for `dsge`

[\[DSGE\] dsge nl](#) — Nonlinear dynamic stochastic general equilibrium models

[\[DSGE\] dsge nl postestimation](#) — Postestimation tools for `dsge nl`

[\[DSGE\] Intro 1](#) — Introduction to DSGEs

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

