

## Description

`type` lists the contents of a file stored on disk. This command is similar to the Windows `type` command and the Unix `more(1)` or `pg(1)` commands.

In Stata for Mac and Stata for Unix, `cat` is a synonym for `type`.

On all platforms, Stata understands a leading “~” as an abbreviation for the home directory.

## Quick start

Display contents of `myfile.txt` in the Results window

```
type myfile.txt
```

Same as above, but display `myfile.txt` saved in `~\mydir\mysubdir` using Stata for Windows

```
type ~\mydir\mysubdir\myfile.txt
```

Same as above, but using Stata for Mac or Unix

```
type ~/mydir/mysubdir/myfile.txt
```

Display contents of `my file.txt`

```
type "my file.txt"
```

Display the first 20 lines of `myfile.txt`

```
type myfile.txt, lines(20)
```

## Syntax

```
type ["filename"] [ , options ]
```

Note: Double quotes must be used to enclose *filename* if the name contains blanks.

<i>options</i>	Description
<code>asis</code>	show file as is; default is to display files with suffix <code>.smcl</code> or <code>.sthlp</code> as SMCL
<code>smcl</code>	display file as SMCL; default for files with suffix <code>.smcl</code> or <code>.sthlp</code>
<code>showtabs</code>	display tabs as <T> rather than being expanded
<code>starbang</code>	list lines in the file that begin with “*!”
<code>lines(#)</code>	list first # lines

## Options

`asis` specifies that the file be shown exactly as it is. The default is to display files with the suffix `.smcl` or `.sthlp` as SMCL, meaning that the SMCL directives are interpreted and properly rendered. Thus `type` can be used to look at files created by the `log using` command.

`smcl` specifies that the file be displayed as SMCL, meaning that the SMCL directives are interpreted and properly rendered. This is the default for files with the suffix `.smcl` or `.sthlp`.

`showtabs` requests that any tabs be displayed as `<T>` rather than being expanded.

`starbang` lists only the lines in the specified file that begin with the characters “\*!”. Such comment lines are typically used to indicate the version number of ado-files, class files, etc. `starbang` may not be used with SMCL files.

`lines(#)` lists the first # lines of a file. `lines()` is ignored if the file is displayed as SMCL or if # is less than or equal to 0.

## Remarks and examples

### ► Example 1

We have raw data containing the level of Lake Victoria Nyanza and the number of sunspots during the years 1902–1921 stored in a file called `sunspots.raw`. We want to read this dataset into Stata by using `infile`, but we cannot remember the order in which we entered the variables. We can find out by using the `type` command:

```
. type sunspots.raw
1902 -10   5   1903  13 24   1904  18 42
1905  15  63   1906  29 54   1907  21 62
1908  10  49   1909   8 44   1910   1 19
1911  -7   6   1912 -11  4   1913  -3  1
1914  -2  10   1915   4 47   1916  15 57
1917  35 104   1918  27 81   1919   8 64
1920   3  38   1921  -5 25
```

Looking at this output, we now remember that the variables are entered year, level, and number of sunspots. We can read this dataset by typing `infile year level spots using sunspots`.

If we wanted to see the tabs in `sunspots.raw`, we could type

```
. type sunspots.raw, showtabs
1902 -10   5<T>1903  13 24<T>1904  18 42
1905  15  63<T>1906  29 54<T>1907  21 62
1908  10  49<T>1909   8 44<T>1910   1 19
1911  -7   6<T>1912 -11  4<T>1913  -3  1
1914  -2  10<T>1915   4 47<T>1916  15 57
1917  35 104<T>1918  27 81<T>1919   8 64
1920   3  38<T>1921  -5 25
```

## ► Example 2

In a previous Stata session, we typed `log` using `myres` and created `myres.smcl`, containing our results. We can use `type` to list the log:

```
. type myres.smcl
```

---

```

      name: <unnamed>
      log:  /work/joe/dof/myres.smcl
    log type: smcl
   opened on: 20 Jan 2025, 15:37:48

. use lbw
(Hosmer & Lemeshow data)

. logistic low age lwt i.race smoke ptl ht ui
Logistic regression
                                     Number of obs   =       189
                                     LR chi2(8)         =       33.22
                                     Prob > chi2        =       0.0001
                                     Pseudo R2         =       0.1416

Log likelihood =   -100.724
(output omitted)

. estat gof
Logistic model for low, goodness-of-fit test
(output omitted)

. log close
      name: <unnamed>
      log:  /work/joe/dof/myres.smcl
    log type: smcl
   closed on: 20 Jan 2025, 15:38:30
```

---

We could also use `view` to look at the log; see [\[R\] view](#).

◀

## Also see

[\[D\] cd](#) — Change directory

[\[D\] copy](#) — Copy file from disk or URL

[\[D\] dir](#) — Display filenames

[\[D\] erase](#) — Erase a disk file

[\[D\] mkdir](#) — Create directory

[\[D\] rmdir](#) — Remove directory

[\[D\] shell](#) — Temporarily invoke operating system

[\[P\] viewsource](#) — View source code

[\[R\] translate](#) — Print and translate logs

[\[R\] view](#) — View files and logs

### [\[U\] 11.6 Filenaming conventions](#)

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

