

**estat lcp**rob — Latent class marginal probabilities
[Description](#)[Remarks and examples](#)[Menu for estat](#)[Stored results](#)[Syntax](#)[Also see](#)[Options](#)

## Description

`estat lcp`rob reports a table of the marginal predicted latent class probabilities.

`marginsplot` can be used after `estat lcp`rob to plot the marginal predicted latent class probabilities.

## Menu for estat

Statistics > Postestimation

## Syntax

```
estat lcp
```

rob [ , *options* ]

<i>options</i>	Description
<code>classpr</code>	latent class probability; the default
<code>classposteriorpr</code>	posterior latent class probability
<code>nose</code>	do not estimate SEs
<code>post</code>	post margins and their VCE as estimation results
<code>display_options</code>	control column formats, row spacing, and line width

`collect` is allowed; see [U] [11.1.10 Prefix commands](#).

## Options

`classpr`, the default, calculates marginal predicted probabilities for each latent class.

`classposteriorpr` calculates marginal predicted posterior probabilities for each latent class. The posterior probabilities are a function of the latent-class predictors and the fitted outcome densities.

`nose` suppresses calculation of the VCE and standard errors.

`post` causes `estat lcp`rob to behave like a Stata estimation (`e-class`) command. `estat lcp`rob posts the vector of estimated margins along with the estimated variance–covariance matrix to `e()`, so you can treat the estimated margins just as you would results from any other estimation command.

`display_options`: `vsquish`, `fwrap(#)`, `fwrapon(style)`, `cformat(%fmt)`, `pformat(%fmt)`, `sformat(%fmt)`, and `nolstretch`.

## Remarks and examples

`estat lcprob` is illustrated in [\[FMM\] Example 1a](#), [\[FMM\] Example 2](#), and [\[FMM\] Example 3](#).

## Stored results

`estat lcprob` stores the following in `r()`:

### Scalars

`r(N)` number of observations

### Macros

`r(title)` title in output

### Matrices

`r(b)` estimates

`r(V)` variance–covariance matrix of the estimates

`r(table)` matrix containing the margins with their standard errors, test statistics, *p*-values, and confidence intervals

`estat lcprob` with the `post` option also stores the following in `e()`:

### Scalars

`e(N)` number of observations

### Macros

`e(title)` title in output

`e(classposteriorpr)` `classposteriorpr` or empty

`e(properties)` `b V`

### Matrices

`e(b)` estimates

`e(V)` variance–covariance matrix of the estimates

## Also see

[\[FMM\] fmm](#) — Finite mixture models using the `fmm` prefix

[\[FMM\] fmm intro](#) — Introduction to finite mixture models

[\[FMM\] fmm postestimation](#) — Postestimation tools for `fmm`