

**fmm: tpoisson** — Finite mixtures of truncated Poisson regression models

[Description](#)[Remarks and examples](#)[Quick start](#)[Stored results](#)[Menu](#)[Methods and formulas](#)[Syntax](#)[Also see](#)

## Description

`fmm: tpoisson` fits mixtures of truncated Poisson regression models; see [\[FMM\] fmm](#) and [\[R\] tpoisson](#) for details.

## Quick start

Mixture of two truncated Poisson distributions with default truncation point at 0

```
fmm 2: tpoisson y
```

Mixture of two truncated Poisson regression models of `y` on `x1` and `x2` with truncation at 0

```
fmm 2: tpoisson y x1 x2
```

As above, but with truncation at 3

```
fmm 2: tpoisson y x1 x2, ll(3)
```

With class probabilities depending on `z1` and `z2`

```
fmm 2, lcp(rob(z1 z2)): tpoisson y x1 x2
```

With robust standard errors

```
fmm 2, vce(robust): tpoisson y x1 x2
```

Constrain coefficients on `x1` and `x2` to be equal across classes

```
fmm 2, lcinvariant(coef): tpoisson y x1 x2
```

## Menu

Statistics > FMM (finite mixture models) > Count outcomes > Truncated Poisson regression

## Syntax

### Basic syntax

```
fmm #: tpoisson depvar [indepvars] [, options]
```

### Full syntax

```
fmm # [if] [in] [weight] [, fmmopts]: tpoisson depvar [indepvars] [, options]
```

where # specifies the number of class models.

<i>options</i>	Description
----------------	-------------

---

### Model

<b>noconstant</b>	suppress the constant term
<b>ll</b> ( <i>varname</i>   #)	truncation point; default value is ll(0), zero truncation
<b>exposure</b> ( <i>varname<sub>e</sub></i> )	include ln( <i>varname<sub>e</sub></i> ) in model with coefficient constrained to 1
<b>offset</b> ( <i>varname<sub>o</sub></i> )	include <i>varname<sub>o</sub></i> in model with coefficient constrained to 1

---

*indepvars* may contain factor variables; see [U] [11.4.3 Factor variables](#).

*depvar* and *indepvars* may contain time-series operators; see [U] [11.4.4 Time-series varlists](#).

For a detailed description of *options*, see [Options](#) in [R] [tpoisson](#).

<i>fmmopts</i>	Description
Model	
<code>lcinvariant(<i>pclassname</i>)</code>	specify parameters that are equal across classes; default is <code>lcinvariant(none)</code>
<code>lcprob(<i>varlist</i>)</code>	specify independent variables for class probabilities
<code>lclabel(<i>name</i>)</code>	name of the categorical latent variable; default is <code>lclabel(Class)</code>
<code>lcbase(#)</code>	base latent class
<code>constraints(<i>constraints</i>)</code>	apply specified linear constraints

## SE/Robust

`vce(vcetype)` *vcetype* may be `oim`, `opg`, `robust`, or `cluster clustvar`

## Reporting

`level(#)` set confidence level; default is `level(95)`  
`nocnsreport` do not display constraints  
`noheader` do not display header above parameter table  
`nodvheader` do not display dependent variables information in the header  
`notable` do not display parameter table  
*display\_options* control columns and column formats, row spacing, line width, display of omitted variables and base and empty cells, and factor-variable labeling

## Maximization

*maximize\_options* control the maximization process  
`startvalues(svmethod)` method for obtaining starting values; default is `startvalues(factor)`  
`emopts(maxopts)` control EM algorithm for improved starting values  
`noestimate` do not fit the model; show starting values instead  
`collinear` keep collinear variables  
`coeflegend` display legend instead of statistics

*varlist* may contain factor variables; see [U] 11.4.3 Factor variables.

`by`, `collect`, `statsby`, and `svy` are allowed; see [U] 11.1.10 Prefix commands.

`vce()` and weights are not allowed with the `svy` prefix; see [SVY] `svy`.

`fweights`, `iweights`, and `pweights` are allowed; see [U] 11.1.6 `weight`.

`collinear` and `coeflegend` do not appear in the dialog box.

See [U] 20 Estimation and postestimation commands for more capabilities of estimation commands.

For a detailed description of *fmmopts*, see *Options* in [FMM] `fmm`.

<i>pclassname</i>	Description
<code>cons</code>	intercepts and cutpoints
<code>coef</code>	fixed coefficients
<code>errvar</code>	covariances of errors
<code>scale</code>	scaling parameters
<code>all</code>	all the above
<code>none</code>	none of the above; the default

## Remarks and examples

For a general introduction to finite mixture models, see [FMM] [fmm intro](#). For general information about truncated Poisson regression, see [R] [tpoisson](#). For examples using `fmm`, see examples in [Contents](#).

## Stored results

See *Stored results* in [FMM] [fmm](#).

## Methods and formulas

See *Methods and formulas* in [FMM] [fmm](#).

## Also see

[FMM] [fmm](#) — Finite mixture models using the `fmm` prefix

[FMM] [fmm intro](#) — Introduction to finite mixture models

[FMM] [fmm postestimation](#) — Postestimation tools for `fmm`

[FMM] [Glossary](#)

[R] [tpoisson](#) — Truncated Poisson regression

[SVY] [svy estimation](#) — Estimation commands for survey data