

Contents

<code>tin(d_1, d_2)</code>	<i>true</i> if $d_1 \leq t \leq d_2$, where t is the time variable previously <code>tsset</code>
<code>twithin(d_1, d_2)</code>	<i>true</i> if $d_1 < t < d_2$, where t is the time variable previously <code>tsset</code>

Functions

`tin(d_1, d_2)`

Description: *true* if $d_1 \leq t \leq d_2$, where t is the time variable previously `tsset`

You must have previously `tsset` the data to use `tin()`; see [TS] [tsset](#). When you `tsset` the data, you specify a time variable, t , and the format on t states how it is recorded. You type d_1 and d_2 according to that format.

If t has a `%tc` format, you could type `tin(5jan1992 11:15, 14apr2002 12:25)`.

If t has a `%td` format, you could type `tin(5jan1992, 14apr2002)`.

If t has a `%tw` format, you could type `tin(1985w1, 2002w15)`.

If t has a `%tm` format, you could type `tin(1985m1, 2002m4)`.

If t has a `%tq` format, you could type `tin(1985q1, 2002q2)`.

If t has a `%th` format, you could type `tin(1985h1, 2002h1)`.

If t has a `%ty` format, you could type `tin(1985, 2002)`.

If t has a `%tb` format, you could type `tin(5jan1992, 14apr2002)`. This will work as expected even if the arguments of `tin()` are not business days.

Otherwise, t is just a set of integers, and you could type `tin(12, 38)`.

The details of the `%t` format do not matter. If your t is formatted `%tdmm/dd/yy` so that `5jan1992` displays as `1/5/92`, you would still type the date in day–month–year order: `tin(5jan1992, 14apr2002)`.

Domain d_1 : date or time literals or strings recorded in units of t previously `tsset` or blank to indicate no minimum date

Domain d_2 : date or time literals or strings recorded in units of t previously `tsset` or blank to indicate no maximum date

Range: 0 and 1, $1 \Rightarrow true$

`twwithin(d1, d2)`

Description: *true* if $d_1 < t < d_2$, where t is the time variable previously `tsset`

See `tin()` above; `twwithin()` is similar, except the range is exclusive.

Domain d_1 : date or time literals or strings recorded in units of t previously `tsset` or blank to indicate no minimum date

Domain d_2 : date or time literals or strings recorded in units of t previously `tsset` or blank to indicate no maximum date

Range: 0 and 1, $1 \Rightarrow true$

Also see

[FN] [Functions by category](#)

[D] [egen](#) — Extensions to generate

[D] [generate](#) — Create or change contents of variable

[U] [13.3 Functions](#)

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).